

环保物料

The technical drawing illustrates a single housing component from three perspectives: top, side, and front. The top view shows a rectangular base with three mounting holes spaced at $A \pm 0.20$, with a pitch of 3.0. The side view indicates a total height of 17.20 and a base width of 5.35. The front view shows a profile with a top width of 4.0, a central slot width of 2.50, and a bottom flange height of 8.45. A large diagonal watermark "KD NEW ENERGY" is overlaid across the center of the drawing.

技术参数 SPECIFICATIONS

- ◆间距: 3.0 Pitch:3.0
- ◆适用线规: AWG#20-#24
Applicable Wire:AWG#20-#24
- ◆额定电压: AC, DC, 250V (有效值)
Voltage rating: AC, DC, 250V(rms)
- ◆额定电流: 5A, AC, DC
Current rating:5A, AC, DC
- ◆耐压值: 1500V AC/minute
Withstand voltage:1500V AC/minute
- ◆工作温度 : -40℃~+105℃
Working Temp:-40℃~+105℃
- ◆绝缘电阻 : $\geq 100\text{M}\Omega$
Insulation resistance: $\geq 1000\text{M}\Omega$
- ◆接触电阻: $\leq 10\text{m}\Omega$
Contact resistance: $\leq 10\text{m}\Omega$

材料 MATERIAL

- ◆绝缘体: 尼龙66, UL94-0
Insulator:Nylon66 UL94-0

线数 Poles	尺寸 Dimensions(mm)	
	A	B
2	3.0	6.85
3	6.0	9.85
4	9.0	12.85
5	12.0	15.85
6	15.0	18.85
7	18.0	21.85
8	21.0	24.85
9	24.0	27.85
10	27.0	30.85
11	30.0	33.85
12	33.0	36.85

		GENERAL TOLERANCES		SCALE:	NAME	DATE
		LINEAR	ANGLES	1:1		
		0.0 ± 0.25	$X^\circ \text{ REF} \pm 6^\circ$	APPROVED		
A0	新图面发行	2018.07.28	UNIT: MM	DESIGNER		
REV.	REVISION RECORD	DATE	SIZE: A4	DRAWN	肖丽娟	2018.07.28
			0.000 ± 0.08			
			$X^\circ X' \pm 2^\circ$			

东莞市康导新能源科技有限公司
DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD
公司网址: www.dgkoonne.cn 公司电话: 0769-85337633
邮 箱: 2850175966@qq.com 公司传真: 0769-85392827

PART. NO: 3020E-1×XX
DWG. NO:
REV: AO SHEET: 1/1

TITLE: 3.00mm pitch Single Housing

- ◆间距: 3.0 Pitch:3.0
- ◆适用线规: AWG#20-#24
Applicable Wire:AWG#20-#24
- ◆额定电压: AC,DC, 250V (有效值)
Voltage rating: AC,DC, 250V(rms)
- ◆额定电流: 5A, AC, DC
Current rating:5A, AC, DC
- ◆耐压值: 1500V AC/minute
Withstand voltage:1500V AC/minute
- ◆工作温度: -40℃~+105℃
Working Temp:-40℃~+105℃
- ◆绝缘电阻: $\geq 100\text{M}\Omega$
Insulation resistance: $\geq 1000\text{M}\Omega$
- ◆接触电阻: $\leq 10\text{m}\Omega$
Contact resistance: $\leq 10\text{m}\Omega$

◆绝缘体：尼龙66, UL94-0
Insulator: Nylon66 UL94-0

线数 Poles	尺寸 Dimensions (mm)	
	A	B
2	3.0	6.85
3	6.0	9.85
4	9.0	12.85
5	12.0	15.85
6	15.0	18.85
7	18.0	21.85
8	21.0	24.85
9	24.0	27.85
10	27.0	30.85
11	30.0	33.85
12	33.0	36.85

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	 东莞市康号新能源科技有限公司 DONGGUAN KD NEW ENERGY TECHNOLOGY CO., LTD 公司网址: www.dgoonne.cn 公司电话: 0769-85337633 邮 箱: 2850175888@qq.com 公司传真: 0769-85392827	PART. NO: 3020E-1×XX		
				LINEAR	ANGLES	APPROVED					DWG. NO:	
				0.0±0.25	X° REF±6°	DESIGNER						
A0	新图面发行	2018.07.28	UNIT: MM	0.00±0.15	X° ±3°				TITLE:			
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	肖丽娟	2018.07.28	3.00mm pitch Single Housing			
									REV: A0	SHEET: 1/1		

 **东莞市康源新能源科技有限公司**
DONGGUAN KD NEW ENERGY TECHNOLOGY CO., LTD

公司地址: www.dgoonne.cn 公司电话: 0769-85337633
传 真: 286017588@qq.com 公司传真: 0769-85392827

PART. NO: 3020E-1×XX

DWG. NO:

REV: A0	SHEET: 1 / 1
---------	--------------