

	1	2	3	4	5	6	7	8																																																																		
A	环保物料		技术参数 SPECIFICATIONS ◆间距: 3.0 Pitch:3.0 ◆适用线规: AWG#20-#24 Applicable Wire:AWG#20-#24 ◆额定电压: AC,DC, 250V (有效值) Voltage rating: AC, DC, 250V(rms) ◆额定电流: 5A, AC, DC Current rating:5A, AC, DC ◆耐压值: 1500V AC/minute Withstand voltage:1500V AC/minute ◆工作温度 : -40℃~+105℃ Working Temp:-40℃~+105℃ ◆绝缘电阻 : ≥100MΩ Insulation resistance:≥1000MΩ ◆接触电阻: ≤10mΩ Contact resistance:≤10mΩ 材料 MATERIAL ◆绝缘体: 尼龙66, UL94-0 Insulator:Nylon66 UL94-0 <table border="1"> <thead> <tr> <th>线数 Poles</th><th colspan="2">尺寸 Dimensions(mm)</th></tr> <tr> <th></th><th>A</th><th>B</th></tr> </thead> <tbody> <tr><td>2</td><td>3.0</td><td>6.85</td></tr> <tr><td>3</td><td>6.0</td><td>9.85</td></tr> <tr><td>4</td><td>9.0</td><td>12.85</td></tr> <tr><td>5</td><td>12.0</td><td>15.85</td></tr> <tr><td>6</td><td>15.0</td><td>18.85</td></tr> <tr><td>7</td><td>18.0</td><td>21.85</td></tr> <tr><td>8</td><td>21.0</td><td>24.85</td></tr> <tr><td>9</td><td>24.0</td><td>27.85</td></tr> <tr><td>10</td><td>27.0</td><td>30.85</td></tr> <tr><td>11</td><td>30.0</td><td>33.85</td></tr> <tr><td>12</td><td>33.0</td><td>36.85</td></tr> </tbody> </table>						线数 Poles	尺寸 Dimensions(mm)			A	B	2	3.0	6.85	3	6.0	9.85	4	9.0	12.85	5	12.0	15.85	6	15.0	18.85	7	18.0	21.85	8	21.0	24.85	9	24.0	27.85	10	27.0	30.85	11	30.0	33.85	12	33.0	36.85																											
线数 Poles	尺寸 Dimensions(mm)																																																																									
	A	B																																																																								
2	3.0	6.85																																																																								
3	6.0	9.85																																																																								
4	9.0	12.85																																																																								
5	12.0	15.85																																																																								
6	15.0	18.85																																																																								
7	18.0	21.85																																																																								
8	21.0	24.85																																																																								
9	24.0	27.85																																																																								
10	27.0	30.85																																																																								
11	30.0	33.85																																																																								
12	33.0	36.85																																																																								
B																																																																										
C																																																																										
D																																																																										
E																																																																										
F																																																																										
G																																																																										
H	<table border="1"> <tr> <td></td><td></td><td></td><td rowspan="3"></td><td colspan="2">GENERAL TOLERANCES</td><td>SCALE: 1:1</td><td>NAME</td><td>DATE</td><td rowspan="3"> 东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD. 公司地址: www.dgoonne.cn 公司电话: 0769-85337633 邮 箱: 2850175966@qq.com 公司传真: 0769-85392627 </td><td>PART. NO:</td><td colspan="2">3025-1×XX</td></tr> <tr> <td></td><td></td><td></td><td>LINEAR</td><td>ANGLES</td><td>APPROVED</td><td></td><td></td><td>DWG. NO:</td><td colspan="2"></td></tr> <tr> <td></td><td></td><td></td><td>0.0±0.25</td><td>X° REF±6°</td><td>DESIGNER</td><td></td><td></td><td>REV:</td><td>AO</td><td>SHEET: 1/1</td></tr> <tr> <td></td><td>AO</td><td>新图面发行</td><td>2018.07.28</td><td>UNIT: MM</td><td>0.00±0.15</td><td>X° ±3°</td><td></td><td></td><td>TITLE:</td><td colspan="3">3.00mm pitch Single Housing</td></tr> <tr> <td></td><td>REV.</td><td>REVISION RECORD</td><td>DATE</td><td>SIZE: A4</td><td>0.000±0.08</td><td>X° X'±2°</td><td>DRAWN</td><td>肖丽娟</td><td>2018.07.28</td><td colspan="3" rowspan="2"></td></tr> </table>																	GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD. 公司地址: www.dgoonne.cn 公司电话: 0769-85337633 邮 箱: 2850175966@qq.com 公司传真: 0769-85392627	PART. NO:	3025-1×XX					LINEAR	ANGLES	APPROVED			DWG. NO:						0.0±0.25	X° REF±6°	DESIGNER			REV:	AO	SHEET: 1/1		AO	新图面发行	2018.07.28	UNIT: MM	0.00±0.15	X° ±3°			TITLE:	3.00mm pitch Single Housing				REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	肖丽娟	2018.07.28			
				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD. 公司地址: www.dgoonne.cn 公司电话: 0769-85337633 邮 箱: 2850175966@qq.com 公司传真: 0769-85392627	PART. NO:	3025-1×XX																																																															
				LINEAR	ANGLES	APPROVED				DWG. NO:																																																																
				0.0±0.25	X° REF±6°	DESIGNER				REV:	AO	SHEET: 1/1																																																														
	AO	新图面发行	2018.07.28	UNIT: MM	0.00±0.15	X° ±3°			TITLE:	3.00mm pitch Single Housing																																																																
	REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	肖丽娟	2018.07.28																																																																	
	1	2	3	4	5	6	7	8																																																																		

- ◆间距: 3.0 Pitch:3.0
- ◆适用线规: AWG#20-#24
Applicable Wire:AWG#20-#24
- ◆额定电压: AC, DC, 250V (有效值)
Voltage rating: AC, DC, 250V (rms)
- ◆额定电流: 5A, AC, DC
Current rating:5A, AC, DC
- ◆耐压值: 1500V AC/minute
Withstand voltage:1500V AC/minute
- ◆工作温度: -40℃~+105℃
Working Temp:-40℃~+105℃
- ◆绝缘电阻: $\geq 100\text{M}\Omega$
Insulation resistance: $\geq 1000\text{M}\Omega$
- ◆接触电阻: $\leq 10\text{m}\Omega$
Contact resistance: $\leq 10\text{m}\Omega$

◆绝缘体：尼龙66, UL94-0
Insulator: Nylon66 UL94-0

线数 Poles	尺寸 Dimensions (mm)	
	A	B
2	3.0	6.85
3	6.0	9.85
4	9.0	12.85
5	12.0	15.85
6	15.0	18.85
7	18.0	21.85
8	21.0	24.85
9	24.0	27.85
10	27.0	30.85
11	30.0	33.85
12	33.0	36.85

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	东莞市康号新能源科技有限公司 DONGGUAN KD NEW ENERGY TECHNOLOGY CO., LTD 公司网址: www.dgkonne.cn 公司电话: 0769-85337633 邮 箱: 2850175888@qq.com 公司传真: 0769-85302827	PART. NO: 3025-1×XX	
				LINEAR	ANGLES					APPROVED	
				0.0±0.25	X° REF±6°						
A0	新图面发行	2018.07.28	UNIT: MM	0.00±0.15	X° ±3°	DESIGNER			TITLE: 3.00mm pitch Single Housing	DWG. NO:	
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	肖丽娟	2018.07.28		REV: A0	SHEET: 1/1