

	1	2	3	4	5	6	7	8																																																																						
A	环保物料																																																																													
B	P.C.B LAYOUT				技术参数 SPECIFICATIONS ◆间距: 3.0 Pitch:3.0 ◆适用线规: AWG#20-#24 Applicable Wire:AWG#20-#24 ◆额定电压: AC, DC, 250V (有效值) Voltage rating: AC,DC, 250V(rms) ◆额定电流: 5A, AC, DC Current rating:5A, AC, DC ◆耐压值: 1500V AC/minute Withstand voltage:1500V AC/minute ◆工作温度 : -40℃~+105℃ Working Temp:-40℃~+105℃ ◆绝缘电阻 : ≥100MΩ Insulation resistance:≥1000MΩ ◆接触电阻: ≤10mΩ Contact resistance:≤10mΩ 材料 MATERIAL ◆绝缘体: 尼龙66, UL94-0 Insulator:Nylon66 UL94-0 ◆接触针:黄铜 Contact PIN: Brass																																																																									
C																																																																														
D																																																																														
E					<table border="1"><thead><tr><th>线数 Poles</th><th colspan="2">尺寸 Dimensions(mm)</th></tr><tr><th></th><th>A</th><th>B</th></tr></thead><tbody><tr><td>2x1</td><td>N/A</td><td>6.7</td></tr><tr><td>2x2</td><td>3.0</td><td>9.7</td></tr><tr><td>2x3</td><td>6.0</td><td>12.7</td></tr><tr><td>2x4</td><td>9.0</td><td>15.7</td></tr><tr><td>2x5</td><td>12.0</td><td>18.7</td></tr><tr><td>2x6</td><td>15.0</td><td>21.7</td></tr><tr><td>2x7</td><td>18.0</td><td>24.7</td></tr><tr><td>2x8</td><td>21.0</td><td>27.7</td></tr><tr><td>2x9</td><td>24.0</td><td>30.7</td></tr><tr><td>2x10</td><td>27.0</td><td>33.7</td></tr><tr><td>2x11</td><td>30.0</td><td>36.7</td></tr><tr><td>2x12</td><td>33.0</td><td>39.7</td></tr></tbody></table>				线数 Poles	尺寸 Dimensions(mm)			A	B	2x1	N/A	6.7	2x2	3.0	9.7	2x3	6.0	12.7	2x4	9.0	15.7	2x5	12.0	18.7	2x6	15.0	21.7	2x7	18.0	24.7	2x8	21.0	27.7	2x9	24.0	30.7	2x10	27.0	33.7	2x11	30.0	36.7	2x12	33.0	39.7																												
线数 Poles									尺寸 Dimensions(mm)																																																																					
	A	B																																																																												
2x1	N/A	6.7																																																																												
2x2	3.0	9.7																																																																												
2x3	6.0	12.7																																																																												
2x4	9.0	15.7																																																																												
2x5	12.0	18.7																																																																												
2x6	15.0	21.7																																																																												
2x7	18.0	24.7																																																																												
2x8	21.0	27.7																																																																												
2x9	24.0	30.7																																																																												
2x10	27.0	33.7																																																																												
2x11	30.0	36.7																																																																												
2x12	33.0	39.7																																																																												
F																																																																														
G																																																																														
H	<table border="1"><thead><tr><th colspan="2"></th><th colspan="2">GENERAL TOLERANCES</th><th>SCALE:</th><th>NAME</th><th>DATE</th><th colspan="2">东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD 公司网址: www.dgconne.cn 公司电话: 0768-65337633 邮箱: 2850175966@qq.com 公司传真: 0768-65362627</th><th>PART. NO:</th></tr><tr><th colspan="2"></th><th colspan="2"></th><th>1:1</th><th></th><th></th><th colspan="2"></th><th>3047-XX</th></tr><tr><th colspan="2"></th><th colspan="2"></th><th>APPROVED</th><th></th><th></th><th colspan="2"></th><th>DWG. NO:</th></tr><tr><th colspan="2"></th><th colspan="2"></th><th>DESIGNER</th><th></th><th></th><th colspan="2"></th><th>REV: AO SHEET: 1/1</th></tr><tr><th colspan="2"></th><th colspan="2"></th><th>DRAWN</th><th>肖丽娟</th><th>2018.07.28</th><th colspan="2">TITLE: 3.00mm pitch Dual Wafer</th><th></th></tr><tr><th>AO</th><th>新图面发行</th><th>2018.07.28</th><th>UNIT: MM</th><th>0.00±0.15</th><th>X° ±3°</th><th></th><th colspan="2"></th><th></th></tr><tr><th>REV.</th><th>REVISION RECORD</th><th>DATE</th><th>SIZE: A4</th><th>0.000±0.08</th><th>X° X'±2°</th><th></th><th colspan="2"></th><th></th></tr></thead></table>										GENERAL TOLERANCES		SCALE:	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD 公司网址: www.dgconne.cn 公司电话: 0768-65337633 邮箱: 2850175966@qq.com 公司传真: 0768-65362627		PART. NO:					1:1					3047-XX					APPROVED					DWG. NO:					DESIGNER					REV: AO SHEET: 1/1					DRAWN	肖丽娟	2018.07.28	TITLE: 3.00mm pitch Dual Wafer			AO	新图面发行	2018.07.28	UNIT: MM	0.00±0.15	X° ±3°					REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°				
		GENERAL TOLERANCES		SCALE:	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD 公司网址: www.dgconne.cn 公司电话: 0768-65337633 邮箱: 2850175966@qq.com 公司传真: 0768-65362627		PART. NO:																																																																					
				1:1					3047-XX																																																																					
				APPROVED					DWG. NO:																																																																					
				DESIGNER					REV: AO SHEET: 1/1																																																																					
				DRAWN	肖丽娟	2018.07.28	TITLE: 3.00mm pitch Dual Wafer																																																																							
AO	新图面发行	2018.07.28	UNIT: MM	0.00±0.15	X° ±3°																																																																									
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°																																																																									

	1	2	3	4	5	6	7	8																																																																						
A	环保物料																																																																													
B	P.C.B LAYOUT				技术参数 SPECIFICATIONS ◆间距: 3.0 Pitch:3.0 ◆适用线规: AWG#20-#24 Applicable Wire:AWG#20-#24 ◆额定电压: AC, DC, 250V (有效值) Voltage rating: AC,DC, 250V(rms) ◆额定电流: 5A, AC, DC Current rating:5A, AC, DC ◆耐压值: 1500V AC/minute Withstand voltage:1500V AC/minute ◆工作温度 : -40℃~+105℃ Working Temp:-40℃~+105℃ ◆绝缘电阻 : ≥100MΩ Insulation resistance:≥1000MΩ ◆接触电阻: ≤10mΩ Contact resistance:≤10mΩ 材料 MATERIAL ◆绝缘体: 尼龙66, UL94-0 Insulator:Nylon66 UL94-0 ◆接触针:黄铜 Contact PIN: Brass																																																																									
C																																																																														
D																																																																														
E					<table border="1"><thead><tr><th>线数 Poles</th><th colspan="2">尺寸 Dimensions(mm)</th></tr><tr><th></th><th>A</th><th>B</th></tr></thead><tbody><tr><td>2x1</td><td>N/A</td><td>6.7</td></tr><tr><td>2x2</td><td>3.0</td><td>9.7</td></tr><tr><td>2x3</td><td>6.0</td><td>12.7</td></tr><tr><td>2x4</td><td>9.0</td><td>15.7</td></tr><tr><td>2x5</td><td>12.0</td><td>18.7</td></tr><tr><td>2x6</td><td>15.0</td><td>21.7</td></tr><tr><td>2x7</td><td>18.0</td><td>24.7</td></tr><tr><td>2x8</td><td>21.0</td><td>27.7</td></tr><tr><td>2x9</td><td>24.0</td><td>30.7</td></tr><tr><td>2x10</td><td>27.0</td><td>33.7</td></tr><tr><td>2x11</td><td>30.0</td><td>36.7</td></tr><tr><td>2x12</td><td>33.0</td><td>39.7</td></tr></tbody></table>				线数 Poles	尺寸 Dimensions(mm)			A	B	2x1	N/A	6.7	2x2	3.0	9.7	2x3	6.0	12.7	2x4	9.0	15.7	2x5	12.0	18.7	2x6	15.0	21.7	2x7	18.0	24.7	2x8	21.0	27.7	2x9	24.0	30.7	2x10	27.0	33.7	2x11	30.0	36.7	2x12	33.0	39.7																												
线数 Poles									尺寸 Dimensions(mm)																																																																					
	A	B																																																																												
2x1	N/A	6.7																																																																												
2x2	3.0	9.7																																																																												
2x3	6.0	12.7																																																																												
2x4	9.0	15.7																																																																												
2x5	12.0	18.7																																																																												
2x6	15.0	21.7																																																																												
2x7	18.0	24.7																																																																												
2x8	21.0	27.7																																																																												
2x9	24.0	30.7																																																																												
2x10	27.0	33.7																																																																												
2x11	30.0	36.7																																																																												
2x12	33.0	39.7																																																																												
F																																																																														
G																																																																														
H	<table border="1"><thead><tr><th colspan="2"></th><th colspan="2">GENERAL TOLERANCES</th><th>SCALE:</th><th>NAME</th><th>DATE</th><th colspan="2">东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD 公司网址: www.dgoonne.cn 公司电话: 0768-65337633 邮箱: 2850175966@qq.com 公司传真: 0768-65362627</th><th>PART. NO:</th></tr><tr><th colspan="2"></th><th colspan="2"></th><th>1:1</th><th></th><th></th><th colspan="2"></th><th>3047-XX</th></tr><tr><th colspan="2"></th><th colspan="2"></th><th>APPROVED</th><th></th><th></th><th colspan="2"></th><th>DWG. NO:</th></tr><tr><th colspan="2"></th><th colspan="2"></th><th>DESIGNER</th><th></th><th></th><th colspan="2"></th><th>REV: AO SHEET: 1/1</th></tr><tr><th colspan="2"></th><th colspan="2"></th><th>DRAWN</th><th>肖丽娟</th><th>2018.07.28</th><th colspan="2">TITLE: 3.00mm pitch Dual Wafer</th><th></th></tr><tr><th>AO</th><th>新图面发行</th><th>2018.07.28</th><th>UNIT: MM</th><th>0.00±0.15</th><th>X° ±3°</th><th></th><th colspan="2"></th><th></th></tr><tr><th>REV.</th><th>REVISION RECORD</th><th>DATE</th><th>SIZE: A4</th><th>0.000±0.08</th><th>X° X'±2°</th><th></th><th colspan="2"></th><th></th></tr></thead></table>										GENERAL TOLERANCES		SCALE:	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD 公司网址: www.dgoonne.cn 公司电话: 0768-65337633 邮箱: 2850175966@qq.com 公司传真: 0768-65362627		PART. NO:					1:1					3047-XX					APPROVED					DWG. NO:					DESIGNER					REV: AO SHEET: 1/1					DRAWN	肖丽娟	2018.07.28	TITLE: 3.00mm pitch Dual Wafer			AO	新图面发行	2018.07.28	UNIT: MM	0.00±0.15	X° ±3°					REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°				
		GENERAL TOLERANCES		SCALE:	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD 公司网址: www.dgoonne.cn 公司电话: 0768-65337633 邮箱: 2850175966@qq.com 公司传真: 0768-65362627		PART. NO:																																																																					
				1:1					3047-XX																																																																					
				APPROVED					DWG. NO:																																																																					
				DESIGNER					REV: AO SHEET: 1/1																																																																					
				DRAWN	肖丽娟	2018.07.28	TITLE: 3.00mm pitch Dual Wafer																																																																							
AO	新图面发行	2018.07.28	UNIT: MM	0.00±0.15	X° ±3°																																																																									
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°																																																																									

- [illegible]

	1	2	3	4	5	6	7	8																																																																						
A	环保物料																																																																													
B																																																																														
C																																																																														
D	技术参数 SPECIFICATIONS ◆间距: 3.0 Pitch:3.0 ◆适用线规: AWG#20-#24 Applicable Wire:AWG#20-#24 ◆额定电压: AC, DC, 250V (有效值) Voltage rating: AC,DC, 250V(rms) ◆额定电流: 5A, AC, DC Current rating:5A, AC, DC ◆耐压值: 1500V AC/minute Withstand voltage:1500V AC/minute ◆工作温度 : -40℃~+105℃ Working Temp:-40℃~+105℃ ◆绝缘电阻 : ≥100MΩ Insulation resistance:≥1000MΩ ◆接触电阻: ≤10mΩ Contact resistance:≤10mΩ 材料 MATERIAL ◆绝缘体: 尼龙66, UL94-0 Insulator:Nylon66 UL94-0 ◆接触针:黄铜 Contact PIN: Brass																																																																													
E	<table border="1"><thead><tr><th>线数 Poles</th><th colspan="2">尺寸 Dimensions(mm)</th></tr><tr><th></th><th>A</th><th>B</th></tr></thead><tbody><tr><td>2x1</td><td>N/A</td><td>6.7</td></tr><tr><td>2x2</td><td>3.0</td><td>9.7</td></tr><tr><td>2x3</td><td>6.0</td><td>12.7</td></tr><tr><td>2x4</td><td>9.0</td><td>15.7</td></tr><tr><td>2x5</td><td>12.0</td><td>18.7</td></tr><tr><td>2x6</td><td>15.0</td><td>21.7</td></tr><tr><td>2x7</td><td>18.0</td><td>24.7</td></tr><tr><td>2x8</td><td>21.0</td><td>27.7</td></tr><tr><td>2x9</td><td>24.0</td><td>30.7</td></tr><tr><td>2x10</td><td>27.0</td><td>33.7</td></tr><tr><td>2x11</td><td>30.0</td><td>36.7</td></tr><tr><td>2x12</td><td>33.0</td><td>39.7</td></tr></tbody></table>								线数 Poles	尺寸 Dimensions(mm)			A	B	2x1	N/A	6.7	2x2	3.0	9.7	2x3	6.0	12.7	2x4	9.0	15.7	2x5	12.0	18.7	2x6	15.0	21.7	2x7	18.0	24.7	2x8	21.0	27.7	2x9	24.0	30.7	2x10	27.0	33.7	2x11	30.0	36.7	2x12	33.0	39.7																												
线数 Poles	尺寸 Dimensions(mm)																																																																													
	A	B																																																																												
2x1	N/A	6.7																																																																												
2x2	3.0	9.7																																																																												
2x3	6.0	12.7																																																																												
2x4	9.0	15.7																																																																												
2x5	12.0	18.7																																																																												
2x6	15.0	21.7																																																																												
2x7	18.0	24.7																																																																												
2x8	21.0	27.7																																																																												
2x9	24.0	30.7																																																																												
2x10	27.0	33.7																																																																												
2x11	30.0	36.7																																																																												
2x12	33.0	39.7																																																																												
F																																																																														
G																																																																														
H	<table border="1"><thead><tr><th colspan="2"></th><th colspan="2">GENERAL TOLERANCES</th><th>SCALE:</th><th>NAME</th><th>DATE</th><th colspan="2">东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD.</th><th>PART. NO:</th></tr><tr><th colspan="2"></th><th>LINER</th><th>ANGLES</th><th>1:1</th><th></th><th></th><th colspan="2">公司网址: www.dgkoonne.cn 公司电话: 0768-65337633</th><th rowspan="2">3047-XX</th></tr><tr><th colspan="2"></th><th>0.0±0.25</th><th>X° REF ±6°</th><th>APPROVED</th><th></th><th></th><th colspan="2">邮 箱: 2850175966@qq.com 公司传真: 0768-65362627</th></tr></thead><tbody><tr><td>A0</td><td>新图面发行</td><td>2018.07.28</td><td>UNIT: MM</td><td>0.00±0.15</td><td>X° ±3°</td><td>DESIGNER</td><td colspan="2">TITLE:</td><td>DWG. NO:</td></tr><tr><td>REV.</td><td>REVISION RECORD</td><td>DATE</td><td>SIZE: A4</td><td>0.000±0.08</td><td>X° X' ±2°</td><td>DRAWN</td><td>肖丽娟</td><td>2018.07.28</td><td>3.00mm pitch Dual Wafer</td></tr><tr><td colspan="2"></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>REV: AO</td></tr><tr><td colspan="2"></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>SHEET: 1/1</td></tr></tbody></table>										GENERAL TOLERANCES		SCALE:	NAME	DATE	东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD.		PART. NO:			LINER	ANGLES	1:1			公司网址: www.dgkoonne.cn 公司电话: 0768-65337633		3047-XX			0.0±0.25	X° REF ±6°	APPROVED			邮 箱: 2850175966@qq.com 公司传真: 0768-65362627		A0	新图面发行	2018.07.28	UNIT: MM	0.00±0.15	X° ±3°	DESIGNER	TITLE:		DWG. NO:	REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X' ±2°	DRAWN	肖丽娟	2018.07.28	3.00mm pitch Dual Wafer										REV: AO										SHEET: 1/1	
		GENERAL TOLERANCES		SCALE:	NAME	DATE	东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD.		PART. NO:																																																																					
		LINER	ANGLES	1:1			公司网址: www.dgkoonne.cn 公司电话: 0768-65337633		3047-XX																																																																					
		0.0±0.25	X° REF ±6°	APPROVED			邮 箱: 2850175966@qq.com 公司传真: 0768-65362627																																																																							
A0	新图面发行	2018.07.28	UNIT: MM	0.00±0.15	X° ±3°	DESIGNER	TITLE:		DWG. NO:																																																																					
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X' ±2°	DRAWN	肖丽娟	2018.07.28	3.00mm pitch Dual Wafer																																																																					
									REV: AO																																																																					
									SHEET: 1/1																																																																					
	1	2	3	4	5	6	7	8																																																																						

- | | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--------------------|--|----------|-------------------------|------|--|-----------|--|---|----------|-------------------|------|--|-----------|---|--------|--------|-----|---------|-----|----------|-----------|----------|----------|-----|-----------|--------|----------|--------------------|------|------------|----------|-------|----------------|------|------|-----|--------|-------------------------|-----|------|------|------|------|------|------|------|------|------|------|------|
| A | 环保物料 | | | | | | <div>技术参数 SPECIFICATIONS</div> <ul style="list-style-type: none">◆间距: 3.0 Pitch:3.0◆适用线规: AWG#20-#24
Applicable Wire:AWG#20-#24◆额定电压: AC, DC, 250V (有效值)
Voltage rating: AC,DC, 250V(rms)◆额定电流: 5A, AC, DC
Current rating:5A, AC, DC◆耐压值: 1500V AC/minute
Withstand voltage:1500V AC/minute◆工作温度 : -40℃~+105℃
Working Temp:-40℃~+105℃◆绝缘电阻 : ≥100MΩ
Insulation resistance:≥1000MΩ◆接触电阻: ≤10mΩ
Contact resistance:≤10mΩ <div>材料 MATERIAL</div> <ul style="list-style-type: none">◆绝缘体: 尼龙66, UL94-0
Insulator:Nylon66 UL94-0◆接触针: 黄铜
Contact PIN: Brass <table border="1"><thead><tr><th>线数 Poles</th><th colspan="2">尺寸 Dimensions(mm)</th></tr><tr><th></th><th>A</th><th>B</th></tr></thead><tbody><tr><td>2x1</td><td>N/A</td><td>6.7</td></tr><tr><td>2x2</td><td>3.0</td><td>9.7</td></tr><tr><td>2x3</td><td>6.0</td><td>12.7</td></tr><tr><td>2x4</td><td>9.0</td><td>15.7</td></tr><tr><td>2x5</td><td>12.0</td><td>18.7</td></tr><tr><td>2x6</td><td>15.0</td><td>21.7</td></tr><tr><td>2x7</td><td>18.0</td><td>24.7</td></tr><tr><td>2x8</td><td>21.0</td><td>27.7</td></tr><tr><td>2x9</td><td>24.0</td><td>30.7</td></tr><tr><td>2x10</td><td>27.0</td><td>33.7</td></tr><tr><td>2x11</td><td>30.0</td><td>36.7</td></tr><tr><td>2x12</td><td>33.0</td><td>39.7</td></tr></tbody></table> | | 线数 Poles | 尺寸 Dimensions(mm) | | | A | B | 2x1 | N/A | 6.7 | 2x2 | 3.0 | 9.7 | 2x3 | 6.0 | 12.7 | 2x4 | 9.0 | 15.7 | 2x5 | 12.0 | 18.7 | 2x6 | 15.0 | 21.7 | 2x7 | 18.0 | 24.7 | 2x8 | 21.0 | 27.7 | 2x9 | 24.0 | 30.7 | 2x10 | 27.0 | 33.7 | 2x11 | 30.0 | 36.7 | 2x12 | 33.0 | 39.7 |
| 线数 Poles | 尺寸 Dimensions(mm) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | A | B | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2x1 | N/A | 6.7 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2x2 | 3.0 | 9.7 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2x3 | 6.0 | 12.7 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2x4 | 9.0 | 15.7 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2x5 | 12.0 | 18.7 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2x6 | 15.0 | 21.7 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2x7 | 18.0 | 24.7 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2x8 | 21.0 | 27.7 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2x9 | 24.0 | 30.7 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2x10 | 27.0 | 33.7 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2x11 | 30.0 | 36.7 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2x12 | 33.0 | 39.7 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| B | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| D | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| F | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| G | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| H | <table border="1"><thead><tr><th colspan="2">GENERAL TOLERANCES</th><th>SCALE:</th><th rowspan="2">NAME</th><th rowspan="2">DATE</th><th rowspan="5"><div><div>东莞市康导新能源科技有限公司</div><div>DONGGUAN KD NEW ENERGY TECHNOLOGY CO., LTD.</div><div>公司网址: www.dgoonne.cn 公司电话: 0768-65337633</div><div>邮 箱: 2850175966@qq.com 公司传真: 0768-65362627</div></div></th><th colspan="2">PART. NO:</th></tr><tr><th>LINEAR</th><th>ANGLES</th><th>1:1</th><th colspan="2">3047-XX</th></tr></thead><tbody><tr><td>0.0±0.25</td><td>X° REF±6°</td><td>APPROVED</td><td colspan="2">DWG. NO:</td></tr><tr><td>0.00±0.15</td><td>X° ±3°</td><td>DESIGNER</td><td colspan="2">REV: AO SHEET: 1/1</td></tr><tr><td>0.000±0.08</td><td>X° X'±2°</td><td>DRAWN</td><td colspan="2">肖丽娟 2018.07.28</td></tr><tr><td colspan="2"></td><td>TITLE:</td><td colspan="2">3.00mm pitch Dual Wafer</td></tr></tbody></table> | | | | | | GENERAL TOLERANCES | | SCALE: | NAME | DATE | <div><div>东莞市康导新能源科技有限公司</div><div>DONGGUAN KD NEW ENERGY TECHNOLOGY CO., LTD.</div><div>公司网址: www.dgoonne.cn 公司电话: 0768-65337633</div><div>邮 箱: 2850175966@qq.com 公司传真: 0768-65362627</div></div> | PART. NO: | | LINEAR | ANGLES | 1:1 | 3047-XX | | 0.0±0.25 | X° REF±6° | APPROVED | DWG. NO: | | 0.00±0.15 | X° ±3° | DESIGNER | REV: AO SHEET: 1/1 | | 0.000±0.08 | X° X'±2° | DRAWN | 肖丽娟 2018.07.28 | | | | TITLE: | 3.00mm pitch Dual Wafer | | | | | | | | | | | | |
| GENERAL TOLERANCES | | SCALE: | NAME | DATE | <div><div>东莞市康导新能源科技有限公司</div><div>DONGGUAN KD NEW ENERGY TECHNOLOGY CO., LTD.</div><div>公司网址: www.dgoonne.cn 公司电话: 0768-65337633</div><div>邮 箱: 2850175966@qq.com 公司传真: 0768-65362627</div></div> | PART. NO: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| LINEAR | ANGLES | 1:1 | | | | 3047-XX | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.0±0.25 | X° REF±6° | APPROVED | DWG. NO: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.00±0.15 | X° ±3° | DESIGNER | REV: AO SHEET: 1/1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.000±0.08 | X° X'±2° | DRAWN | 肖丽娟 2018.07.28 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | TITLE: | 3.00mm pitch Dual Wafer | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

[illegible]

A

B

C

D

E

F

G

H

1

2

3

4

5

6

7

8

环保物料

The figure contains four technical drawings:

- Top View:** Shows a rectangular component with dimensions A ± 0.20, B ± 0.25, and overall width 9.85 mm. It features two rows of pins.
- P.C.B LAYOUT:** Illustrates the internal circuit board layout with dimensions such as 3.0, 1.27, 3.43, 2.54, 9.0, 20.20, 1.65, and 3.0.
- Side View:** Displays the profile of the component with dimensions 6.80, 7.30, 1.7, and 2.2.
- Front View:** Provides another perspective of the component's geometry.

技术参数 SPECIFICATIONS

◆间距：3.0 Pitch:3.0

◆适用线规：AWG#20-#24
Applicable Wire:AWG#20-#24

◆额定电压：AC,DC,250V（有效值）
Voltage rating：AC,DC,250V(rms)

◆额定电流：5A, AC, DC
Current rating:5A, AC, DC

◆耐压值：1500V AC/minute
Withstand voltage:1500V AC/minute

◆工作温度：-40℃~+105℃
Working Temp:-40℃~+105℃

◆绝缘电阻：≥100MΩ
Insulation resistance:≥1000MΩ

◆接触电阻：≤10mΩ
Contact resistance:≤10mΩ

材料 MATERIAL

◆绝缘体：尼龙66，UL94-0
Insulator:Nylon66 UL94-0

◆接触针：黄铜
Contact PIN: Brass

线数 Poles	尺寸 Dimensions(mm) A B	
2x1	N/A	6.7
2x2	3.0	9.7
2x3	6.0	12.7
2x4	9.0	15.7
2x5	12.0	18.7
2x6	15.0	21.7
2x7	18.0	24.7
2x8	21.0	27.7
2x9	24.0	30.7
2x10	27.0	33.7
2x11	30.0	36.7
2x12	33.0	39.7

				GENERAL TOLERANCES	SCALE： 1:1	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD. 公司地址: www.dgoonne.cn 公司电话: 0768-65337633 邮 箱: 2850175966@qq.com 公司传真: 0768-65362627 TITLE: 3.00mm pitch Dual Wafer	PART. NO: 3047-XX
				LINER	APPROVED				DWG. NO:
				0.0±0.25	X° REF±6°				REV: AO SHEET: 1/1
AO	新图面发行	2018.07.28	UNIT: MM	0.00±0.15	X° ±3°	DESIGNER			
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	肖丽娟	2018.07.28	

1

2

3

4

5

6

7

8