

环保物料

技术参数 SPECIFICATIONS

- ◆间距: 4.14 Pitch:4.14
- ◆额定电压: AC, DC, 300V (有效值)
Voltage rating: AC, DC, 300V(rms)
- ◆额定电流: 10-8.0A, AC, DC
Current rating:10-8.0A, AC, DC
- ◆耐压值: 1500V AC/minute
Withstand voltage:1500V AC/minute
- ◆工作温度: -25℃~+85℃
Working Temp:-25℃~+85℃
- ◆绝缘电阻: $\geq 1000M\Omega$
Insulation resistance: $\geq 1000M\Omega$
- ◆接触电阻: $\leq 20m\Omega$
Contact resistance: $\leq 20m\Omega$

材料 MATERIAL

- ◆绝缘体: 尼龙66, UL94V-0
Insulator:Nylon66 UL94V-0

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD 公司网址: www.dgkonne.cn 公司电话: 0769-85337633 邮箱: 2850175888@qq.com 公司传真: 0769-85392827	PART. NO: 6612M-XX		
				LINEAR	ANGLES	APPROVED				DWG. NO:		
				0.0±0.25	X° REF±6°	DESIGNER				REV: AO		
				0.00±0.15	X° ±3°	DRAWN	肖丽娟	2018.11.23		SHEET: 1/1		
REV.	REVISION RECORD		DATE	SIZE: A4	0.000±0.08	X° X'±2°	TITLE: 4.14mm pitch Single Housing					
A0	新图面发行		2018.11.23	UNIT: MM	0.00±0.15	X° ±3°						