


环保物料

Pin数	尺寸A	尺寸B
2	4.20	20.00
3	8.40	24.20
4	12.60	28.40
5	16.80	32.60
6	21.00	36.80
7	25.20	41.00
8	29.40	45.20
9	33.60	49.40
10	37.80	53.60
11	42.00	57.80
12	46.20	62.00
13	50.40	66.20
14	54.60	70.40
15	58.80	74.60
16	63.00	78.80
17	67.20	83.00
18	71.40	87.20
19	75.60	91.40
20	79.80	95.60
21	84.00	99.80
22	88.20	104.00
23	92.40	108.20
24	96.60	112.40
25	100.80	116.60



技术参数 SPECIFICATIONS

- ◆间距: 4.2 Pitch:4.2
- ◆适用线规: AWG#22-#28
Applicable Wire:AWG#22-#28
- ◆额定电压: AC, DC, 250V (有效值)
Voltage rating: AC, DC, 250V(rms)
- ◆额定电流: 5A, AC, DC
Current rating:5A, AC, DC
- ◆耐压值: 1500V AC/minute
Withstand voltage:1500V AC/minute
- ◆工作温度: -25℃~+85℃
Working Temp:-25℃~+85℃
- ◆绝缘电阻: ≥1000MΩ
Insulation resistance:≥1000MΩ
- ◆接触电阻: ≤20mΩ
Contact resistance:≤20mΩ

材料 MATERIAL

- ◆绝缘体: 尼龙66, UL94-2
Insulator:Nylon66 UL94-2

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	 东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD 公司网址: www.dgoonne.cn 公司电话: 0769-85337533 邮 箱: 2850175986@qq.com 公司传真: 0769-85392827	PART. NO: 9358F-XX		
				LINEAR	ANGLES	APPROVED						DWG. NO:
				0.0±0.25	X° REF±6°	DESIGNER						
A0	新图面发行	2018.11.23	UNIT: MM	0.00±0.15	X° ±3°					TITLE: 4.20mm pitch Dual Housing	REV: A0	SHEET: 1/1
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	肖丽娟	2018.11.23				