




环保物料

Pin数	尺寸A	尺寸B
2	4.20	9.60
3	8.40	13.80
4	12.60	18.00
5	16.80	22.20
6	21.00	26.40
7	25.20	30.60
8	29.40	34.80
9	33.60	39.00
10	37.80	43.20
11	42.00	47.40
12	46.20	51.60
13	50.40	55.80
14	54.60	60.00
15	58.80	64.20
16	63.00	68.40
17	67.20	72.60
18	71.40	76.82
19	75.60	81.00
20	79.80	85.20
21	84.00	89.40
22	88.20	93.60
23	92.40	97.80
24	96.60	102.00
25	100.80	106.20



- 技术参数
 SPECIFICATIONS
- ◆间距：4.2 Pitch:4.2
 - ◆适用线规：AWG#22-#28
Applicable Wire:AWG#22-#28
 - ◆额定电压：AC,DC,250V（有效值）
Voltage rating: AC,DC,250V(rms)
 - ◆额定电流：5A,AC,DC
Current rating:5A,AC,DC
 - ◆耐压值：1500V AC/minute
Withstand voltage:1500V AC/minute
 - ◆工作温度：-25℃~+85℃
Working Temp:-25℃~+85℃
 - ◆绝缘电阻：≥1000MΩ
Insulation resistance:≥1000MΩ
 - ◆接触电阻：≤20mΩ
Contact resistance:≤20mΩ

- 材料
 MATERIAL
- ◆绝缘体：尼龙66,UL94-2
Insulator:Nylon66 UL94-2

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	 东莞市康导新能源科技有限公司 DONGGUAN KD NEW ENERGY TECHNOLOGY CO., LTD 公司网址: www.dgoonne.cn 公司电话: 0769-85337533 邮 箱: 2850175986@qq.com 公司传真: 0769-85392827	PART. NO: 9358-1×XX		
				LINEAR	ANGLES					APPROVED		
				0.0±0.25	X° REF±6°	DESIGNER						
A0	新图面发行	2018.11.26	UNIT: MM	0.00±0.15	X° ±3°					TITLE:	4.20mm pitch Single Housing	
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	肖丽娟	2018.11.26			REV: A0	SHEET: 1/1