



孔位 Poles	A	B	C
4	3.0	7.1	5.1
5	4.0	8.1	6.1
6	5.0	9.1	7.1
7	6.0	10.1	8.1
8	7.0	11.1	9.1
9	8.0	12.1	10.1
10	9.0	13.1	11.1
11	10.0	14.1	12.1
12	11.0	15.1	13.1
13	12.0	16.1	14.1
14	13.0	17.1	15.1
15	14.0	18.1	16.1
16	15.0	19.1	17.1
17	16.0	20.1	18.1
18	17.0	21.1	19.1
19	18.0	22.1	20.1
20	19.0	23.1	21.1
21	20.0	24.1	22.1
22	21.0	25.1	23.1
23	22.0	26.1	24.1
24	23.0	27.1	25.1
25	24.0	28.1	26.1
26	25.0	29.1	27.1
27	26.0	30.1	28.1
28	27.0	31.1	29.1
29	28.0	32.1	30.1
30	29.0	33.1	31.1
31	30.0	34.1	32.1
32	31.0	35.1	33.1
33	32.0	36.1	34.1
34	33.0	37.1	35.1
35	34.0	38.1	36.1
36	35.0	39.1	37.1
37	36.0	40.1	38.1
38	37.0	41.1	39.1
39	38.0	42.1	40.1
40	39.0	43.1	41.1



				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	 东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD 公司网址: www.dgconne.cn 公司电话: 0769-85337633 邮 箱: 2850175988@qq.com 公司传真: 0769-85392827	PART. NO: FPC 1.0A-LT	
				LINEAR	ANGLES	APPROVED				DWG. NO: KDFPC-0014	
				0.0±0.25	X° REF±6°						
A0	新图面发行	2018.11.29	UNIT: MM	0.00±0.15	X° ±3°	DESIGNER			TITLE: 1.00mm pitch Single Wafer	REV: A0	SHEET: 1/1
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	肖丽娟	2018.11.29			

1	2	3	4	5	6	7	8
---	---	---	---	---	---	---	---