



线数

(Poles): 1, 2, 3, 4, 6, 9, 12, 15

適用線規 (Applicable wires):AWG26#
~20#

适应基板厚度 (Applicable PC board thickness): 1.6~2.0mm

温度范围 (Temperature range): -25℃
~+105℃

额定电压 (Voltage rating): 300V. AC/DC

额定电流 (Current rating): 13-8A

接触电阻 (Contact resistance): $\leq 0.01\Omega$

绝缘电阻 (Insulation resistance): $\geq 1000\text{M}\Omega$

耐压 (Withstand voltage):1500V.AC/1
分钟 (Minute)

材料 (Material):

插头 (Plug housing): 尼龙 (Nylon) UL94V-0

插座 (Receptacle housing): 尼龙 (Nylon) UL94V-0

端子(Terminal):磷青铜
(Phos. bronze Tin/plated)

黄铜 (Brass

Tin/plated)

东莞市康导新能源科技有限公司
DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD

公司地址: www.dgconne.cn 公司电话: 0769-85337633
销售热线: 2850175988@qq.com 公司传真: 0769-85392827

PART. NO: KD180XX-XR

DWG. NO:

TITLE:	1.80mm pitch Single Housing
--------	-----------------------------

REV:	A0	SHEET:	1 / 1
------	----	--------	-------