

环保物料

技术参数 SPECIFICATIONS

线数 (Poles):1、2、3、4

适用线规 (Applicable wires):AWG26#
~20#

适应基板厚度 (Applicable PC board
thickness):1.6~2.0mm

温度范围 (Temperature range):-25℃
~+105℃

额定电压 (Voltage
rating):300V.AC/DC

额定电流 (Current rating):12A

接触电阻 (Contact
resistance):≤0.01Ω

绝缘电阻 (Insulation
resistance):≥1000MΩ

耐压 (Withstand voltage):1500V.AC/1
分钟 (Minute)

材料 (Material):

插座 (Housing):尼龙 (Nylon)

UL94V-0

焊片 (Wafer):尼龙 (Nylon)

UL94V-0

端子(Terminal):磷青铜

(Phos.bronze Tin/plated)

D1.8K-1A(640595)

D1.8K-2A(640598)(641265/Auto)

D1.8K-3A(640608/6mm)(640580/12mm)

D1.8K-4A(640675)



GENERAL TOLERANCES

LINEAR

ANGLES

0.0±0.25

X° REF±6°

0.00±0.15

X° ±3°

0.000±0.08

X° X'±2°

SCALE:
1:1

NAME

DATE

APPROVED

DESIGNER

DRAWN

肖丽娟

2018. 12. 04



东莞市康导新能源科技有限公司

DONGGUAN KD NEW ENERGY TECHNOLOGY CO.,LTD

公司网址: www.dgkonne.cn

公司电话: 0769-85337633

邮箱: 2850175988@qq.com

公司传真: 0769-85392827

TITLE:

1.80mm pitch Single Wafer

PART. NO:

KD1. 8K-XA

DWG. NO:

REV: A0

SHEET: 1/1

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	 东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD 公司网址: www.dgkonne.cn 公司电话: 0769-85337633 邮 箱: 2850175988@qq.com 公司传真: 0769-85392827	PART. NO: KD1. 8K-XA		
				LINEAR	ANGLES	APPROVED				DWG. NO:		
				0. 0 ± 0. 25	X° REF ± 6°							
AO	新图面发行	2018. 12. 04	UNIT: MM	0. 00 ± 0. 15	X° ± 3°	DESIGNER					TITLE: 1. 80mm pitch Single Wafer	REV: A0
REV.	REVISION RECORD	DATE	SIZE: A4	0. 000 ± 0. 08	X° X' ± 2°	DRAWN	肖丽娟	2018. 12. 04				