


环保物料



- 技术参数 SPECIFICATIONS
- ◆间距: 4.5 Pitch:4.5
 - ◆适用线规: AWG#26-#16
Applicable Wire:AWG#26-#16
 - ◆额定电压: AC,DC, 300V (有效值)
Voltage rating: AC,DC, 300V(rms)
 - ◆额定电流: 6.0-10.0A, AC, DC
Current rating:6.0-10.0A, AC, DC
 - ◆耐压值: 1500V AC/minute
Withstand voltage:1500V AC/minute
 - ◆工作温度: -25℃~+85℃
Working Temp:-25℃~+85℃
 - ◆绝缘电阻: $\geq 1500M\Omega$
Insulation resistance: $\geq 1500M\Omega$
 - ◆接触电阻: $\leq 15m\Omega$
Contact resistance: $\leq 15m\Omega$
- 材料 MATERIAL
- ◆绝缘体: 尼龙66, UL94V-0
Insulator:Nylon66 UL94V-0

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD 公司地址: www.dgkonne.cn 公司电话: 0769-85337533 邮 箱: 2850175986@qq.com 公司传真: 0769-85392827	PART. NO: 4500F-02	
				LINEAR	ANGLES	APPROVED					
				0.0±0.25	X° REF±6°	DESIGNER					
A0	新图面发行	2018.12.12		UNIT: MM	0.00±0.15	X° ±3°					
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	肖丽娟	2018.12.12		TITLE: 4.50mm pitch Single Housing	
										REV: A0	SHEET: 1/1