

环保物料

技术参数:

线数: 2、3、4、6、9、12、15

温度范围: -25℃~+85℃

额定电压: 250V DC/AC (有效值)

额定电流: 5.0A

绝缘电阻: $\geq 1000M\Omega$

接触电阻: $\leq 0.01\Omega$

耐压: 1000V AC(有效值)

材料:

孔座: 尼龙66 UL94V-0

插座: 尼龙66 UL94V-0

端子: 磷青铜



线数 Poles	料号 Part No	尺寸Dimensions(mm)	
		A	B
2	KD50300-2P	16.42	7.92
3	KD50300-3P	21.10	7.92
4(1x4)	KD50300-4P	26.37	7.92
4(2x2)	KD50300-4PIN	12.70	15.24
6	KD50300-6P	17.22	15.24
9	KD50300-9P	21.03	18.42
12	KD50300-12P	26.67	18.42
15	KD50300-15P	31.50	18.42

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	 东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD 公司网址: www.dgoonne.cn 公司电话: 0769-85337633 邮 箱: 2850175986@qq.com 公司传真: 0769-85392827	PART. NO: KD3000-XPf		
				LINEAR	ANGLES	APPROVED				DWG. NO:		
				0.0±0.25	X° REF±6°							
A0	新图面发行	2018.12.14	UNIT: MM	0.00±0.15	X° ±3°	DESIGNER				TITLE: 5.00mm pitch Single Housing	REV: A0	SHEET: 1/1
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	肖丽娟	2018.12.14				