




环保物料



技术参数 SPECIFICATIONS

- ◆间距: 5.08 Pitch:5.08
- ◆适用线规: AWG#24-#14
Applicable Wire:AWG#24-#14
- ◆额定电压: AC,DC, 250V (有效值)
Voltage rating: AC,DC, 250V(rms)
- ◆额定电流: 5A, AC, DC
Current rating:5A, AC, DC
- ◆耐压值: 1500V AC/minute
Withstand voltage:1500V AC/minute
- ◆工作温度: $-25^{\circ}\text{C}\sim+85^{\circ}\text{C}$
Working Temp: $-25^{\circ}\text{C}\sim+85^{\circ}\text{C}$
- ◆绝缘电阻: $\geq 1000\text{M}\Omega$
Insulation resistance: $\geq 1000\text{M}\Omega$
- ◆接触电阻: $\leq 20\text{m}\Omega$
Contact resistance: $\leq 20\text{m}\Omega$

材料 MATERIAL

- ◆绝缘体: 尼龙66, UL94-0
Insulator:Nylon66 UL94-0

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	东莞市康导新能源科技有限公司 公司网址: www.dgoonne.cn 公司电话: 0769-85337533 邮箱: 2850175986@qq.com 公司传真: 0769-85392827		PART. NO: 6060-02	
				LINEAR	ANGLES						DWG. NO:	
				0.0 $\pm$ 0.25	X° REF $\pm$ 6°							
A0	新图面发行	2018.12.15		0.00 $\pm$ 0.15	X° $\pm$ 3°							
REV.	REVISION RECORD	DATE	SIZE: A4	0.000 $\pm$ 0.08	X° X' $\pm$ 2°	DRAWN	肖丽娟	2018.12.15	TITLE: 5.08mm pitch Single Housing		REV: A0	SHEET: 1/1