





环保物料



技术参数 SPECIFICATIONS

- ◆间距: 6.0 Pitch:6.0
 - ◆适用线规: AWG#22-#28
Applicable Wire:AWG#22-#28
 - ◆额定电压: AC, DC, 250V (有效值)
Voltage rating: AC, DC, 250V(rms)
 - ◆额定电流: 7A, AC, DC
Current rating:7A, AC, DC
 - ◆耐压值: 1500V AC/minute
Withstand voltage:1500V AC/minute
 - ◆工作温度: -25℃~+85℃
Working Temp:-25℃~+85℃
 - ◆绝缘电阻: $\geq 1000M\Omega$
Insulation resistance: $\geq 1000M\Omega$
 - ◆接触电阻: $\leq 20m\Omega$
Contact resistance: $\leq 20m\Omega$
- 材料 MATERIAL
- ◆绝缘体: 尼龙66, UL94-0
Insulator:Nylon66 UL94-0
 - ◆插针: 黄铜
Contact pin:Brass

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUAN KD NEW ENERGY TECHNOLOGY CO.,LTD 公司网址: www.dgoonne.cn 公司电话: 0769-85337533 邮 箱: 2850175986@qq.com 公司传真: 0769-85392827	PART. NO: 8针 6.0mm		
				LINEAR	ANGLES	APPROVED						DWG. NO:
				0.0±0.25	X° REF±6°							
AO	新图面发行	2018.12.17		UNIT: MM	0.00±0.15	X° ±3°				DESIGNER		
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	肖丽娟	2018.12.17				