




环保物料

Pin数	尺寸A	尺寸B
2	5.08	9.95
3	10.16	15.03
4	15.24	20.11
5	20.32	25.19
6	25.40	30.27
7	30.48	35.35
8	35.56	40.43
9	40.64	45.51
10	45.72	50.59
11	50.80	55.67
12	55.88	60.75
13	60.96	65.83
14	66.04	70.91
15	71.12	75.99
16	76.20	81.07
17	81.28	86.15
18	86.36	91.23
19	91.44	96.31
20	96.52	101.39



P. C. B LAYOUT

技术参数 SPECIFICATIONS

- ◆间距: 5.08 Pitch:5.08
 - ◆适用线规: AWG#22-#28
Applicable Wire:AWG#22-#28
 - ◆额定电压: AC, DC, 250V (有效值)
Voltage rating: AC, DC, 250V(rms)
 - ◆额定电流: 7A, AC, DC (AWG#24)
Current rating:7A, AC, DC (AWG#24)
 - ◆耐压值: 1500V AC/minute
Withstand voltage:1500V AC/minute
 - ◆工作温度: -25℃~+85℃
Working Temp:-25℃~+85℃
 - ◆绝缘电阻: $\geq 1000M\Omega$
Insulation resistance: $\geq 1000M\Omega$
 - ◆接触电阻: $\leq 20m\Omega$
Contact resistance: $\leq 20m\Omega$
- 材料 MATERIAL
- ◆绝缘体: 尼龙66, UL94V-2
Insulator:Nylon66 UL94V-2
 - ◆插针: 黄铜
Contact pin:Brass, Tin Plated

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	东莞市康号新能源科技有限公司 公司网址: www.dgoonne.cn 公司电话: 0769-85337533 邮箱: 2850175988@qq.com 公司传真: 0769-85392827	PART. NO: 5814-XX	
				LINEAR	ANGLES	APPROVED				DWG. NO:	
				0.0±0.25	X° REF±6°	DESIGNER					
A0	新图面发行	2018.12.15		0.00±0.15	X° ±3°	DRAWN	肖丽娟	2018.12.15		TITLE: 5.08mm pitch Single Wafer	
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°					REV: A0	SHEET: 1/1