









环保物料

技术参数 SPECIFICATIONS

- ◆间距: 6.2 Pitch:6.2
 - ◆适用线规: AWG#22-#28
Applicable Wire:AWG#22-#28
 - ◆额定电压: AC,DC, 300-600V (有效值)
Voltage rating: AC,DC, 300-600V(rms)
 - ◆额定电流: 9-15A, AC, DC
Current rating:9-15A, AC, DC
 - ◆耐压值: 1500V AC/minute
Withstand voltage:1500V AC/minute
 - ◆工作温度: -20℃~+85℃
Working Temp:-20℃~+85℃
 - ◆绝缘电阻: $\geq 1000M\Omega$
Insulation resistance: $\geq 1000M\Omega$
 - ◆接触电阻: $\leq 20m\Omega$
Contact resistance: $\leq 20m\Omega$
- 材料 MATERIAL
- ◆绝缘体: 尼龙66, UL94-0
Insulator:Nylon66 UL94-0



				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	东莞市康导新能源科技有限公司 公司网址: www.dgoonne.cn 公司电话: 0769-85337633 邮箱: 2850175988@qq.com 公司传真: 0769-85392827			PART. NO:	
				LINEAR	ANGLES							6420M-XX	
				0.0±0.25	X° REF±6°							DWG. NO:	
A0	新图面发行	2018.12.17		0.00±0.15	X° ±3°							REV: A0 SHEET: 1/1	
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	肖丽娟	2018.12.17	TITLE: 6.20mm pitch Single Housing				