






环保物料



6420F-02



6420F-03



6420F-04

技术参数 SPECIFICATIONS

- ◆间距: 6.2 Pitch:6.2
- ◆适用线规: AWG#22-#28
Applicable Wire:AWG#22-#28
- ◆额定电压: AC, DC, 300-600V (有效值)
Voltage rating: AC, DC, 300-600V(rms)
- ◆额定电流: 9-15A, AC, DC
Current rating:9-15A, AC, DC
- ◆耐压值: 1500V AC/minute
Withstand voltage:1500V AC/minute
- ◆工作温度: -20℃~+85℃
Working Temp:-20℃~+85℃
- ◆绝缘电阻: $\geq 1000M\Omega$
Insulation resistance: $\geq 1000M\Omega$
- ◆接触电阻: $\leq 20m\Omega$
Contact resistance: $\leq 20m\Omega$

材料 MATERIAL

- ◆绝缘体: 尼龙66, UL94-0
Insulator:Nylon66 UL94-0



GENERAL TOLERANCES

LINEAR	ANGLES
0.0 $\pm$ 0.25	X° REF $\pm$ 6°
0.00 $\pm$ 0.15	X° $\pm$ 3°
0.000 $\pm$ 0.08	X° X' $\pm$ 2°

SCALE:
1:1

NAME

DATE

APPROVED

DESIGNER

DRAWN

肖丽娟

2018. 12. 17



东莞市康导新能源科技有限公司

DONGGUAN KD NEW ENERGY TECHNOLOGY CO.,LTD

公司网址: www.dgkonne.cn

公司电话: 0769-85337533

邮箱: 2850175986@qq.com 公司传真: 0769-85392827

TITLE:

6.20mm pitch Single Housing

PART. NO:

6420F-XX

DWG. NO:

REV: A0

SHEET: 1/1

A0 新图面发行

2018. 12. 17

UNIT: MM

SIZE: A4

REVISION RECORD

DATE