


环保物料

Pin数	尺寸A	尺寸B
2	1.00	4.30
3	2.00	5.30
4	3.00	6.30
5	4.00	7.30
6	5.00	8.30
7	6.00	9.30
8	7.00	10.30
9	8.00	11.30
10	9.00	12.30
11	10.00	13.30
12	11.00	14.30
13	12.00	15.30
14	13.00	16.30
15	14.00	17.30
16	15.00	18.30
17	16.00	19.30
18	17.00	20.30
19	18.00	21.30
20	19.00	22.30
21	20.00	23.30
22	21.00	24.30
23	22.00	25.30
24	23.00	26.30
25	24.00	27.30



技术参数 SPECIFICATIONS

- ◆适用线规: AWG#28~#32
Applicable Wire: AWG#28~#32
- ◆额定电压: 50V DC, AC(rms)
Rated voltage: 50V DC, AC(rms)
- ◆额定电流: 1A(AWG #28)
Rated Current: 1A(AWG #28)
- ◆耐压值: 500V AC/minute
Withstand voltage: 500V AC/min
- ◆工作温度: -25℃~+85℃
Working Temp:-25℃~+85℃
- ◆绝缘电阻: 100MΩ Min
Insulation resistance:≥100MΩ
- ◆接触电阻: ≤20mΩ
Contact resistance:≤20mΩ

材料 MATERIAL

- ◆绝缘体: 尼龙9T, UL94-V0
Insulator:Nylon9T, UL94-V0
- ◆接触针: 磷铜
Contact PIN: Phosphor bronze
- ◆焊片: 磷铜
Solder tab: Phosphor bronze

REV.	新图面发行	2018. 12. 01	UNIT: MM	GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE
				LINEAR	ANGLES			
				0. 00±0. 15	X° REF±6°			
				0. 00±0. 08	X° X'±2°			
REV.	REVISION RECORD	DATE	SIZE: A4			DRAWN	肖丽娟	2018. 12. 01


东莞市康导新能源科技有限公司
 DONGGUAN KD NEW ENERGY TECHNOLOGY CO.,LTD
 公司网址: www.dgoonne.cn 公司电话: 0769-85337533
 邮 箱: 2850175986@qq.com 公司传真: 0769-85392827

TITLE:
 1.00mm pitch Single Wafer

PART. NO: 1. 0T-1-LT (SH)

DWG. NO:

REV: A0 SHEET: 1/1