





Pin数	尺寸A	尺寸B
4	6.00	8.10
5	8.00	10.10
6	10.00	12.10
7	12.00	14.10
8	14.00	16.10
9	16.00	18.10
10	18.00	20.10
11	20.00	22.10
12	22.00	24.10
13	24.00	26.10
14	26.00	28.10
15	28.00	30.10
16	30.00	32.10
17	32.00	34.10
18	34.00	36.10
19	36.00	38.10
20	38.00	40.10
21	40.00	42.10
22	42.00	44.10
23	44.00	46.10
24	46.00	48.10
25	48.00	50.10
26	50.00	52.10
27	52.00	54.10



P. C. B LAYOUT

- ◆间距：2.0 Pitch:2.0
- ◆适用线规：AWG#24-#32
Applicable Wire:AWG#24-#32
- ◆额定电压：AC,DC,100V（有效值）
Voltage rating: AC,DC,100V(rms)
- ◆额定电流：2A, AC,DC (AWG#24)
Current rating:2A, AC,DC (AWG#24)
- ◆耐压值：800V AC/minute
Withstand voltage:800V AC/minute
- ◆工作温度：-25℃~+85℃
Working Temp:-25℃~+85℃
- ◆绝缘电阻：≥1000MΩ
Insulation resistance:≥1000MΩ
- ◆接触电阻：≤10mΩ
Contact resistance:≤10mΩ

◆绝缘体：尼龙66, UL94-V0
Insulator: Nylon66 UL94-V0

◆接触针：黄铜
Contact PIN: Brass

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	 东莞市康号新能源科技有限公司 DONGGUAN KD NEW ENERGY TECHNOLOGY CO., LTD 公司网址: www.dgoonns.cn 公司电话: 0769-85337633 邮 箱: 2860175866@qq.com 公司传真: 0769-85392827	PART. NO: PH2.0-NAWD		
				LINEAR	ANGLES	APPROVED					DWG. NO:	
				0.0±0.25	X° REF±6°	DESIGNER						
A0	新图面发行	2018.12.05		UNIT: MM	0.00±0.15	X° ±3°					TITLE: 2.00mm pitch Single Wafer	
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	肖丽娟	2018.12.05			REV: A0	SHEET: 1/1

东莞市康导新能源科技有限公司
DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD

公司网址: www.dgoonne.cn 公司电话: 0769-85337633
电 邮: 2850175866@qq.com 传 真: 0769-85362827

PART. NO: PH2. 0-NAWD

DWG. NO:

TITLE: 2.00mm pitch Single Wafer

REV: A0	SHEET: 1 / 1
---------	--------------