


环保物料

Pin数	尺寸A	尺寸B
4	6.00	12.00
5	8.00	14.00
6	10.00	16.00
7	12.00	18.00
8	14.00	20.00
9	16.00	22.00
10	18.00	24.00
11	20.00	26.00
12	22.00	28.00
13	24.00	30.00
14	26.00	32.00
15	28.00	34.00
16	30.00	36.00
17	32.00	38.00
18	34.00	40.00
19	36.00	42.00
20	38.00	44.00
21	40.00	46.00
22	42.00	48.00
23	44.00	50.00
24	46.00	52.00
25	48.00	54.00
26	50.00	56.00
27	52.00	58.00



- 技术参数 SPECIFICATIONS
- ◆间距: 2.0 Pitch:2.0
 - ◆适用线规: AWG#22-#30
Applicable Wire:AWG#22-#30
 - ◆额定电压: AC,DC, 125V (有效值)
Voltage rating: AC,DC, 125V(rms)
 - ◆额定电流: 2A, AC, DC (AWG#28)
Current rating:2A, AC, DC (AWG#28)
 - ◆耐压值: 1000V AC/minute
Withstand voltage:1000V AC/minute
 - ◆工作温度: -25℃~+85℃
Working Temp:-25℃~+85℃
 - ◆绝缘电阻: ≥1000MΩ
Insulation resistance:≥1000MΩ
 - ◆接触电阻: ≤20mΩ
Contact resistance:≤20mΩ
- 材料 MATERIAL
- ◆绝缘体: 尼龙9T, UL94-V0
Insulator:Nylon94-V0
 - ◆接触针: 磷铜/黄铜
Contact PIN:Phosphor Bronze/Brass

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	 东莞市康导新能源科技有限公司 DONGGUAN KD NEW ENERGY TECHNOLOGY CO.,LTD 公司网址: www.dgkonne.cn 公司电话: 0769-85337533 邮箱: 2850175986@qq.com 公司传真: 0769-85392827	PART. NO: PHS2. 0-WT-NA-B
					LINEAR	ANGLES	APPROVED			DWG. NO:
					0. 0±0. 25	X° REF±6°	DESIGNER			REV: A0
A0	新图面发行	2018. 12. 05	UNIT: MM		0. 00±0. 15	X° ±3°	DRAWN	肖丽娟		SHEET: 1/1
REV.	REVISION RECORD	DATE	SIZE: A4		0. 000±0. 08	X° X'±2°			TITLE: 2.00mm pitch Single Wafer	