




环保物料

Pin数	尺寸A	尺寸B
4	6.00	10.60
5	8.00	12.60
6	10.00	14.60
7	12.00	16.60
8	14.00	18.60
9	16.00	20.60
10	18.00	22.60
11	20.00	24.60
12	22.00	26.60
13	24.00	28.60
14	26.00	30.60
15	28.00	32.60
16	30.00	34.60
17	32.00	36.60
18	34.00	38.60
19	36.00	40.60
20	38.00	42.60
21	40.00	44.60
22	42.00	46.60
23	44.00	48.60
24	46.00	50.60
25	48.00	52.60
26	50.00	54.60
27	52.00	56.60



技术参数 SPECIFICATIONS

- ◆间距: 2.0 Pitch:2.0
- ◆适用线规: AWG#24-#28
Applicable Wire:AWG#24-#28
- ◆额定电压: AC, DC, 125V (有效值)
Voltage rating: AC, DC, 125V(rms)
- ◆额定电流: 2A, AC, DC (AWG#24)
Current rating:2A, AC, DC (AWG#24)
- ◆耐压值: 500V AC/minute
Withstand voltage:500V AC/minute
- ◆工作温度: -25℃~+85℃
Working Temp:-25℃~+85℃
- ◆绝缘电阻: ≥1000MΩ
Insulation resistance:≥1000MΩ
- ◆接触电阻: ≤20mΩ
Contact resistance:≤20mΩ

材料 MATERIAL

- ◆绝缘体: 尼龙66, UL94-V2
Insulator:Nylon66 UL94-V2

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	 东莞市康导新能源科技有限公司 DONGGUAN KD NEW ENERGY TECHNOLOGY CO., LTD 公司网址: www.dgoonne.cn 公司电话: 0769-85337533 邮 箱: 2850175986@qq.com 公司传真: 0769-85392827	PART. NO: 51006-胶芯		
				LINEAR	ANGLES	APPROVED						DWG. NO:
				0.0±0.25	X° REF±6°	DESIGNER						
A0	新图面发行	2018. 12. 05		UNIT: MM	0.00±0.15	X° ±3°						TITLE: 2.00mm pitch Single Housing
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	肖丽娟	2018. 12. 05				