

	1	2	3	4	5	6	7	8																																																																																																																											
	ROHS						For reference only																																																																																																																												
A	<table><tr><td>Pin数</td><td>尺寸A</td><td>尺寸B</td></tr><tr><td>2×1</td><td>-</td><td>2.54</td></tr><tr><td>2×2</td><td>2.54</td><td>5.08</td></tr><tr><td>2×3</td><td>5.08</td><td>7.62</td></tr><tr><td>2×4</td><td>7.62</td><td>10.16</td></tr><tr><td>2×5</td><td>10.16</td><td>12.70</td></tr><tr><td>2×6</td><td>12.70</td><td>15.24</td></tr><tr><td>2×7</td><td>15.24</td><td>17.78</td></tr><tr><td>2×8</td><td>17.78</td><td>20.32</td></tr><tr><td>2×9</td><td>20.32</td><td>22.86</td></tr><tr><td>2×10</td><td>22.86</td><td>25.40</td></tr><tr><td>2×11</td><td>25.40</td><td>27.94</td></tr><tr><td>2×12</td><td>27.94</td><td>30.48</td></tr><tr><td>2×13</td><td>30.48</td><td>33.02</td></tr><tr><td>2×14</td><td>33.02</td><td>35.56</td></tr><tr><td>2×15</td><td>35.56</td><td>38.10</td></tr><tr><td>2×16</td><td>38.10</td><td>40.64</td></tr><tr><td>2×17</td><td>40.64</td><td>43.18</td></tr><tr><td>2×18</td><td>43.18</td><td>45.72</td></tr><tr><td>2×19</td><td>45.72</td><td>48.26</td></tr><tr><td>2×20</td><td>48.26</td><td>50.80</td></tr><tr><td>2×21</td><td>50.80</td><td>53.34</td></tr><tr><td>2×22</td><td>53.34</td><td>55.88</td></tr><tr><td>2×23</td><td>55.88</td><td>58.42</td></tr><tr><td>2×24</td><td>58.42</td><td>60.96</td></tr><tr><td>2×25</td><td>60.96</td><td>63.50</td></tr><tr><td>2×26</td><td>63.50</td><td>66.04</td></tr><tr><td>2×27</td><td>66.04</td><td>68.58</td></tr><tr><td>2×28</td><td>68.58</td><td>71.12</td></tr><tr><td>2×29</td><td>71.12</td><td>73.66</td></tr><tr><td>2×30</td><td>73.66</td><td>76.20</td></tr><tr><td>2×31</td><td>76.20</td><td>78.74</td></tr><tr><td>2×32</td><td>78.74</td><td>81.28</td></tr><tr><td>2×33</td><td>81.28</td><td>83.82</td></tr><tr><td>2×34</td><td>83.82</td><td>86.36</td></tr><tr><td>2×35</td><td>86.36</td><td>88.90</td></tr><tr><td>2×36</td><td>88.90</td><td>91.44</td></tr><tr><td>2×37</td><td>91.44</td><td>93.98</td></tr><tr><td>2×38</td><td>93.98</td><td>96.52</td></tr><tr><td>2×39</td><td>96.52</td><td>99.06</td></tr><tr><td>2×40</td><td>99.06</td><td>101.60</td></tr></table>		Pin数	尺寸A	尺寸B	2×1	-	2.54	2×2	2.54	5.08	2×3	5.08	7.62	2×4	7.62	10.16	2×5	10.16	12.70	2×6	12.70	15.24	2×7	15.24	17.78	2×8	17.78	20.32	2×9	20.32	22.86	2×10	22.86	25.40	2×11	25.40	27.94	2×12	27.94	30.48	2×13	30.48	33.02	2×14	33.02	35.56	2×15	35.56	38.10	2×16	38.10	40.64	2×17	40.64	43.18	2×18	43.18	45.72	2×19	45.72	48.26	2×20	48.26	50.80	2×21	50.80	53.34	2×22	53.34	55.88	2×23	55.88	58.42	2×24	58.42	60.96	2×25	60.96	63.50	2×26	63.50	66.04	2×27	66.04	68.58	2×28	68.58	71.12	2×29	71.12	73.66	2×30	73.66	76.20	2×31	76.20	78.74	2×32	78.74	81.28	2×33	81.28	83.82	2×34	83.82	86.36	2×35	86.36	88.90	2×36	88.90	91.44	2×37	91.44	93.98	2×38	93.98	96.52	2×39	96.52	99.06	2×40	99.06	101.60			Specification: Current Rating : 3.0AMP Temperature Range : -40℃to+105℃ Contact Resistance : 20mΩ Max Insulation Resistance : 1000MΩ Min Withstanding Voltage : AC 1000V Material: Insulator : Polyester (UL94V-0) Standard:PBT/PA6T/LCP Contact: Brass Plating : Au or Sn Over 50u" Ni			
Pin数	尺寸A	尺寸B																																																																																																																																	
2×1	-	2.54																																																																																																																																	
2×2	2.54	5.08																																																																																																																																	
2×3	5.08	7.62																																																																																																																																	
2×4	7.62	10.16																																																																																																																																	
2×5	10.16	12.70																																																																																																																																	
2×6	12.70	15.24																																																																																																																																	
2×7	15.24	17.78																																																																																																																																	
2×8	17.78	20.32																																																																																																																																	
2×9	20.32	22.86																																																																																																																																	
2×10	22.86	25.40																																																																																																																																	
2×11	25.40	27.94																																																																																																																																	
2×12	27.94	30.48																																																																																																																																	
2×13	30.48	33.02																																																																																																																																	
2×14	33.02	35.56																																																																																																																																	
2×15	35.56	38.10																																																																																																																																	
2×16	38.10	40.64																																																																																																																																	
2×17	40.64	43.18																																																																																																																																	
2×18	43.18	45.72																																																																																																																																	
2×19	45.72	48.26																																																																																																																																	
2×20	48.26	50.80																																																																																																																																	
2×21	50.80	53.34																																																																																																																																	
2×22	53.34	55.88																																																																																																																																	
2×23	55.88	58.42																																																																																																																																	
2×24	58.42	60.96																																																																																																																																	
2×25	60.96	63.50																																																																																																																																	
2×26	63.50	66.04																																																																																																																																	
2×27	66.04	68.58																																																																																																																																	
2×28	68.58	71.12																																																																																																																																	
2×29	71.12	73.66																																																																																																																																	
2×30	73.66	76.20																																																																																																																																	
2×31	76.20	78.74																																																																																																																																	
2×32	78.74	81.28																																																																																																																																	
2×33	81.28	83.82																																																																																																																																	
2×34	83.82	86.36																																																																																																																																	
2×35	86.36	88.90																																																																																																																																	
2×36	88.90	91.44																																																																																																																																	
2×37	91.44	93.98																																																																																																																																	
2×38	93.98	96.52																																																																																																																																	
2×39	96.52	99.06																																																																																																																																	
2×40	99.06	101.60																																																																																																																																	
B																																																																																																																																			
C																																																																																																																																			
D																																																																																																																																			
E					P 25 0D-XXX X X-XX-X-XXX ① Series No: ② Pitch: ③ Tail&Mounting Style: ④ No. of Pins: ⑤ Insulator Color: P=Pin Header 08=0.80 9D=Right Angle DIP Type Single Row Double Row A:Black B:Brown C:Red F=Female Header 10=1.00 9S=Straight SMT Type 101=1*1Pin 201=2*1Pin D:Orange E:Yellow F:Green B=Box Header 12=1.27 00=Straight DIP Type 102=1*2Pin 202=2*2Pin G:Blue H:Violet J:Gray E=Injector Header 20=2.00 0S=Horizontal SMT Type i i i i K:White P:Light Blue 25=2.54 39=3.96 50=5.08 140=1*40pin 240=2*40pin																																																																																																																														
F																																																																																																																																			
G																																																																																																																																			
H																																																																																																																																			
					<table><tr><td colspan="2">GENERAL TOLERANCES</td><td>SCALE: 1:1</td><td>NAME</td><td>DATE</td></tr><tr><td>LINEAR</td><td>ANGLES</td><td>APPROVED</td><td></td><td></td></tr><tr><td>0.0±0.25</td><td>X° REF±6°</td><td>DESIGNER</td><td></td><td></td></tr><tr><td>0.00±0.15</td><td>X° ±3°</td><td>DRAWN</td><td></td><td></td></tr><tr><td>0.000±0.08</td><td>X° X'±2°</td><td></td><td></td><td></td></tr></table>				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	LINEAR	ANGLES	APPROVED			0.0±0.25	X° REF±6°	DESIGNER			0.00±0.15	X° ±3°	DRAWN			0.000±0.08	X° X'±2°																																																																																																					
GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE																																																																																																																															
LINEAR	ANGLES	APPROVED																																																																																																																																	
0.0±0.25	X° REF±6°	DESIGNER																																																																																																																																	
0.00±0.15	X° ±3°	DRAWN																																																																																																																																	
0.000±0.08	X° X'±2°																																																																																																																																		
					<table><tr><td colspan="2">东 莞 市 康 号 新 能 源 科 技 有 限 公 司</td><td colspan="2">PART. NO:</td></tr><tr><td colspan="2">DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD.</td><td colspan="2">KDPH-0110</td></tr><tr><td colspan="2">Web: www.dgconne.com Tel: 0769-85337633</td><td colspan="2">DWG. NO:</td></tr><tr><td colspan="2">Email: 2850175986@qq.com Fax: 0769-85392827</td><td colspan="2">ENDE0110</td></tr><tr><td colspan="2">TITLE:</td><td colspan="2">REV: AO</td></tr><tr><td colspan="2">Pitch2.54mm Pin Header, Single Plastic, Dual Row, DIP</td><td colspan="2">SHEET: 1/1</td></tr></table>				东 莞 市 康 号 新 能 源 科 技 有 限 公 司		PART. NO:		DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD.		KDPH-0110		Web: www.dgconne.com Tel: 0769-85337633		DWG. NO:		Email: 2850175986@qq.com Fax: 0769-85392827		ENDE0110		TITLE:		REV: AO		Pitch2.54mm Pin Header, Single Plastic, Dual Row, DIP		SHEET: 1/1																																																																																																				
东 莞 市 康 号 新 能 源 科 技 有 限 公 司		PART. NO:																																																																																																																																	
DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD.		KDPH-0110																																																																																																																																	
Web: www.dgconne.com Tel: 0769-85337633		DWG. NO:																																																																																																																																	
Email: 2850175986@qq.com Fax: 0769-85392827		ENDE0110																																																																																																																																	
TITLE:		REV: AO																																																																																																																																	
Pitch2.54mm Pin Header, Single Plastic, Dual Row, DIP		SHEET: 1/1																																																																																																																																	
	1	2	3	4	5	6	7	8																																																																																																																											