

1		2		3		4		5		6		7		8																																																																																																																																																							
ROHS														For reference only																																																																																																																																																							
A	<table><tr><td>Pin数</td><td>尺寸A</td><td>尺寸B</td></tr><tr><td>1x2</td><td>1.27</td><td>2.94</td></tr><tr><td>1x3</td><td>2.54</td><td>4.21</td></tr><tr><td>1x4</td><td>3.81</td><td>5.48</td></tr><tr><td>1x5</td><td>5.08</td><td>6.75</td></tr><tr><td>1x6</td><td>6.35</td><td>8.02</td></tr><tr><td>1x7</td><td>7.62</td><td>9.29</td></tr><tr><td>1x8</td><td>8.89</td><td>10.56</td></tr><tr><td>1x9</td><td>10.16</td><td>11.83</td></tr><tr><td>1x10</td><td>11.43</td><td>13.10</td></tr><tr><td>1x11</td><td>12.70</td><td>14.37</td></tr><tr><td>1x12</td><td>13.97</td><td>15.64</td></tr><tr><td>1x13</td><td>15.24</td><td>16.91</td></tr><tr><td>1x14</td><td>16.51</td><td>18.18</td></tr><tr><td>1x15</td><td>17.78</td><td>19.45</td></tr><tr><td>1x16</td><td>19.05</td><td>20.72</td></tr><tr><td>1x17</td><td>20.32</td><td>21.99</td></tr><tr><td>1x18</td><td>21.59</td><td>23.26</td></tr><tr><td>1x19</td><td>22.86</td><td>24.53</td></tr><tr><td>1x20</td><td>24.13</td><td>25.80</td></tr><tr><td>1x21</td><td>25.40</td><td>27.07</td></tr><tr><td>1x22</td><td>26.67</td><td>28.34</td></tr><tr><td>1x23</td><td>27.94</td><td>29.61</td></tr><tr><td>1x24</td><td>29.21</td><td>30.88</td></tr><tr><td>1x25</td><td>30.48</td><td>32.15</td></tr><tr><td>1x26</td><td>31.75</td><td>33.42</td></tr><tr><td>1x27</td><td>33.02</td><td>34.69</td></tr><tr><td>1x28</td><td>34.29</td><td>35.96</td></tr><tr><td>1x29</td><td>35.56</td><td>37.23</td></tr><tr><td>1x30</td><td>36.83</td><td>38.50</td></tr><tr><td>1x31</td><td>38.10</td><td>39.77</td></tr><tr><td>1x32</td><td>39.37</td><td>41.04</td></tr><tr><td>1x33</td><td>40.64</td><td>42.31</td></tr><tr><td>1x34</td><td>41.91</td><td>43.58</td></tr><tr><td>1x35</td><td>43.18</td><td>44.85</td></tr><tr><td>1x36</td><td>44.45</td><td>46.12</td></tr><tr><td>1x37</td><td>45.72</td><td>47.39</td></tr><tr><td>1x38</td><td>46.99</td><td>48.66</td></tr><tr><td>1x39</td><td>48.26</td><td>49.93</td></tr><tr><td>1x40</td><td>49.53</td><td>51.20</td></tr><tr><td>1x41</td><td>50.80</td><td>52.47</td></tr><tr><td>1x42</td><td>52.07</td><td>53.74</td></tr><tr><td>1x43</td><td>53.34</td><td>55.01</td></tr><tr><td>1x44</td><td>54.61</td><td>56.28</td></tr><tr><td>1x45</td><td>55.88</td><td>57.55</td></tr><tr><td>1x46</td><td>57.15</td><td>58.82</td></tr><tr><td>1x47</td><td>58.42</td><td>60.09</td></tr><tr><td>1x48</td><td>59.69</td><td>61.36</td></tr><tr><td>1x49</td><td>60.96</td><td>62.63</td></tr><tr><td>1x50</td><td>62.23</td><td>63.90</td></tr></table>		Pin数	尺寸A	尺寸B	1x2	1.27	2.94	1x3	2.54	4.21	1x4	3.81	5.48	1x5	5.08	6.75	1x6	6.35	8.02	1x7	7.62	9.29	1x8	8.89	10.56	1x9	10.16	11.83	1x10	11.43	13.10	1x11	12.70	14.37	1x12	13.97	15.64	1x13	15.24	16.91	1x14	16.51	18.18	1x15	17.78	19.45	1x16	19.05	20.72	1x17	20.32	21.99	1x18	21.59	23.26	1x19	22.86	24.53	1x20	24.13	25.80	1x21	25.40	27.07	1x22	26.67	28.34	1x23	27.94	29.61	1x24	29.21	30.88	1x25	30.48	32.15	1x26	31.75	33.42	1x27	33.02	34.69	1x28	34.29	35.96	1x29	35.56	37.23	1x30	36.83	38.50	1x31	38.10	39.77	1x32	39.37	41.04	1x33	40.64	42.31	1x34	41.91	43.58	1x35	43.18	44.85	1x36	44.45	46.12	1x37	45.72	47.39	1x38	46.99	48.66	1x39	48.26	49.93	1x40	49.53	51.20	1x41	50.80	52.47	1x42	52.07	53.74	1x43	53.34	55.01	1x44	54.61	56.28	1x45	55.88	57.55	1x46	57.15	58.82	1x47	58.42	60.09	1x48	59.69	61.36	1x49	60.96	62.63	1x50	62.23	63.90													A
Pin数	尺寸A	尺寸B																																																																																																																																																																			
1x2	1.27	2.94																																																																																																																																																																			
1x3	2.54	4.21																																																																																																																																																																			
1x4	3.81	5.48																																																																																																																																																																			
1x5	5.08	6.75																																																																																																																																																																			
1x6	6.35	8.02																																																																																																																																																																			
1x7	7.62	9.29																																																																																																																																																																			
1x8	8.89	10.56																																																																																																																																																																			
1x9	10.16	11.83																																																																																																																																																																			
1x10	11.43	13.10																																																																																																																																																																			
1x11	12.70	14.37																																																																																																																																																																			
1x12	13.97	15.64																																																																																																																																																																			
1x13	15.24	16.91																																																																																																																																																																			
1x14	16.51	18.18																																																																																																																																																																			
1x15	17.78	19.45																																																																																																																																																																			
1x16	19.05	20.72																																																																																																																																																																			
1x17	20.32	21.99																																																																																																																																																																			
1x18	21.59	23.26																																																																																																																																																																			
1x19	22.86	24.53																																																																																																																																																																			
1x20	24.13	25.80																																																																																																																																																																			
1x21	25.40	27.07																																																																																																																																																																			
1x22	26.67	28.34																																																																																																																																																																			
1x23	27.94	29.61																																																																																																																																																																			
1x24	29.21	30.88																																																																																																																																																																			
1x25	30.48	32.15																																																																																																																																																																			
1x26	31.75	33.42																																																																																																																																																																			
1x27	33.02	34.69																																																																																																																																																																			
1x28	34.29	35.96																																																																																																																																																																			
1x29	35.56	37.23																																																																																																																																																																			
1x30	36.83	38.50																																																																																																																																																																			
1x31	38.10	39.77																																																																																																																																																																			
1x32	39.37	41.04																																																																																																																																																																			
1x33	40.64	42.31																																																																																																																																																																			
1x34	41.91	43.58																																																																																																																																																																			
1x35	43.18	44.85																																																																																																																																																																			
1x36	44.45	46.12																																																																																																																																																																			
1x37	45.72	47.39																																																																																																																																																																			
1x38	46.99	48.66																																																																																																																																																																			
1x39	48.26	49.93																																																																																																																																																																			
1x40	49.53	51.20																																																																																																																																																																			
1x41	50.80	52.47																																																																																																																																																																			
1x42	52.07	53.74																																																																																																																																																																			
1x43	53.34	55.01																																																																																																																																																																			
1x44	54.61	56.28																																																																																																																																																																			
1x45	55.88	57.55																																																																																																																																																																			
1x46	57.15	58.82																																																																																																																																																																			
1x47	58.42	60.09																																																																																																																																																																			
1x48	59.69	61.36																																																																																																																																																																			
1x49	60.96	62.63																																																																																																																																																																			
1x50	62.23	63.90																																																																																																																																																																			
B															B																																																																																																																																																						
C															C																																																																																																																																																						
D															D																																																																																																																																																						
E															E																																																																																																																																																						
F			<table><tr><td colspan="2">① Series No:</td><td colspan="2">② Pitch:</td><td colspan="2">③ Tail&Mounting Style:</td><td colspan="2">④ No. of Pins:</td><td colspan="2">⑤ Insulator Color:</td></tr><tr><td colspan="2">P=Pin Header</td><td colspan="2">08=0.80</td><td colspan="2">90=Right Angle DIP Type</td><td colspan="2">Single Row Double Row</td><td colspan="2">A:Black B:Brom C:Red</td></tr><tr><td colspan="2">F=Female Header</td><td colspan="2">10=1.00</td><td colspan="2">9S=Straight SMT Type</td><td colspan="2">101=1*1Pin 201=2*1Pin</td><td colspan="2">D:Orange E:Yellow F:Green</td></tr><tr><td colspan="2">B=Box Header</td><td colspan="2">12=1.27</td><td colspan="2">0D=Straight DIP Type</td><td colspan="2">102=1*2Pin 202=2*2Pin</td><td colspan="2">G:Blue H:Violet J:Gray</td></tr><tr><td colspan="2">E=Ejector Header</td><td colspan="2">20=2.00</td><td colspan="2">0S=horizontal SMT Type</td><td colspan="2">110=1*40pin 240=2*40pin</td><td colspan="2">K:White P:Light Blue</td></tr><tr><td colspan="2"></td><td colspan="2">25=2.54</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2">39=3.96</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2">50=5.08</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr></table>												① Series No:		② Pitch:		③ Tail&Mounting Style:		④ No. of Pins:		⑤ Insulator Color:		P=Pin Header		08=0.80		90=Right Angle DIP Type		Single Row Double Row		A:Black B:Brom C:Red		F=Female Header		10=1.00		9S=Straight SMT Type		101=1*1Pin 201=2*1Pin		D:Orange E:Yellow F:Green		B=Box Header		12=1.27		0D=Straight DIP Type		102=1*2Pin 202=2*2Pin		G:Blue H:Violet J:Gray		E=Ejector Header		20=2.00		0S=horizontal SMT Type		110=1*40pin 240=2*40pin		K:White P:Light Blue				25=2.54										39=3.96										50=5.08								F																																																																						
① Series No:		② Pitch:		③ Tail&Mounting Style:		④ No. of Pins:		⑤ Insulator Color:																																																																																																																																																													
P=Pin Header		08=0.80		90=Right Angle DIP Type		Single Row Double Row		A:Black B:Brom C:Red																																																																																																																																																													
F=Female Header		10=1.00		9S=Straight SMT Type		101=1*1Pin 201=2*1Pin		D:Orange E:Yellow F:Green																																																																																																																																																													
B=Box Header		12=1.27		0D=Straight DIP Type		102=1*2Pin 202=2*2Pin		G:Blue H:Violet J:Gray																																																																																																																																																													
E=Ejector Header		20=2.00		0S=horizontal SMT Type		110=1*40pin 240=2*40pin		K:White P:Light Blue																																																																																																																																																													
		25=2.54																																																																																																																																																																			
		39=3.96																																																																																																																																																																			
		50=5.08																																																																																																																																																																			
G			<table><tr><td colspan="2">⑥ Material Type:</td><td colspan="2">⑦ Plating Type:</td><td colspan="2">⑧ RoHS Request:</td><td colspan="2">⑨ Customer Code</td></tr><tr><td colspan="2">A=PBT</td><td colspan="2">0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au</td><td colspan="2">0:No Request</td><td colspan="2"></td></tr><tr><td colspan="2">B=PA46</td><td colspan="2">0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"</td><td colspan="2">1:RoHS</td><td colspan="2"></td></tr><tr><td colspan="2">C=PA6T</td><td colspan="2">0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"</td><td colspan="2">2:HF (Halogen Free)</td><td colspan="2"></td></tr><tr><td colspan="2">D=PA9T</td><td colspan="2">0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"</td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">E=LCP</td><td colspan="2">0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"</td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2">0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"</td><td colspan="2"></td><td colspan="2"></td></tr></table>												⑥ Material Type:		⑦ Plating Type:		⑧ RoHS Request:		⑨ Customer Code		A=PBT		0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au		0:No Request				B=PA46		0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"		1:RoHS				C=PA6T		0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"		2:HF (Halogen Free)				D=PA9T		0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"						E=LCP		0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"								0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"						G																																																																																														
⑥ Material Type:		⑦ Plating Type:		⑧ RoHS Request:		⑨ Customer Code																																																																																																																																																															
A=PBT		0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au		0:No Request																																																																																																																																																																	
B=PA46		0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"		1:RoHS																																																																																																																																																																	
C=PA6T		0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"		2:HF (Halogen Free)																																																																																																																																																																	
D=PA9T		0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"																																																																																																																																																																			
E=LCP		0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"																																																																																																																																																																			
		0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"																																																																																																																																																																			
H			<table><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2">GENERAL TOLERANCES</td><td colspan="2">SCALE: 1:1</td><td colspan="2">NAME</td><td colspan="2">DATE</td><td colspan="2">PART. NO:</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">APPROVED</td><td colspan="2"></td><td colspan="2"></td><td colspan="2">KDFH-0025</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">DESIGNER</td><td colspan="2"></td><td colspan="2"></td><td colspan="2">DWG. NO:</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">DRAWN</td><td colspan="2"></td><td colspan="2"></td><td colspan="2">ENDE1025</td></tr><tr><td colspan="2">REV.</td><td colspan="2">REVISION RECORD</td><td colspan="2">DATE</td><td colspan="2">UNIT: MM</td><td colspan="2">SIZE: A4</td><td colspan="2">TITLE: Pitch1.27mm Female Header, Single Row, Plastic Height 3.4mm, SMT Type(U)</td><td colspan="2">REV: A0 SHEET: 1/1</td></tr></table>																GENERAL TOLERANCES		SCALE: 1:1		NAME		DATE		PART. NO:								APPROVED						KDFH-0025								DESIGNER						DWG. NO:								DRAWN						ENDE1025		REV.		REVISION RECORD		DATE		UNIT: MM		SIZE: A4		TITLE: Pitch1.27mm Female Header, Single Row, Plastic Height 3.4mm, SMT Type(U)		REV: A0 SHEET: 1/1		H																																																																																
				GENERAL TOLERANCES		SCALE: 1:1		NAME		DATE		PART. NO:																																																																																																																																																									
						APPROVED						KDFH-0025																																																																																																																																																									
						DESIGNER						DWG. NO:																																																																																																																																																									
						DRAWN						ENDE1025																																																																																																																																																									
REV.		REVISION RECORD		DATE		UNIT: MM		SIZE: A4		TITLE: Pitch1.27mm Female Header, Single Row, Plastic Height 3.4mm, SMT Type(U)		REV: A0 SHEET: 1/1																																																																																																																																																									
1		2		3		4		5		6		7		8																																																																																																																																																							

Specification:
Current Rating : 1AMP
Temperature Range : -40℃to+105℃
Contact Resistance : 20mΩ Max
Insulation Resistance : 1000MΩ Min
Withstanding Voltage : AC 500V
Material:
Insulator : Polyester (UL94V-0)
Standard:PA6T/LCP
Contact: Bronze
Plating : Au or Sn Over 50u" Ni

 东莞市康号新能源科技有限公司
DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD.
Web: www.dgconne.com Tel: 0769-85337633
Email: 2850175986@qq.com Fax: 0769-85392827