

	1	2	3	4	5	6	7	8																																																																																																																																																						
A	ROHS		For reference only																																																																																																																																																											
B	<table><tr><td>Pin数</td><td>尺寸A</td><td>尺寸B</td></tr><tr><td>1x2</td><td>1.27</td><td>2.94</td></tr><tr><td>1x3</td><td>2.54</td><td>4.21</td></tr><tr><td>1x4</td><td>3.81</td><td>5.48</td></tr><tr><td>1x5</td><td>5.08</td><td>6.75</td></tr><tr><td>1x6</td><td>6.35</td><td>8.02</td></tr><tr><td>1x7</td><td>7.62</td><td>9.29</td></tr><tr><td>1x8</td><td>8.89</td><td>10.56</td></tr><tr><td>1x9</td><td>10.16</td><td>11.83</td></tr><tr><td>1x10</td><td>11.43</td><td>13.10</td></tr><tr><td>1x11</td><td>12.70</td><td>14.37</td></tr><tr><td>1x12</td><td>13.97</td><td>15.64</td></tr><tr><td>1x13</td><td>15.24</td><td>16.91</td></tr><tr><td>1x14</td><td>16.51</td><td>18.18</td></tr><tr><td>1x15</td><td>17.78</td><td>19.45</td></tr><tr><td>1x16</td><td>19.05</td><td>20.72</td></tr><tr><td>1x17</td><td>20.32</td><td>21.99</td></tr><tr><td>1x18</td><td>21.59</td><td>23.26</td></tr><tr><td>1x19</td><td>22.86</td><td>24.53</td></tr><tr><td>1x20</td><td>24.13</td><td>25.80</td></tr><tr><td>1x21</td><td>25.40</td><td>27.07</td></tr><tr><td>1x22</td><td>26.67</td><td>28.34</td></tr><tr><td>1x23</td><td>27.94</td><td>29.61</td></tr><tr><td>1x24</td><td>29.21</td><td>30.88</td></tr><tr><td>1x25</td><td>30.48</td><td>32.15</td></tr><tr><td>1x26</td><td>31.75</td><td>33.42</td></tr><tr><td>1x27</td><td>33.02</td><td>34.69</td></tr><tr><td>1x28</td><td>34.29</td><td>35.96</td></tr><tr><td>1x29</td><td>35.56</td><td>37.23</td></tr><tr><td>1x30</td><td>36.83</td><td>38.50</td></tr><tr><td>1x31</td><td>38.10</td><td>39.77</td></tr><tr><td>1x32</td><td>39.37</td><td>41.04</td></tr><tr><td>1x33</td><td>40.64</td><td>42.31</td></tr><tr><td>1x34</td><td>41.91</td><td>43.58</td></tr><tr><td>1x35</td><td>43.18</td><td>44.85</td></tr><tr><td>1x36</td><td>44.45</td><td>46.12</td></tr><tr><td>1x37</td><td>45.72</td><td>47.39</td></tr><tr><td>1x38</td><td>46.99</td><td>48.66</td></tr><tr><td>1x39</td><td>48.26</td><td>49.93</td></tr><tr><td>1x40</td><td>49.53</td><td>51.20</td></tr><tr><td>1x41</td><td>50.80</td><td>52.47</td></tr><tr><td>1x42</td><td>52.07</td><td>53.74</td></tr><tr><td>1x43</td><td>53.34</td><td>55.01</td></tr><tr><td>1x44</td><td>54.61</td><td>56.28</td></tr><tr><td>1x45</td><td>55.88</td><td>57.55</td></tr><tr><td>1x46</td><td>57.15</td><td>58.82</td></tr><tr><td>1x47</td><td>58.42</td><td>60.09</td></tr><tr><td>1x48</td><td>59.69</td><td>61.36</td></tr><tr><td>1x49</td><td>60.96</td><td>62.63</td></tr><tr><td>1x50</td><td>62.23</td><td>63.90</td></tr></table>		Pin数	尺寸A	尺寸B	1x2	1.27	2.94	1x3	2.54	4.21	1x4	3.81	5.48	1x5	5.08	6.75	1x6	6.35	8.02	1x7	7.62	9.29	1x8	8.89	10.56	1x9	10.16	11.83	1x10	11.43	13.10	1x11	12.70	14.37	1x12	13.97	15.64	1x13	15.24	16.91	1x14	16.51	18.18	1x15	17.78	19.45	1x16	19.05	20.72	1x17	20.32	21.99	1x18	21.59	23.26	1x19	22.86	24.53	1x20	24.13	25.80	1x21	25.40	27.07	1x22	26.67	28.34	1x23	27.94	29.61	1x24	29.21	30.88	1x25	30.48	32.15	1x26	31.75	33.42	1x27	33.02	34.69	1x28	34.29	35.96	1x29	35.56	37.23	1x30	36.83	38.50	1x31	38.10	39.77	1x32	39.37	41.04	1x33	40.64	42.31	1x34	41.91	43.58	1x35	43.18	44.85	1x36	44.45	46.12	1x37	45.72	47.39	1x38	46.99	48.66	1x39	48.26	49.93	1x40	49.53	51.20	1x41	50.80	52.47	1x42	52.07	53.74	1x43	53.34	55.01	1x44	54.61	56.28	1x45	55.88	57.55	1x46	57.15	58.82	1x47	58.42	60.09	1x48	59.69	61.36	1x49	60.96	62.63	1x50	62.23	63.90						
Pin数	尺寸A	尺寸B																																																																																																																																																												
1x2	1.27	2.94																																																																																																																																																												
1x3	2.54	4.21																																																																																																																																																												
1x4	3.81	5.48																																																																																																																																																												
1x5	5.08	6.75																																																																																																																																																												
1x6	6.35	8.02																																																																																																																																																												
1x7	7.62	9.29																																																																																																																																																												
1x8	8.89	10.56																																																																																																																																																												
1x9	10.16	11.83																																																																																																																																																												
1x10	11.43	13.10																																																																																																																																																												
1x11	12.70	14.37																																																																																																																																																												
1x12	13.97	15.64																																																																																																																																																												
1x13	15.24	16.91																																																																																																																																																												
1x14	16.51	18.18																																																																																																																																																												
1x15	17.78	19.45																																																																																																																																																												
1x16	19.05	20.72																																																																																																																																																												
1x17	20.32	21.99																																																																																																																																																												
1x18	21.59	23.26																																																																																																																																																												
1x19	22.86	24.53																																																																																																																																																												
1x20	24.13	25.80																																																																																																																																																												
1x21	25.40	27.07																																																																																																																																																												
1x22	26.67	28.34																																																																																																																																																												
1x23	27.94	29.61																																																																																																																																																												
1x24	29.21	30.88																																																																																																																																																												
1x25	30.48	32.15																																																																																																																																																												
1x26	31.75	33.42																																																																																																																																																												
1x27	33.02	34.69																																																																																																																																																												
1x28	34.29	35.96																																																																																																																																																												
1x29	35.56	37.23																																																																																																																																																												
1x30	36.83	38.50																																																																																																																																																												
1x31	38.10	39.77																																																																																																																																																												
1x32	39.37	41.04																																																																																																																																																												
1x33	40.64	42.31																																																																																																																																																												
1x34	41.91	43.58																																																																																																																																																												
1x35	43.18	44.85																																																																																																																																																												
1x36	44.45	46.12																																																																																																																																																												
1x37	45.72	47.39																																																																																																																																																												
1x38	46.99	48.66																																																																																																																																																												
1x39	48.26	49.93																																																																																																																																																												
1x40	49.53	51.20																																																																																																																																																												
1x41	50.80	52.47																																																																																																																																																												
1x42	52.07	53.74																																																																																																																																																												
1x43	53.34	55.01																																																																																																																																																												
1x44	54.61	56.28																																																																																																																																																												
1x45	55.88	57.55																																																																																																																																																												
1x46	57.15	58.82																																																																																																																																																												
1x47	58.42	60.09																																																																																																																																																												
1x48	59.69	61.36																																																																																																																																																												
1x49	60.96	62.63																																																																																																																																																												
1x50	62.23	63.90																																																																																																																																																												
C																																																																																																																																																														
D																																																																																																																																																														
E																																																																																																																																																														
F																																																																																																																																																														
G	<table><tr><td>① Series No:</td><td>② Pitch:</td><td>③ Tail&Mounting Style:</td><td>④ No. of Pins:</td><td>⑤ Insulator Color:</td></tr><tr><td>P=Pin Header F=Female Header E=Ejector Header</td><td>08=0.80 10=1.00 12=1.27 20=2.00 25=2.54 39=3.96 50=5.08</td><td>90=Right Angle DIP Type 9S=Straight SMT Type 0D=Straight DIP Type 0S=Horizontal SMT Type</td><td>Single Row Double Row 101=1x1Pin 201=2x1Pin 102=1x2Pin 202=2x2Pin ! ! ! 140=1x40pin 240=2x40pin</td><td>A:Black B:Brown C:Red D:Orange E:Yellow F:Green G:Blue H:Violet J:Gray K:White P:Light Blue</td></tr><tr><td>⑥ Material Type: A-PBT B-PA46 C-PA6T D-PA9T E-LCP</td><td>⑦ Plating Type: 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au 0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u" 0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u" 0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u" 0D-Sn-Au 4u" 0I-Sn-Au 40u" : 0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"</td><td>⑧ RoHS Request: 0:No Request 1:RoHS 2:HF(Halogen Free)</td><td>⑨ Customer Code</td></tr></table>		① Series No:	② Pitch:	③ Tail&Mounting Style:	④ No. of Pins:	⑤ Insulator Color:	P=Pin Header F=Female Header E=Ejector Header	08=0.80 10=1.00 12=1.27 20=2.00 25=2.54 39=3.96 50=5.08	90=Right Angle DIP Type 9S=Straight SMT Type 0D=Straight DIP Type 0S=Horizontal SMT Type	Single Row Double Row 101=1x1Pin 201=2x1Pin 102=1x2Pin 202=2x2Pin ! ! ! 140=1x40pin 240=2x40pin	A:Black B:Brown C:Red D:Orange E:Yellow F:Green G:Blue H:Violet J:Gray K:White P:Light Blue	⑥ Material Type: A-PBT B-PA46 C-PA6T D-PA9T E-LCP	⑦ Plating Type: 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au 0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u" 0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u" 0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u" 0D-Sn-Au 4u" 0I-Sn-Au 40u" : 0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"	⑧ RoHS Request: 0:No Request 1:RoHS 2:HF(Halogen Free)	⑨ Customer Code																																																																																																																																														
① Series No:	② Pitch:	③ Tail&Mounting Style:	④ No. of Pins:	⑤ Insulator Color:																																																																																																																																																										
P=Pin Header F=Female Header E=Ejector Header	08=0.80 10=1.00 12=1.27 20=2.00 25=2.54 39=3.96 50=5.08	90=Right Angle DIP Type 9S=Straight SMT Type 0D=Straight DIP Type 0S=Horizontal SMT Type	Single Row Double Row 101=1x1Pin 201=2x1Pin 102=1x2Pin 202=2x2Pin ! ! ! 140=1x40pin 240=2x40pin	A:Black B:Brown C:Red D:Orange E:Yellow F:Green G:Blue H:Violet J:Gray K:White P:Light Blue																																																																																																																																																										
⑥ Material Type: A-PBT B-PA46 C-PA6T D-PA9T E-LCP	⑦ Plating Type: 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au 0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u" 0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u" 0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u" 0D-Sn-Au 4u" 0I-Sn-Au 40u" : 0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"	⑧ RoHS Request: 0:No Request 1:RoHS 2:HF(Halogen Free)	⑨ Customer Code																																																																																																																																																											
H	<table><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>REV.</td><td colspan="2">REVISION RECORD</td><td>DATE</td><td>SIZE: A4</td><td>0.000±0.08</td><td>X° X'±2°</td><td colspan="2">DRAWN</td></tr></table>																																						REV.	REVISION RECORD		DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN		<table><tr><td colspan="2">GENERAL TOLERANCES</td><td>SCALE: 1:1</td><td>NAME</td><td>DATE</td></tr><tr><td>LINEAR</td><td>ANGLES</td><td></td><td></td><td></td></tr><tr><td>0.0 ± 0.25</td><td>X° REF ± 6°</td><td>APPROVED</td><td></td><td></td></tr><tr><td>0.00 ± 0.15</td><td>X° ± 3°</td><td>DESIGNER</td><td></td><td></td></tr><tr><td></td><td></td><td>DRAWN</td><td></td><td></td></tr></table>		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	LINEAR	ANGLES				0.0 ± 0.25	X° REF ± 6°	APPROVED			0.00 ± 0.15	X° ± 3°	DESIGNER					DRAWN			<table><tr><td colspan="2">东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827</td></tr><tr><td>TITLE: Pitch1.27mm Female Header, Single Row, Plastic Height 3.4mm, DIP(U)</td><td>PART. NO.: KDFH-0024</td></tr><tr><td></td><td>DWG. NO.: ENDE1024</td></tr><tr><td></td><td>REV: A0 SHEET: 1/1</td></tr></table>		东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827		TITLE: Pitch1.27mm Female Header, Single Row, Plastic Height 3.4mm, DIP(U)	PART. NO.: KDFH-0024		DWG. NO.: ENDE1024		REV: A0 SHEET: 1/1																																																																										
REV.	REVISION RECORD		DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN																																																																																																																																																							
GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE																																																																																																																																																										
LINEAR	ANGLES																																																																																																																																																													
0.0 ± 0.25	X° REF ± 6°	APPROVED																																																																																																																																																												
0.00 ± 0.15	X° ± 3°	DESIGNER																																																																																																																																																												
		DRAWN																																																																																																																																																												
东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827																																																																																																																																																														
TITLE: Pitch1.27mm Female Header, Single Row, Plastic Height 3.4mm, DIP(U)	PART. NO.: KDFH-0024																																																																																																																																																													
	DWG. NO.: ENDE1024																																																																																																																																																													
	REV: A0 SHEET: 1/1																																																																																																																																																													
	1	2	3	4	5	6	7	8																																																																																																																																																						