

1		2		3		4		5		6		7		8																																																																																																																											
ROHS														For reference only																																																																																																																											
A		<table><tr><td>Pin数</td><td>尺寸A</td><td>尺寸B</td></tr><tr><td>1X2</td><td>2.0</td><td>4.5</td></tr><tr><td>1X3</td><td>4.0</td><td>6.5</td></tr><tr><td>1X4</td><td>6.0</td><td>8.5</td></tr><tr><td>1X5</td><td>8.0</td><td>10.5</td></tr><tr><td>1X6</td><td>10.0</td><td>12.5</td></tr><tr><td>1X7</td><td>12.0</td><td>14.5</td></tr><tr><td>1X8</td><td>14.0</td><td>16.5</td></tr><tr><td>1X9</td><td>16.0</td><td>18.5</td></tr><tr><td>1X10</td><td>18.0</td><td>20.5</td></tr><tr><td>1X11</td><td>20.0</td><td>22.5</td></tr><tr><td>1X12</td><td>22.0</td><td>24.5</td></tr><tr><td>1X13</td><td>24.0</td><td>26.5</td></tr><tr><td>1X14</td><td>26.0</td><td>28.5</td></tr><tr><td>1X15</td><td>28.0</td><td>30.5</td></tr><tr><td>1X16</td><td>30.0</td><td>32.5</td></tr><tr><td>1X17</td><td>32.0</td><td>34.5</td></tr><tr><td>1X18</td><td>34.0</td><td>36.5</td></tr><tr><td>1X19</td><td>36.0</td><td>38.5</td></tr><tr><td>1X20</td><td>38.0</td><td>40.5</td></tr><tr><td>1X21</td><td>40.0</td><td>42.5</td></tr><tr><td>1X22</td><td>42.0</td><td>44.5</td></tr><tr><td>1X23</td><td>44.0</td><td>46.5</td></tr><tr><td>1X24</td><td>46.0</td><td>48.5</td></tr><tr><td>1X25</td><td>48.0</td><td>50.5</td></tr><tr><td>1X26</td><td>50.0</td><td>52.5</td></tr><tr><td>1X27</td><td>52.0</td><td>54.5</td></tr><tr><td>1X28</td><td>54.0</td><td>56.5</td></tr><tr><td>1X29</td><td>56.0</td><td>58.5</td></tr><tr><td>1X30</td><td>58.0</td><td>60.5</td></tr><tr><td>1X31</td><td>60.0</td><td>62.5</td></tr><tr><td>1X32</td><td>62.0</td><td>64.5</td></tr><tr><td>1X33</td><td>64.0</td><td>66.5</td></tr><tr><td>1X34</td><td>66.0</td><td>68.5</td></tr><tr><td>1X35</td><td>68.0</td><td>70.5</td></tr><tr><td>1X36</td><td>70.0</td><td>72.5</td></tr><tr><td>1X37</td><td>72.0</td><td>74.5</td></tr><tr><td>1X38</td><td>74.0</td><td>76.5</td></tr><tr><td>1X39</td><td>76.0</td><td>78.5</td></tr><tr><td>1X40</td><td>78.0</td><td>80.5</td></tr></table>														Pin数	尺寸A	尺寸B	1X2	2.0	4.5	1X3	4.0	6.5	1X4	6.0	8.5	1X5	8.0	10.5	1X6	10.0	12.5	1X7	12.0	14.5	1X8	14.0	16.5	1X9	16.0	18.5	1X10	18.0	20.5	1X11	20.0	22.5	1X12	22.0	24.5	1X13	24.0	26.5	1X14	26.0	28.5	1X15	28.0	30.5	1X16	30.0	32.5	1X17	32.0	34.5	1X18	34.0	36.5	1X19	36.0	38.5	1X20	38.0	40.5	1X21	40.0	42.5	1X22	42.0	44.5	1X23	44.0	46.5	1X24	46.0	48.5	1X25	48.0	50.5	1X26	50.0	52.5	1X27	52.0	54.5	1X28	54.0	56.5	1X29	56.0	58.5	1X30	58.0	60.5	1X31	60.0	62.5	1X32	62.0	64.5	1X33	64.0	66.5	1X34	66.0	68.5	1X35	68.0	70.5	1X36	70.0	72.5	1X37	72.0	74.5	1X38	74.0	76.5	1X39	76.0	78.5	1X40	78.0	80.5	A	
Pin数	尺寸A	尺寸B																																																																																																																																							
1X2	2.0	4.5																																																																																																																																							
1X3	4.0	6.5																																																																																																																																							
1X4	6.0	8.5																																																																																																																																							
1X5	8.0	10.5																																																																																																																																							
1X6	10.0	12.5																																																																																																																																							
1X7	12.0	14.5																																																																																																																																							
1X8	14.0	16.5																																																																																																																																							
1X9	16.0	18.5																																																																																																																																							
1X10	18.0	20.5																																																																																																																																							
1X11	20.0	22.5																																																																																																																																							
1X12	22.0	24.5																																																																																																																																							
1X13	24.0	26.5																																																																																																																																							
1X14	26.0	28.5																																																																																																																																							
1X15	28.0	30.5																																																																																																																																							
1X16	30.0	32.5																																																																																																																																							
1X17	32.0	34.5																																																																																																																																							
1X18	34.0	36.5																																																																																																																																							
1X19	36.0	38.5																																																																																																																																							
1X20	38.0	40.5																																																																																																																																							
1X21	40.0	42.5																																																																																																																																							
1X22	42.0	44.5																																																																																																																																							
1X23	44.0	46.5																																																																																																																																							
1X24	46.0	48.5																																																																																																																																							
1X25	48.0	50.5																																																																																																																																							
1X26	50.0	52.5																																																																																																																																							
1X27	52.0	54.5																																																																																																																																							
1X28	54.0	56.5																																																																																																																																							
1X29	56.0	58.5																																																																																																																																							
1X30	58.0	60.5																																																																																																																																							
1X31	60.0	62.5																																																																																																																																							
1X32	62.0	64.5																																																																																																																																							
1X33	64.0	66.5																																																																																																																																							
1X34	66.0	68.5																																																																																																																																							
1X35	68.0	70.5																																																																																																																																							
1X36	70.0	72.5																																																																																																																																							
1X37	72.0	74.5																																																																																																																																							
1X38	74.0	76.5																																																																																																																																							
1X39	76.0	78.5																																																																																																																																							
1X40	78.0	80.5																																																																																																																																							
B																B																																																																																																																									
C																C																																																																																																																									
D																D																																																																																																																									
E																E																																																																																																																									
F		<table><tr><td colspan="2">F 20 9D-XXX X X-XX-X-XXX</td></tr><tr><td>① Series No:</td><td>② Pitch:</td><td>③ Tail&Mounting Style:</td><td>④ No. of Pins:</td><td>⑤ Insulator Color:</td></tr><tr><td>P=Pin Header</td><td>08=0.80</td><td>9D=Right Angle DIP Type</td><td>Single Row Double Row</td><td>A:Black B:Brom C:Red</td></tr><tr><td>F=Female Header</td><td>10=1.00</td><td>9S=Straight SMT Type</td><td>101=1*1Pin 201=2*1Pin</td><td>D:Orange E:Yellow F:Green</td></tr><tr><td>B=Box Header</td><td>12=1.27</td><td>0D=Straight DIP Type</td><td>102=1*2Pin 202=2*2Pin</td><td>G:Blue H:Violet J:Gray</td></tr><tr><td>E=Ejector Header</td><td>20=2.00</td><td>0S=horizontal SMT Type</td><td>140=1*40pin 240=2*40pin</td><td>K:White P:Light Blue</td></tr><tr><td></td><td>25=2.54</td><td></td><td></td><td></td></tr><tr><td></td><td>39=3.96</td><td></td><td></td><td></td></tr><tr><td></td><td>50=5.08</td><td></td><td></td><td></td></tr></table>														F 20 9D-XXX X X-XX-X-XXX		① Series No:	② Pitch:	③ Tail&Mounting Style:	④ No. of Pins:	⑤ Insulator Color:	P=Pin Header	08=0.80	9D=Right Angle DIP Type	Single Row Double Row	A:Black B:Brom C:Red	F=Female Header	10=1.00	9S=Straight SMT Type	101=1*1Pin 201=2*1Pin	D:Orange E:Yellow F:Green	B=Box Header	12=1.27	0D=Straight DIP Type	102=1*2Pin 202=2*2Pin	G:Blue H:Violet J:Gray	E=Ejector Header	20=2.00	0S=horizontal SMT Type	140=1*40pin 240=2*40pin	K:White P:Light Blue		25=2.54					39=3.96					50=5.08				F																																																																															
F 20 9D-XXX X X-XX-X-XXX																																																																																																																																									
① Series No:	② Pitch:	③ Tail&Mounting Style:	④ No. of Pins:	⑤ Insulator Color:																																																																																																																																					
P=Pin Header	08=0.80	9D=Right Angle DIP Type	Single Row Double Row	A:Black B:Brom C:Red																																																																																																																																					
F=Female Header	10=1.00	9S=Straight SMT Type	101=1*1Pin 201=2*1Pin	D:Orange E:Yellow F:Green																																																																																																																																					
B=Box Header	12=1.27	0D=Straight DIP Type	102=1*2Pin 202=2*2Pin	G:Blue H:Violet J:Gray																																																																																																																																					
E=Ejector Header	20=2.00	0S=horizontal SMT Type	140=1*40pin 240=2*40pin	K:White P:Light Blue																																																																																																																																					
	25=2.54																																																																																																																																								
	39=3.96																																																																																																																																								
	50=5.08																																																																																																																																								
G		<table><tr><td>⑥ Material Type:</td><td>⑦ Plating Type:</td><td>⑧ RoHS Request:</td><td>⑨ Customer Code</td></tr><tr><td>A=PBT</td><td>0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au</td><td>0:No Request</td><td></td></tr><tr><td>B=PA46</td><td>0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"</td><td>1:RoHS</td><td></td></tr><tr><td>C=PA6T</td><td>0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"</td><td>2:HF (Halogen Free)</td><td></td></tr><tr><td>D=PA9T</td><td>0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"</td><td></td><td></td></tr><tr><td>E=LCP</td><td>0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"</td><td></td><td></td></tr><tr><td></td><td>0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"</td><td></td><td></td></tr></table>														⑥ Material Type:	⑦ Plating Type:	⑧ RoHS Request:	⑨ Customer Code	A=PBT	0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au	0:No Request		B=PA46	0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"	1:RoHS		C=PA6T	0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"	2:HF (Halogen Free)		D=PA9T	0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"			E=LCP	0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"				0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"			G																																																																																													
⑥ Material Type:	⑦ Plating Type:	⑧ RoHS Request:	⑨ Customer Code																																																																																																																																						
A=PBT	0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au	0:No Request																																																																																																																																							
B=PA46	0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"	1:RoHS																																																																																																																																							
C=PA6T	0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"	2:HF (Halogen Free)																																																																																																																																							
D=PA9T	0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"																																																																																																																																								
E=LCP	0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"																																																																																																																																								
	0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"																																																																																																																																								
H		<table><tr><td colspan="2">GENERAL TOLERANCES</td><td>SCALE: 1:1</td><td>NAME</td><td>DATE</td><td rowspan="4">东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827</td><td colspan="2">PART. NO:</td></tr><tr><td colspan="2">LINEAR</td><td>ANGLES</td><td>APPROVED</td><td></td><td colspan="2">KDFH-0066</td></tr><tr><td colspan="2">0.0±0.25</td><td>X° REF±6°</td><td>DESIGNER</td><td></td><td colspan="2">DWG. NO:</td></tr><tr><td colspan="2">0.00±0.15</td><td>X° ±3°</td><td>DRAWN</td><td></td><td colspan="2">ENDE1066</td></tr><tr><td>REV.</td><td>REVISION RECORD</td><td>DATE</td><td>UNIT: MM</td><td>0.00±0.15</td><td>X° X'±2°</td><td colspan="2">TITLE: Pitch2.0mm Female Header,Single Row, Plastic Height 2.0mm,Right Angle Type(U)</td><td>REV: AO</td><td>SHEET: 1/1</td></tr></table>														GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827	PART. NO:		LINEAR		ANGLES	APPROVED		KDFH-0066		0.0±0.25		X° REF±6°	DESIGNER		DWG. NO:		0.00±0.15		X° ±3°	DRAWN		ENDE1066		REV.	REVISION RECORD	DATE	UNIT: MM	0.00±0.15	X° X'±2°	TITLE: Pitch2.0mm Female Header,Single Row, Plastic Height 2.0mm,Right Angle Type(U)		REV: AO	SHEET: 1/1	H																																																																																		
GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827	PART. NO:																																																																																																																																			
LINEAR		ANGLES	APPROVED			KDFH-0066																																																																																																																																			
0.0±0.25		X° REF±6°	DESIGNER			DWG. NO:																																																																																																																																			
0.00±0.15		X° ±3°	DRAWN			ENDE1066																																																																																																																																			
REV.	REVISION RECORD	DATE	UNIT: MM	0.00±0.15	X° X'±2°	TITLE: Pitch2.0mm Female Header,Single Row, Plastic Height 2.0mm,Right Angle Type(U)		REV: AO	SHEET: 1/1																																																																																																																																
1		2		3		4		5		6		7		8																																																																																																																											

Specification:
Current Rating : 1.5AMP
Temperature Range : -40℃to+105℃
Contact Resistance : 20mΩ Max
Insulation Resistance : 1000MΩ Min
Withstanding Voltage : AC 500V
Material:
Insulator : Polyester (UL94V-0)
Standard:PBT/PA6T/LCP
Contact: Bronze
Plating : Au or Sn Over 50u" Ni