

1		2		3		4		5		6		7		8																																																																																																																											
ROHS														For reference only																																																																																																																											
A		<table><tr><td>Pin数</td><td>尺寸A</td><td>尺寸B</td></tr><tr><td>2×2</td><td>2.0</td><td>4.5</td></tr><tr><td>2×3</td><td>4.0</td><td>6.5</td></tr><tr><td>2×4</td><td>6.0</td><td>8.5</td></tr><tr><td>2×5</td><td>8.0</td><td>10.5</td></tr><tr><td>2×6</td><td>10.0</td><td>12.5</td></tr><tr><td>2×7</td><td>12.0</td><td>14.5</td></tr><tr><td>2×8</td><td>14.0</td><td>16.5</td></tr><tr><td>2×9</td><td>16.0</td><td>18.5</td></tr><tr><td>2×10</td><td>18.0</td><td>20.5</td></tr><tr><td>2×11</td><td>20.0</td><td>22.5</td></tr><tr><td>2×12</td><td>22.0</td><td>24.5</td></tr><tr><td>2×13</td><td>24.0</td><td>26.5</td></tr><tr><td>2×14</td><td>26.0</td><td>28.5</td></tr><tr><td>2×15</td><td>28.0</td><td>30.5</td></tr><tr><td>2×16</td><td>30.0</td><td>32.5</td></tr><tr><td>2×17</td><td>32.0</td><td>34.5</td></tr><tr><td>2×18</td><td>34.0</td><td>36.5</td></tr><tr><td>2×19</td><td>36.0</td><td>38.5</td></tr><tr><td>2×20</td><td>38.0</td><td>40.5</td></tr><tr><td>2×21</td><td>40.0</td><td>42.5</td></tr><tr><td>2×22</td><td>42.0</td><td>44.5</td></tr><tr><td>2×23</td><td>44.0</td><td>46.5</td></tr><tr><td>2×24</td><td>46.0</td><td>48.5</td></tr><tr><td>2×25</td><td>48.0</td><td>50.5</td></tr><tr><td>2×26</td><td>50.0</td><td>52.5</td></tr><tr><td>2×27</td><td>52.0</td><td>54.5</td></tr><tr><td>2×28</td><td>54.0</td><td>56.5</td></tr><tr><td>2×29</td><td>56.0</td><td>58.5</td></tr><tr><td>2×30</td><td>58.0</td><td>60.5</td></tr><tr><td>2×31</td><td>60.0</td><td>62.5</td></tr><tr><td>2×32</td><td>62.0</td><td>64.5</td></tr><tr><td>2×33</td><td>64.0</td><td>66.5</td></tr><tr><td>2×34</td><td>66.0</td><td>68.5</td></tr><tr><td>2×35</td><td>68.0</td><td>70.5</td></tr><tr><td>2×36</td><td>70.0</td><td>72.5</td></tr><tr><td>2×37</td><td>72.0</td><td>74.5</td></tr><tr><td>2×38</td><td>74.0</td><td>76.5</td></tr><tr><td>2×39</td><td>76.0</td><td>78.5</td></tr><tr><td>2×40</td><td>78.0</td><td>80.5</td></tr></table>														Pin数	尺寸A	尺寸B	2×2	2.0	4.5	2×3	4.0	6.5	2×4	6.0	8.5	2×5	8.0	10.5	2×6	10.0	12.5	2×7	12.0	14.5	2×8	14.0	16.5	2×9	16.0	18.5	2×10	18.0	20.5	2×11	20.0	22.5	2×12	22.0	24.5	2×13	24.0	26.5	2×14	26.0	28.5	2×15	28.0	30.5	2×16	30.0	32.5	2×17	32.0	34.5	2×18	34.0	36.5	2×19	36.0	38.5	2×20	38.0	40.5	2×21	40.0	42.5	2×22	42.0	44.5	2×23	44.0	46.5	2×24	46.0	48.5	2×25	48.0	50.5	2×26	50.0	52.5	2×27	52.0	54.5	2×28	54.0	56.5	2×29	56.0	58.5	2×30	58.0	60.5	2×31	60.0	62.5	2×32	62.0	64.5	2×33	64.0	66.5	2×34	66.0	68.5	2×35	68.0	70.5	2×36	70.0	72.5	2×37	72.0	74.5	2×38	74.0	76.5	2×39	76.0	78.5	2×40	78.0	80.5	A	
Pin数	尺寸A	尺寸B																																																																																																																																							
2×2	2.0	4.5																																																																																																																																							
2×3	4.0	6.5																																																																																																																																							
2×4	6.0	8.5																																																																																																																																							
2×5	8.0	10.5																																																																																																																																							
2×6	10.0	12.5																																																																																																																																							
2×7	12.0	14.5																																																																																																																																							
2×8	14.0	16.5																																																																																																																																							
2×9	16.0	18.5																																																																																																																																							
2×10	18.0	20.5																																																																																																																																							
2×11	20.0	22.5																																																																																																																																							
2×12	22.0	24.5																																																																																																																																							
2×13	24.0	26.5																																																																																																																																							
2×14	26.0	28.5																																																																																																																																							
2×15	28.0	30.5																																																																																																																																							
2×16	30.0	32.5																																																																																																																																							
2×17	32.0	34.5																																																																																																																																							
2×18	34.0	36.5																																																																																																																																							
2×19	36.0	38.5																																																																																																																																							
2×20	38.0	40.5																																																																																																																																							
2×21	40.0	42.5																																																																																																																																							
2×22	42.0	44.5																																																																																																																																							
2×23	44.0	46.5																																																																																																																																							
2×24	46.0	48.5																																																																																																																																							
2×25	48.0	50.5																																																																																																																																							
2×26	50.0	52.5																																																																																																																																							
2×27	52.0	54.5																																																																																																																																							
2×28	54.0	56.5																																																																																																																																							
2×29	56.0	58.5																																																																																																																																							
2×30	58.0	60.5																																																																																																																																							
2×31	60.0	62.5																																																																																																																																							
2×32	62.0	64.5																																																																																																																																							
2×33	64.0	66.5																																																																																																																																							
2×34	66.0	68.5																																																																																																																																							
2×35	68.0	70.5																																																																																																																																							
2×36	70.0	72.5																																																																																																																																							
2×37	72.0	74.5																																																																																																																																							
2×38	74.0	76.5																																																																																																																																							
2×39	76.0	78.5																																																																																																																																							
2×40	78.0	80.5																																																																																																																																							
B																B																																																																																																																									
C		Specification: Current Rating : 1.5AMP Temperature Range : -40℃to+105℃ Contact Resistance : 20mΩ Max Insulation Resistance : 1000MΩ Min Withstanding Voltage : AC 500V Material: Insulator : Polyester (UL94V-0) Standard:PBT/PA6T/LCP Contact: Bronze Plating : Au or Sn Over 50u" Ni														C																																																																																																																									
D																D																																																																																																																									
E		PCB LAYOUT														E																																																																																																																									
F		<table><tr><td colspan="2">F 20 0D-XXX X X-XX-X-XXX</td></tr><tr><td>① Series No:</td><td>② Pitch:</td><td>③ Tail&Mounting Style:</td><td>④ No. of Pins:</td><td>⑤ Insulator Color:</td></tr><tr><td>P=Pin Header</td><td>08=0.80</td><td>90=Right Angle DIP Type</td><td>Single Row Double Row</td><td>A:Black B:Brom C:Red</td></tr><tr><td>F=Female Header</td><td>10=1.00</td><td>9S=Straight SMT Type</td><td>101=1*1Pin 201=2*1Pin</td><td>D:Orange E:Yellow F:Green</td></tr><tr><td>B=Box Header</td><td>12=1.27</td><td>0D=Straight DIP Type</td><td>102=1*2Pin 202=2*2Pin</td><td>G:Blue H:Violet J:Gray</td></tr><tr><td>E=Ejector Header</td><td>20=2.00</td><td>0S=horizontal SMT Type</td><td>11=1*1Pin 21=1*1Pin</td><td>K:White P:Light Blue</td></tr><tr><td></td><td>25=2.54</td><td></td><td>140=1*40pin 240=2*40pin</td><td></td></tr><tr><td></td><td>39=3.96</td><td></td><td></td><td></td></tr><tr><td></td><td>50=5.08</td><td></td><td></td><td></td></tr></table>														F 20 0D-XXX X X-XX-X-XXX		① Series No:	② Pitch:	③ Tail&Mounting Style:	④ No. of Pins:	⑤ Insulator Color:	P=Pin Header	08=0.80	90=Right Angle DIP Type	Single Row Double Row	A:Black B:Brom C:Red	F=Female Header	10=1.00	9S=Straight SMT Type	101=1*1Pin 201=2*1Pin	D:Orange E:Yellow F:Green	B=Box Header	12=1.27	0D=Straight DIP Type	102=1*2Pin 202=2*2Pin	G:Blue H:Violet J:Gray	E=Ejector Header	20=2.00	0S=horizontal SMT Type	11=1*1Pin 21=1*1Pin	K:White P:Light Blue		25=2.54		140=1*40pin 240=2*40pin			39=3.96					50=5.08				F																																																																															
F 20 0D-XXX X X-XX-X-XXX																																																																																																																																									
① Series No:	② Pitch:	③ Tail&Mounting Style:	④ No. of Pins:	⑤ Insulator Color:																																																																																																																																					
P=Pin Header	08=0.80	90=Right Angle DIP Type	Single Row Double Row	A:Black B:Brom C:Red																																																																																																																																					
F=Female Header	10=1.00	9S=Straight SMT Type	101=1*1Pin 201=2*1Pin	D:Orange E:Yellow F:Green																																																																																																																																					
B=Box Header	12=1.27	0D=Straight DIP Type	102=1*2Pin 202=2*2Pin	G:Blue H:Violet J:Gray																																																																																																																																					
E=Ejector Header	20=2.00	0S=horizontal SMT Type	11=1*1Pin 21=1*1Pin	K:White P:Light Blue																																																																																																																																					
	25=2.54		140=1*40pin 240=2*40pin																																																																																																																																						
	39=3.96																																																																																																																																								
	50=5.08																																																																																																																																								
G		<table><tr><td>⑥ Material Type:</td><td>⑦ Plating Type:</td><td>⑧ RoHS Request:</td><td>⑨ Customer Code</td></tr><tr><td>A=PBT</td><td>0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au</td><td>0:No Request</td><td></td></tr><tr><td>B=PA46</td><td>0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"</td><td>1:RoHS</td><td></td></tr><tr><td>C=PA6T</td><td>0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"</td><td>2:HF (Halogen Free)</td><td></td></tr><tr><td>D=PA9T</td><td>0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"</td><td></td><td></td></tr><tr><td>E=LCP</td><td>0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"</td><td></td><td></td></tr><tr><td></td><td>0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"</td><td></td><td></td></tr></table>														⑥ Material Type:	⑦ Plating Type:	⑧ RoHS Request:	⑨ Customer Code	A=PBT	0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au	0:No Request		B=PA46	0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"	1:RoHS		C=PA6T	0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"	2:HF (Halogen Free)		D=PA9T	0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"			E=LCP	0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"				0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"			G																																																																																													
⑥ Material Type:	⑦ Plating Type:	⑧ RoHS Request:	⑨ Customer Code																																																																																																																																						
A=PBT	0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au	0:No Request																																																																																																																																							
B=PA46	0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"	1:RoHS																																																																																																																																							
C=PA6T	0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"	2:HF (Halogen Free)																																																																																																																																							
D=PA9T	0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"																																																																																																																																								
E=LCP	0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"																																																																																																																																								
	0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"																																																																																																																																								
H		<table><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">GENERAL TOLERANCES</td><td colspan="2">SCALE: 1:1</td><td colspan="2">NAME</td><td colspan="2">DATE</td><td colspan="2" rowspan="4">  东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827 </td><td colspan="2">PART. NO:</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">APPROVED</td><td colspan="2"></td><td colspan="2"></td><td colspan="2">KDFH-0071</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">DESIGNER</td><td colspan="2"></td><td colspan="2"></td><td colspan="2">DWG. NO:</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">DRAWN</td><td colspan="2"></td><td colspan="2"></td><td colspan="2">ENDE1071</td></tr><tr><td colspan="2">REV.</td><td colspan="2">REVISION RECORD</td><td colspan="2">DATE</td><td colspan="2">UNIT: MM</td><td colspan="2">SIZE: A4</td><td colspan="2">0.00±0.08</td><td colspan="2">X° X'±2°</td><td colspan="2">TITLE:</td><td colspan="2">Pitch2.0mm Female Header, Dual Row, Plastic Height 3.0mm, DIP</td><td colspan="2">REV: AO</td><td colspan="2">SHEET: 1/1</td></tr><tr><td colspan="2">1</td><td colspan="2">2</td><td colspan="2">3</td><td colspan="2">4</td><td colspan="2">5</td><td colspan="2">6</td><td colspan="2">7</td><td colspan="2">8</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr></table>																				GENERAL TOLERANCES		SCALE: 1:1		NAME		DATE		 东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827		PART. NO:										APPROVED						KDFH-0071										DESIGNER						DWG. NO:										DRAWN						ENDE1071		REV.		REVISION RECORD		DATE		UNIT: MM		SIZE: A4		0.00±0.08		X° X'±2°		TITLE:		Pitch2.0mm Female Header, Dual Row, Plastic Height 3.0mm, DIP		REV: AO		SHEET: 1/1		1		2		3		4		5		6		7		8																			
						GENERAL TOLERANCES		SCALE: 1:1		NAME		DATE		 东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827		PART. NO:																																																																																																																									
								APPROVED								KDFH-0071																																																																																																																									
								DESIGNER								DWG. NO:																																																																																																																									
								DRAWN								ENDE1071																																																																																																																									
REV.		REVISION RECORD		DATE		UNIT: MM		SIZE: A4		0.00±0.08		X° X'±2°		TITLE:		Pitch2.0mm Female Header, Dual Row, Plastic Height 3.0mm, DIP		REV: AO		SHEET: 1/1																																																																																																																					
1		2		3		4		5		6		7		8																																																																																																																											