

1		2		3		4		5		6		7		8																																																																																																																									
ROHS														For reference only																																																																																																																									
A		<table><tr><td>Pin数</td><td>尺寸A</td><td>尺寸B</td></tr><tr><td>1×2</td><td>2.54</td><td>5.58</td></tr><tr><td>1×3</td><td>5.08</td><td>8.12</td></tr><tr><td>1×4</td><td>7.62</td><td>10.66</td></tr><tr><td>1×5</td><td>10.16</td><td>13.20</td></tr><tr><td>1×6</td><td>12.70</td><td>15.74</td></tr><tr><td>1×7</td><td>15.24</td><td>18.28</td></tr><tr><td>1×8</td><td>17.78</td><td>20.82</td></tr><tr><td>1×9</td><td>20.32</td><td>23.36</td></tr><tr><td>1×10</td><td>22.86</td><td>25.90</td></tr><tr><td>1×11</td><td>25.40</td><td>28.44</td></tr><tr><td>1×12</td><td>27.94</td><td>30.98</td></tr><tr><td>1×13</td><td>30.48</td><td>33.52</td></tr><tr><td>1×14</td><td>33.02</td><td>36.06</td></tr><tr><td>1×15</td><td>35.56</td><td>38.60</td></tr><tr><td>1×16</td><td>38.10</td><td>41.14</td></tr><tr><td>1×17</td><td>40.64</td><td>43.68</td></tr><tr><td>1×18</td><td>43.18</td><td>46.22</td></tr><tr><td>1×19</td><td>45.72</td><td>48.76</td></tr><tr><td>1×20</td><td>48.26</td><td>51.30</td></tr><tr><td>1×21</td><td>50.80</td><td>53.84</td></tr><tr><td>1×22</td><td>53.34</td><td>56.38</td></tr><tr><td>1×23</td><td>55.88</td><td>58.92</td></tr><tr><td>1×24</td><td>58.42</td><td>61.46</td></tr><tr><td>1×25</td><td>60.96</td><td>64.00</td></tr><tr><td>1×26</td><td>63.50</td><td>66.54</td></tr><tr><td>1×27</td><td>66.04</td><td>69.08</td></tr><tr><td>1×28</td><td>68.58</td><td>71.62</td></tr><tr><td>1×29</td><td>71.12</td><td>74.16</td></tr><tr><td>1×30</td><td>73.66</td><td>76.70</td></tr><tr><td>1×31</td><td>76.20</td><td>79.24</td></tr><tr><td>1×32</td><td>78.74</td><td>81.78</td></tr><tr><td>1×33</td><td>81.28</td><td>84.32</td></tr><tr><td>1×34</td><td>83.82</td><td>86.86</td></tr><tr><td>1×35</td><td>86.36</td><td>89.40</td></tr><tr><td>1×36</td><td>88.90</td><td>91.94</td></tr><tr><td>1×37</td><td>91.44</td><td>94.48</td></tr><tr><td>1×38</td><td>93.98</td><td>97.02</td></tr><tr><td>1×39</td><td>96.52</td><td>99.56</td></tr><tr><td>1×40</td><td>99.06</td><td>102.10</td></tr></table>												Pin数	尺寸A	尺寸B	1×2	2.54	5.58	1×3	5.08	8.12	1×4	7.62	10.66	1×5	10.16	13.20	1×6	12.70	15.74	1×7	15.24	18.28	1×8	17.78	20.82	1×9	20.32	23.36	1×10	22.86	25.90	1×11	25.40	28.44	1×12	27.94	30.98	1×13	30.48	33.52	1×14	33.02	36.06	1×15	35.56	38.60	1×16	38.10	41.14	1×17	40.64	43.68	1×18	43.18	46.22	1×19	45.72	48.76	1×20	48.26	51.30	1×21	50.80	53.84	1×22	53.34	56.38	1×23	55.88	58.92	1×24	58.42	61.46	1×25	60.96	64.00	1×26	63.50	66.54	1×27	66.04	69.08	1×28	68.58	71.62	1×29	71.12	74.16	1×30	73.66	76.70	1×31	76.20	79.24	1×32	78.74	81.78	1×33	81.28	84.32	1×34	83.82	86.86	1×35	86.36	89.40	1×36	88.90	91.94	1×37	91.44	94.48	1×38	93.98	97.02	1×39	96.52	99.56	1×40	99.06	102.10	A	
Pin数	尺寸A	尺寸B																																																																																																																																					
1×2	2.54	5.58																																																																																																																																					
1×3	5.08	8.12																																																																																																																																					
1×4	7.62	10.66																																																																																																																																					
1×5	10.16	13.20																																																																																																																																					
1×6	12.70	15.74																																																																																																																																					
1×7	15.24	18.28																																																																																																																																					
1×8	17.78	20.82																																																																																																																																					
1×9	20.32	23.36																																																																																																																																					
1×10	22.86	25.90																																																																																																																																					
1×11	25.40	28.44																																																																																																																																					
1×12	27.94	30.98																																																																																																																																					
1×13	30.48	33.52																																																																																																																																					
1×14	33.02	36.06																																																																																																																																					
1×15	35.56	38.60																																																																																																																																					
1×16	38.10	41.14																																																																																																																																					
1×17	40.64	43.68																																																																																																																																					
1×18	43.18	46.22																																																																																																																																					
1×19	45.72	48.76																																																																																																																																					
1×20	48.26	51.30																																																																																																																																					
1×21	50.80	53.84																																																																																																																																					
1×22	53.34	56.38																																																																																																																																					
1×23	55.88	58.92																																																																																																																																					
1×24	58.42	61.46																																																																																																																																					
1×25	60.96	64.00																																																																																																																																					
1×26	63.50	66.54																																																																																																																																					
1×27	66.04	69.08																																																																																																																																					
1×28	68.58	71.62																																																																																																																																					
1×29	71.12	74.16																																																																																																																																					
1×30	73.66	76.70																																																																																																																																					
1×31	76.20	79.24																																																																																																																																					
1×32	78.74	81.78																																																																																																																																					
1×33	81.28	84.32																																																																																																																																					
1×34	83.82	86.86																																																																																																																																					
1×35	86.36	89.40																																																																																																																																					
1×36	88.90	91.94																																																																																																																																					
1×37	91.44	94.48																																																																																																																																					
1×38	93.98	97.02																																																																																																																																					
1×39	96.52	99.56																																																																																																																																					
1×40	99.06	102.10																																																																																																																																					
B														B																																																																																																																									
C														C																																																																																																																									
D														D																																																																																																																									
E														E																																																																																																																									
F		<table><tr><td colspan="2">F 25 9D-XXX X X-XX-X-XXX</td></tr><tr><td>① Series No:</td><td>② Pitch:</td><td>③ Tail&Mounting Style:</td><td>④ No. of Pins:</td><td>⑤ Insulator Color:</td></tr><tr><td>P=Pin Header</td><td>08=0.80</td><td>9D=Right Angle DIP Type</td><td>Single Row Double Row</td><td>A:Black B:Brom C:Red</td></tr><tr><td>F=Female Header</td><td>10=1.00</td><td>9S=Straight SMT Type</td><td>101=1*1Pin 201=2*1Pin</td><td>D:Orange E:Yellow F:Green</td></tr><tr><td>B=Box Header</td><td>12=1.27</td><td>0D=Straight DIP Type</td><td>102=1*2Pin 202=2*2Pin</td><td>G:Blue H:Violet J:Gray</td></tr><tr><td>E=Ejector Header</td><td>20=2.00</td><td>0S=horizontal SMT Type</td><td>11=1*1pin 140=1*40pin</td><td>K:White P:Light Blue</td></tr><tr><td></td><td>25=2.54</td><td></td><td></td><td></td></tr><tr><td></td><td>39=3.96</td><td></td><td></td><td></td></tr><tr><td></td><td>50=5.08</td><td></td><td></td><td></td></tr></table>												F 25 9D-XXX X X-XX-X-XXX		① Series No:	② Pitch:	③ Tail&Mounting Style:	④ No. of Pins:	⑤ Insulator Color:	P=Pin Header	08=0.80	9D=Right Angle DIP Type	Single Row Double Row	A:Black B:Brom C:Red	F=Female Header	10=1.00	9S=Straight SMT Type	101=1*1Pin 201=2*1Pin	D:Orange E:Yellow F:Green	B=Box Header	12=1.27	0D=Straight DIP Type	102=1*2Pin 202=2*2Pin	G:Blue H:Violet J:Gray	E=Ejector Header	20=2.00	0S=horizontal SMT Type	11=1*1pin 140=1*40pin	K:White P:Light Blue		25=2.54					39=3.96					50=5.08				F																																																																															
F 25 9D-XXX X X-XX-X-XXX																																																																																																																																							
① Series No:	② Pitch:	③ Tail&Mounting Style:	④ No. of Pins:	⑤ Insulator Color:																																																																																																																																			
P=Pin Header	08=0.80	9D=Right Angle DIP Type	Single Row Double Row	A:Black B:Brom C:Red																																																																																																																																			
F=Female Header	10=1.00	9S=Straight SMT Type	101=1*1Pin 201=2*1Pin	D:Orange E:Yellow F:Green																																																																																																																																			
B=Box Header	12=1.27	0D=Straight DIP Type	102=1*2Pin 202=2*2Pin	G:Blue H:Violet J:Gray																																																																																																																																			
E=Ejector Header	20=2.00	0S=horizontal SMT Type	11=1*1pin 140=1*40pin	K:White P:Light Blue																																																																																																																																			
	25=2.54																																																																																																																																						
	39=3.96																																																																																																																																						
	50=5.08																																																																																																																																						
G		<table><tr><td>⑥ Material Type:</td><td>⑦ Plating Type:</td><td>⑧ RoHS Request:</td><td>⑨ Customer Code</td></tr><tr><td>A=PBT</td><td>0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au</td><td>0:No Request</td><td></td></tr><tr><td>B=PA46</td><td>0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"</td><td>1:RoHS</td><td></td></tr><tr><td>C=PA6T</td><td>0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"</td><td>2:HF (Halogen Free)</td><td></td></tr><tr><td>D=PA9T</td><td>0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"</td><td></td><td></td></tr><tr><td>E=LCP</td><td>0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"</td><td></td><td></td></tr><tr><td></td><td>0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"</td><td></td><td></td></tr></table>												⑥ Material Type:	⑦ Plating Type:	⑧ RoHS Request:	⑨ Customer Code	A=PBT	0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au	0:No Request		B=PA46	0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"	1:RoHS		C=PA6T	0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"	2:HF (Halogen Free)		D=PA9T	0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"			E=LCP	0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"				0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"			G																																																																																													
⑥ Material Type:	⑦ Plating Type:	⑧ RoHS Request:	⑨ Customer Code																																																																																																																																				
A=PBT	0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au	0:No Request																																																																																																																																					
B=PA46	0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"	1:RoHS																																																																																																																																					
C=PA6T	0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"	2:HF (Halogen Free)																																																																																																																																					
D=PA9T	0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"																																																																																																																																						
E=LCP	0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"																																																																																																																																						
	0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"																																																																																																																																						
H		<table><tr><td colspan="2"></td><td colspan="2">GENERAL TOLERANCES</td><td>SCALE: 1:1</td><td>NAME</td><td>DATE</td><td rowspan="4">东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827</td><td colspan="2">PART. NO:</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td>APPROVED</td><td></td><td></td><td colspan="2">KDFH-0112</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td>DESIGNER</td><td></td><td></td><td colspan="2">DWG. NO:</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td>DRAWN</td><td></td><td></td><td colspan="2">ENDE1112</td></tr><tr><td>REV.</td><td colspan="2">REVISION RECORD</td><td>DATE</td><td>UNIT: MM</td><td>0.00±0.15</td><td>X° ±3°</td><td colspan="2">TITLE:</td><td>REV: AO</td><td>SHEET: 1/1</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td>SIZE: A4</td><td>0.000±0.08</td><td>X° X'±2°</td><td colspan="2">Pitch2.54mm Female Header, Single Row, Plastic Height 5.0mm, Right Angle Type(U)</td><td colspan="2"></td></tr></table>														GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827	PART. NO:						APPROVED			KDFH-0112						DESIGNER			DWG. NO:						DRAWN			ENDE1112		REV.	REVISION RECORD		DATE	UNIT: MM	0.00±0.15	X° ±3°	TITLE:		REV: AO	SHEET: 1/1					SIZE: A4	0.000±0.08	X° X'±2°	Pitch2.54mm Female Header, Single Row, Plastic Height 5.0mm, Right Angle Type(U)				H																																																														
		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827	PART. NO:																																																																																																																															
				APPROVED				KDFH-0112																																																																																																																															
				DESIGNER				DWG. NO:																																																																																																																															
				DRAWN				ENDE1112																																																																																																																															
REV.	REVISION RECORD		DATE	UNIT: MM	0.00±0.15	X° ±3°	TITLE:		REV: AO	SHEET: 1/1																																																																																																																													
				SIZE: A4	0.000±0.08	X° X'±2°	Pitch2.54mm Female Header, Single Row, Plastic Height 5.0mm, Right Angle Type(U)																																																																																																																																
1		2		3		4		5		6		7		8																																																																																																																									

Specification:
Current Rating : 3AMP
Temperature Range : -40℃to+105℃
Contact Resistance : 20mΩ Max
Insulation Resistance : 1000MΩ Min
Withstanding Voltage : AC 1000V
Material:
Insulator : Polyester (UL94V-0)
Standard:PBT/PA6T/LCP
Contact: Bronze
Plating : Au or Sn Over 50u" Ni