




ROHS

For reference only

Pin数	尺寸A	尺寸B
1X1	-	2.0
1X2	2.0	4.0
1X3	4.0	6.0
1X4	6.0	8.0
1X5	8.0	10.0
1X6	10.0	12.0
1X7	12.0	14.0
1X8	14.0	16.0
1X9	16.0	18.0
1X10	18.0	20.0
1X11	20.0	22.0
1X12	22.0	24.0
1X13	24.0	26.0
1X14	26.0	28.0
1X15	28.0	30.0
1X16	30.0	32.0
1X17	32.0	34.0
1X18	34.0	36.0
1X19	36.0	38.0
1X20	38.0	40.0
1X21	40.0	42.0
1X22	42.0	44.0
1X23	44.0	46.0
1X24	46.0	48.0
1X25	48.0	50.0
1X26	50.0	52.0
1X27	52.0	54.0
1X28	54.0	56.0
1X29	56.0	58.0
1X30	58.0	60.0
1X31	60.0	62.0
1X32	62.0	64.0
1X33	64.0	66.0
1X34	66.0	68.0
1X35	68.0	70.0
1X36	70.0	72.0
1X37	72.0	74.0
1X38	74.0	76.0
1X39	76.0	78.0
1X40	78.0	80.0
1X41	80.0	82.0
1X42	82.0	84.0
1X43	84.0	86.0
1X44	86.0	88.0
1X45	88.0	90.0
1X46	90.0	92.0
1X47	92.0	94.0
1X48	94.0	96.0
1X49	96.0	98.0
1X50	98.0	100.0
1X51	100.0	102.0
1X52	102.0	104.0



Specification:

Current Rating : 1.5AMP

Temperature Range : -40°Cto+105°C

Contact Resistance : 20mΩ Max

Insulation Resistance : 1000MΩ Min

Withstanding Voltage : AC 500V

Material:

Insulator : Polyester (UL94V-0)

Standard:PBT/PA6T/LCP

Contact: Brass

Plating : Au or Sn Over 50u" Ni

Height

H=1.0mm、1.5mm、2.0mm、3.0mm

P 20 9D-XXX X X-XX-X-XXX
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

① Series No: P=Pin Header F=Female Header B=Box Header E=Ejector Header	② Pitch: 08=0.80 10=1.00 12=1.27 20=2.00 25=2.54 39=3.96 50=5.08	③ Tail&Mounting Style: 9D=Right Angle DIP Type 9S=Straight SMT Type 0D=Straight DIP Type 0S=Horizontal SMT Type	④ No. of Pins: Single Row Double Row 101=1*1Pin 201=2*1Pin 102=1*2Pin 202=2*2Pin ⋮ ⋮ 140=1*40pin 240=2*40pin	⑤ Insulator Color: A:Black B:Brown C:Red D:Orange E:Yellow F:Green G:Blue H:Violet J:Gray K:White P:Light Blue
⑥ Material Type: A-PBT B-PA46 C-PA6T D-PA9T E-LCP	⑦ Plating Type: 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au 0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u" 0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u" 0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u" 0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u" 0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"	⑧ RoHS Request: 0:No Request 1:RoHS 2:HF (Halogen Free)	⑨ Customer Code	

REV.	REVISION RECORD	DATE	UNIT: MM	GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE
				LINEAR	ANGLES			
				0.0±0.25	X° REF±6°	APPROVED		
				0.00±0.15	X° ±3°	DESIGNER		
				0.000±0.08	X° X'±2°	DRAWN		

东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Email: 2850175986@qq.com	PART. NO: KDPH-0050	
	DWG. NO: ENDE0050	
	REV:	A0
	SHEET:	1/1