





ROHS

For reference only


Pin数	尺寸A	尺寸B
2X1	-	2.0
2X2	2.0	4.0
2X3	4.0	6.0
2X4	6.0	8.0
2X5	8.0	10.0
2X6	10.0	12.0
2X7	12.0	14.0
2X8	14.0	16.0
2X9	16.0	18.0
2X10	18.0	20.0
2X11	20.0	22.0
2X12	22.0	24.0
2X13	24.0	26.0
2X14	26.0	28.0
2X15	28.0	30.0
2X16	30.0	32.0
2X17	32.0	34.0
2X18	34.0	36.0
2X19	36.0	38.0
2X20	38.0	40.0
2X21	40.0	42.0
2X22	42.0	44.0
2X23	44.0	46.0
2X24	46.0	48.0
2X25	48.0	50.0
2X26	50.0	52.0
2X27	52.0	54.0
2X28	54.0	56.0
2X29	56.0	58.0
2X30	58.0	60.0
2X31	60.0	62.0
2X32	62.0	64.0
2X33	64.0	66.0
2X34	66.0	68.0
2X35	68.0	70.0
2X36	70.0	72.0
2X37	72.0	74.0
2X38	74.0	76.0
2X39	76.0	78.0
2X40	78.0	80.0
2X41	80.0	82.0
2X42	82.0	84.0
2X43	84.0	86.0
2X44	86.0	88.0
2X45	88.0	90.0
2X46	90.0	92.0
2X47	92.0	94.0
2X48	94.0	96.0
2X49	96.0	98.0
2X50	98.0	100.0
2X51	100.0	102.0
2X52	102.0	104.0



Specification:
Current Rating : 1.5AMP
Temperature Range : -40℃to+105℃
Contact Resistance : 20mΩ Max
Insulation Resistance : 1000MΩ Min
Withstanding Voltage : AC 500V
Material:
Insulator : Polyester (UL94V-0)
Standard:PA6T/LCP
Contact: Brass
Plating : Au or Sn Over 50u" Ni

Height
H=1.0mm、1.5mm、2.0mm、3.0mm

PCB LAYOUT



P 20 9S-XXX X X-XX-X-XXX			
① Series No: P=Pin Header F=Female Header B=Box Header E=Ejector Header	② Pitch: 08=0.80 10=1.00 12=1.27 20=2.00 25=2.54 39=3.96 50=5.08	③ Tail&Mounting Style: 90=Right Angle DIP Type 95=Straight SMT Type 00=Straight DIP Type 05=Horizontal SMT Type	④ No. of Pins: Single Row Double Row 101=1*1Pin 201=2*1Pin 102=1*2Pin 202=2*2Pin 140=1*40pin 240=2*40pin
⑤ Insulator Color: A:Black B:Brown C:Red D:Orange E:Yellow F:Green G:Blue H:Violet J:Gray K:White P:Light Blue			
⑥ Material Type: A-PBT B-PA46 C-PA6T D-PA9T E-LCP	⑦ Plating Type: 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au 0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u" 0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u" 0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u" 0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u" 0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"	⑧ RoHS Request: 0:No Request 1:RoHS 2:HF(Halogen Free)	⑨ Customer Code

REV.	REVISION RECORD	DATE	UNIT: MM	SIZE: A4	GENERAL TOLERANCES	SCALE: 1:1	NAME	DATE
					LINEAR	APPROVED		
					ANGLES	DESIGNER		
					0.0±0.25	DRAWN		
					X° REF±6°			
					0.00±0.15			
					X° ±3°			
					X° X'±2°			

东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD.		PART. NO:	KDPH-0058
Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827		DWG. NO:	ENDE0058
TITLE: Pitch2.00mm Pin Header, Dual Plastic, Dual Row, SMT Type		REV:	A0
		SHEET:	1/1