





ROHS

For reference only

Pin数	尺寸A	尺寸B
2X1	-	1.27
2X2	1.27	2.54
2X3	2.54	3.81
2X4	3.81	5.08
2X5	5.08	6.35
2X6	6.35	7.62
2X7	7.62	8.89
2X8	8.89	10.16
2X9	10.16	11.43
2X10	11.43	12.70
2X11	12.70	13.97
2X12	13.97	15.24
2X13	15.24	16.51
2X14	16.51	17.78
2X15	17.78	19.05
2X16	19.05	20.32
2X17	20.32	21.59
2X18	21.59	22.86
2X19	22.86	24.13
2X20	24.13	25.40
2X21	25.40	26.67
2X22	26.67	27.94
2X23	27.94	29.21
2X24	29.21	30.48
2X25	30.48	31.75
2X26	31.75	33.02
2X27	33.02	34.29
2X28	34.29	35.56
2X29	35.56	36.83
2X30	36.83	38.10
2X31	38.10	39.37
2X32	39.37	40.64
2X33	40.64	41.91
2X34	41.91	43.18
2X35	43.18	44.45
2X36	44.45	45.72
2X37	45.72	46.99
2X38	46.99	48.26
2X39	48.26	49.53
2X40	49.53	50.80
2X41	50.80	52.07
2X42	52.07	53.34
2X43	53.34	54.61
2X44	54.61	55.88
2X45	55.88	57.15
2X46	57.15	58.42
2X47	58.42	59.69
2X48	59.69	60.96
2X49	60.96	62.23
2X50	62.23	63.50



Specification:

Current Rating : 1AMP

Temperature Range : -40℃to+105℃

Contact Resistance : 20mΩ Max

Insulation Resistance : 1000MΩ Min

Withstanding Voltage : AC 500V

Material:

Insulator : Polyester (UL94V-0)

Standard:PBT/PA6T/LCP

Contact: Brass

Plating : Au or Sn Over 50u" Ni

Height
H=0.65mm、1.0MM、1.5mm、1.7mm、2.0mm、2.5mm

P 12 9D-XXX X X-XX-X-XXX
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

① Series No: P=Pin Header F=Female Header B=Box Header E=Ejector Header	② Pitch: 08=0.80 10=1.00 12=1.27 20=2.00 25=2.54 39=3.96 50=5.08	③ Tail&Mounting Style: 9D=Right Angle DIP Type 9S=Straight SMT Type 0D=Straight DIP Type 0S=Horizontal SMT Type	④ No. of Pins: Single Row 101=1*1Pin 102=1*2Pin 140=1*40pin 201=2*1Pin 202=2*2Pin 240=2*40pin	⑤ Insulator Color: A:Black B:Brown C:Red D:Orange E:Yellow F:Green G:Blue H:Violet J:Gray K:White P:Light Blue
⑥ Material Type: A-PBT B-PA46 C-PA6T D-PA9T E-LCP	⑦ Plating Type: 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au 0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u" 0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u" 0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u" 0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u" 0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"	⑧ RoHS Request: 0:No Request 1:RoHS 2:HF(Halogen Free)	⑨ Customer Code	

REV.	REVISION RECORD	DATE	UNIT: MM	GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE
				LINEAR	ANGLES			
				0.0±0.25	X° REF±6°	APPROVED		
				0.00±0.15	X° ±3°	DESIGNER		
				0.000±0.08	X° X'±2°	DRAWN		

 东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827		PART. NO: KDPH-0042			
		DWG. NO: ENDE0042			
TITLE: 1.27*2.54mm Pin Header, Dual Plastic, Dual Row, Right Angle Type		REV:	A0	SHEET:	1/1