

	1	2	3	4	5	6	7	8																																																																																																																												
A	ROHS						For reference only																																																																																																																													
B	<table><tr><td>Pin数</td><td>尺寸A</td><td>尺寸B</td><td>尺寸C</td></tr><tr><td>2×3</td><td>5.08</td><td>12.94</td><td>15.24</td></tr><tr><td>2×4</td><td>7.62</td><td>15.48</td><td>17.78</td></tr><tr><td>2×5</td><td>10.16</td><td>18.02</td><td>20.32</td></tr><tr><td>2×6</td><td>12.70</td><td>20.56</td><td>22.86</td></tr><tr><td>2×7</td><td>15.24</td><td>23.10</td><td>25.40</td></tr><tr><td>2×8</td><td>17.78</td><td>25.64</td><td>27.94</td></tr><tr><td>2×9</td><td>20.32</td><td>28.18</td><td>30.48</td></tr><tr><td>2×10</td><td>22.86</td><td>30.72</td><td>33.02</td></tr><tr><td>2×11</td><td>25.40</td><td>33.26</td><td>35.56</td></tr><tr><td>2×12</td><td>27.94</td><td>35.80</td><td>38.10</td></tr><tr><td>2×13</td><td>30.48</td><td>38.34</td><td>40.64</td></tr><tr><td>2×14</td><td>33.02</td><td>40.88</td><td>43.18</td></tr><tr><td>2×15</td><td>35.56</td><td>43.42</td><td>45.72</td></tr><tr><td>2×16</td><td>38.10</td><td>45.96</td><td>48.26</td></tr><tr><td>2×17</td><td>40.64</td><td>48.50</td><td>50.80</td></tr><tr><td>2×18</td><td>43.18</td><td>51.04</td><td>53.34</td></tr><tr><td>2×19</td><td>45.72</td><td>53.58</td><td>55.88</td></tr><tr><td>2×20</td><td>48.26</td><td>56.12</td><td>58.42</td></tr><tr><td>2×21</td><td>50.80</td><td>58.66</td><td>60.96</td></tr><tr><td>2×22</td><td>53.34</td><td>61.20</td><td>63.50</td></tr><tr><td>2×23</td><td>55.88</td><td>63.74</td><td>66.04</td></tr><tr><td>2×24</td><td>58.42</td><td>66.28</td><td>68.58</td></tr><tr><td>2×25</td><td>60.96</td><td>68.82</td><td>71.12</td></tr><tr><td>2×26</td><td>63.50</td><td>71.36</td><td>73.66</td></tr><tr><td>2×27</td><td>66.04</td><td>73.90</td><td>76.20</td></tr><tr><td>2×28</td><td>68.58</td><td>76.44</td><td>78.74</td></tr><tr><td>2×29</td><td>71.12</td><td>78.98</td><td>81.28</td></tr><tr><td>2×30</td><td>73.66</td><td>81.52</td><td>83.82</td></tr><tr><td>2×31</td><td>76.20</td><td>84.06</td><td>86.36</td></tr><tr><td>2×32</td><td>78.74</td><td>86.60</td><td>88.90</td></tr></table>		Pin数	尺寸A	尺寸B	尺寸C	2×3	5.08	12.94	15.24	2×4	7.62	15.48	17.78	2×5	10.16	18.02	20.32	2×6	12.70	20.56	22.86	2×7	15.24	23.10	25.40	2×8	17.78	25.64	27.94	2×9	20.32	28.18	30.48	2×10	22.86	30.72	33.02	2×11	25.40	33.26	35.56	2×12	27.94	35.80	38.10	2×13	30.48	38.34	40.64	2×14	33.02	40.88	43.18	2×15	35.56	43.42	45.72	2×16	38.10	45.96	48.26	2×17	40.64	48.50	50.80	2×18	43.18	51.04	53.34	2×19	45.72	53.58	55.88	2×20	48.26	56.12	58.42	2×21	50.80	58.66	60.96	2×22	53.34	61.20	63.50	2×23	55.88	63.74	66.04	2×24	58.42	66.28	68.58	2×25	60.96	68.82	71.12	2×26	63.50	71.36	73.66	2×27	66.04	73.90	76.20	2×28	68.58	76.44	78.74	2×29	71.12	78.98	81.28	2×30	73.66	81.52	83.82	2×31	76.20	84.06	86.36	2×32	78.74	86.60	88.90					Specification: Current Rating : 3AMP Temperature Range : -40℃to+105℃ Contact Resistance : 20mΩ Max Insulation Resistance : 1000MΩ Min Withstanding Voltage : AC 1000V Material: Insulator : Polyester (UL94V-0) Standard:PBT/PA6T/LCP Contact: Brass Plating : Au or Sn Over 50u" Ni	
Pin数	尺寸A	尺寸B	尺寸C																																																																																																																																	
2×3	5.08	12.94	15.24																																																																																																																																	
2×4	7.62	15.48	17.78																																																																																																																																	
2×5	10.16	18.02	20.32																																																																																																																																	
2×6	12.70	20.56	22.86																																																																																																																																	
2×7	15.24	23.10	25.40																																																																																																																																	
2×8	17.78	25.64	27.94																																																																																																																																	
2×9	20.32	28.18	30.48																																																																																																																																	
2×10	22.86	30.72	33.02																																																																																																																																	
2×11	25.40	33.26	35.56																																																																																																																																	
2×12	27.94	35.80	38.10																																																																																																																																	
2×13	30.48	38.34	40.64																																																																																																																																	
2×14	33.02	40.88	43.18																																																																																																																																	
2×15	35.56	43.42	45.72																																																																																																																																	
2×16	38.10	45.96	48.26																																																																																																																																	
2×17	40.64	48.50	50.80																																																																																																																																	
2×18	43.18	51.04	53.34																																																																																																																																	
2×19	45.72	53.58	55.88																																																																																																																																	
2×20	48.26	56.12	58.42																																																																																																																																	
2×21	50.80	58.66	60.96																																																																																																																																	
2×22	53.34	61.20	63.50																																																																																																																																	
2×23	55.88	63.74	66.04																																																																																																																																	
2×24	58.42	66.28	68.58																																																																																																																																	
2×25	60.96	68.82	71.12																																																																																																																																	
2×26	63.50	71.36	73.66																																																																																																																																	
2×27	66.04	73.90	76.20																																																																																																																																	
2×28	68.58	76.44	78.74																																																																																																																																	
2×29	71.12	78.98	81.28																																																																																																																																	
2×30	73.66	81.52	83.82																																																																																																																																	
2×31	76.20	84.06	86.36																																																																																																																																	
2×32	78.74	86.60	88.90																																																																																																																																	
C																																																																																																																																				
D																																																																																																																																				
E																																																																																																																																				
F							B 25 9D-XXX X X-XX-X-XXX <table><tr><td>① Series No:</td><td>② Pitch:</td><td>③ Tail&Mounting Style:</td><td>④ No. of Pins:</td><td>⑤ Insulator Color:</td></tr><tr><td>P=Pin Header</td><td>08=0.80</td><td>90=Right Angle DIP Type</td><td>Single Row Double Row</td><td>A:Black B:Brom C:Red</td></tr><tr><td>F=Female Header</td><td>10=1.00</td><td>9S=Straight SMT Type</td><td>101=1*1Pin 201=2*1Pin</td><td>D:Orange E:Yellow F:Green</td></tr><tr><td>B=Box Header</td><td>12=1.27</td><td>0D=Straight DIP Type</td><td>102=1*2Pin 202=2*2Pin</td><td>G:Blue H:Violet J:Gray</td></tr><tr><td>E=Ejector Header</td><td>20=2.00</td><td>0S=horizontal SMT Type</td><td>140=1*40pin 240=2*40pin</td><td>K:White P:Light Blue</td></tr><tr><td></td><td>25=2.54</td><td></td><td></td><td></td></tr><tr><td></td><td>39=3.96</td><td></td><td></td><td></td></tr><tr><td></td><td>50=5.08</td><td></td><td></td><td></td></tr></table>		① Series No:	② Pitch:	③ Tail&Mounting Style:	④ No. of Pins:	⑤ Insulator Color:	P=Pin Header	08=0.80	90=Right Angle DIP Type	Single Row Double Row	A:Black B:Brom C:Red	F=Female Header	10=1.00	9S=Straight SMT Type	101=1*1Pin 201=2*1Pin	D:Orange E:Yellow F:Green	B=Box Header	12=1.27	0D=Straight DIP Type	102=1*2Pin 202=2*2Pin	G:Blue H:Violet J:Gray	E=Ejector Header	20=2.00	0S=horizontal SMT Type	140=1*40pin 240=2*40pin	K:White P:Light Blue		25=2.54					39=3.96					50=5.08																																																																																							
① Series No:	② Pitch:	③ Tail&Mounting Style:	④ No. of Pins:	⑤ Insulator Color:																																																																																																																																
P=Pin Header	08=0.80	90=Right Angle DIP Type	Single Row Double Row	A:Black B:Brom C:Red																																																																																																																																
F=Female Header	10=1.00	9S=Straight SMT Type	101=1*1Pin 201=2*1Pin	D:Orange E:Yellow F:Green																																																																																																																																
B=Box Header	12=1.27	0D=Straight DIP Type	102=1*2Pin 202=2*2Pin	G:Blue H:Violet J:Gray																																																																																																																																
E=Ejector Header	20=2.00	0S=horizontal SMT Type	140=1*40pin 240=2*40pin	K:White P:Light Blue																																																																																																																																
	25=2.54																																																																																																																																			
	39=3.96																																																																																																																																			
	50=5.08																																																																																																																																			
G							<table><tr><td>⑥ Material Type:</td><td>⑦ Plating Type:</td><td>⑧ RoHS Request:</td><td>⑨ Customer Code</td></tr><tr><td>A-PBT</td><td>0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au</td><td>0:No Request</td><td></td></tr><tr><td>B-PA46</td><td>0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"</td><td>1:RoHS</td><td></td></tr><tr><td>C-PA6T</td><td>0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"</td><td>2:HF (Halogen Free)</td><td></td></tr><tr><td>D-PA9T</td><td>0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"</td><td></td><td></td></tr><tr><td>E-LCP</td><td>0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"</td><td></td><td></td></tr><tr><td></td><td>0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"</td><td></td><td></td></tr></table>		⑥ Material Type:	⑦ Plating Type:	⑧ RoHS Request:	⑨ Customer Code	A-PBT	0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au	0:No Request		B-PA46	0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"	1:RoHS		C-PA6T	0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"	2:HF (Halogen Free)		D-PA9T	0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"			E-LCP	0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"				0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"																																																																																																		
⑥ Material Type:	⑦ Plating Type:	⑧ RoHS Request:	⑨ Customer Code																																																																																																																																	
A-PBT	0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au	0:No Request																																																																																																																																		
B-PA46	0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"	1:RoHS																																																																																																																																		
C-PA6T	0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"	2:HF (Halogen Free)																																																																																																																																		
D-PA9T	0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"																																																																																																																																			
E-LCP	0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"																																																																																																																																			
	0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"																																																																																																																																			
H			<table><tr><td colspan="2">GENERAL TOLERANCES</td><td>SCALE: 1:1</td><td>NAME</td><td>DATE</td></tr><tr><td>LINEAR</td><td>ANGLES</td><td>APPROVED</td><td></td><td></td></tr><tr><td>0.0±0.25</td><td>X° REF±6°</td><td>DESIGNER</td><td></td><td></td></tr><tr><td>0.00±0.15</td><td>X° ±3°</td><td>DRAWN</td><td></td><td></td></tr><tr><td>0.000±0.08</td><td>X° X'±2°</td><td></td><td></td><td></td></tr></table>		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	LINEAR	ANGLES	APPROVED			0.0±0.25	X° REF±6°	DESIGNER			0.00±0.15	X° ±3°	DRAWN			0.000±0.08	X° X'±2°				东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827 PART. NO: KDBH-0029 DWG. NO: ENDE2029 REV: A0 SHEET: 1/1																																																																																																						
GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE																																																																																																																																
LINEAR	ANGLES	APPROVED																																																																																																																																		
0.0±0.25	X° REF±6°	DESIGNER																																																																																																																																		
0.00±0.15	X° ±3°	DRAWN																																																																																																																																		
0.000±0.08	X° X'±2°																																																																																																																																			
	1	2	3	4	5	6	7	8																																																																																																																												