

	1	2	3	4	5	6	7	8																																																																																																																																																						
	ROHS						For reference only																																																																																																																																																							
A	<table><tr><td>Pin数</td><td>尺寸A</td><td>尺寸B</td></tr><tr><td>1X2</td><td>3.96</td><td>7.92</td></tr><tr><td>1X3</td><td>7.92</td><td>11.88</td></tr><tr><td>1X4</td><td>11.88</td><td>15.84</td></tr><tr><td>1X5</td><td>15.84</td><td>19.80</td></tr><tr><td>1X6</td><td>19.80</td><td>23.76</td></tr><tr><td>1X7</td><td>23.76</td><td>27.72</td></tr><tr><td>1X8</td><td>27.72</td><td>31.68</td></tr><tr><td>1X9</td><td>31.68</td><td>35.64</td></tr><tr><td>1X10</td><td>35.64</td><td>39.60</td></tr><tr><td>1X11</td><td>39.60</td><td>43.56</td></tr><tr><td>1X12</td><td>43.56</td><td>47.52</td></tr><tr><td>1X13</td><td>47.52</td><td>51.48</td></tr><tr><td>1X14</td><td>51.48</td><td>55.44</td></tr><tr><td>1X15</td><td>55.44</td><td>59.40</td></tr><tr><td>1X16</td><td>59.40</td><td>63.36</td></tr><tr><td>1X17</td><td>63.36</td><td>67.32</td></tr><tr><td>1X18</td><td>67.32</td><td>71.28</td></tr><tr><td>1X19</td><td>71.28</td><td>75.24</td></tr><tr><td>1X20</td><td>75.24</td><td>79.20</td></tr><tr><td>1X21</td><td>79.20</td><td>83.16</td></tr><tr><td>1X22</td><td>83.16</td><td>87.12</td></tr><tr><td>1X23</td><td>87.12</td><td>91.08</td></tr><tr><td>1X24</td><td>91.08</td><td>95.04</td></tr><tr><td>1X25</td><td>95.04</td><td>99.00</td></tr><tr><td>1X26</td><td>99.00</td><td>102.96</td></tr><tr><td>1X27</td><td>102.96</td><td>106.92</td></tr><tr><td>1X28</td><td>106.92</td><td>110.88</td></tr><tr><td>1X29</td><td>110.88</td><td>114.84</td></tr><tr><td>1X30</td><td>114.84</td><td>118.80</td></tr><tr><td>1X31</td><td>118.80</td><td>122.76</td></tr><tr><td>1X32</td><td>122.76</td><td>126.72</td></tr><tr><td>1X33</td><td>126.72</td><td>130.68</td></tr><tr><td>1X34</td><td>130.68</td><td>134.64</td></tr><tr><td>1X35</td><td>134.64</td><td>138.60</td></tr><tr><td>1X36</td><td>138.60</td><td>142.56</td></tr><tr><td>1X37</td><td>142.56</td><td>146.52</td></tr><tr><td>1X38</td><td>146.52</td><td>150.48</td></tr><tr><td>1X39</td><td>150.48</td><td>154.44</td></tr><tr><td>1X40</td><td>154.44</td><td>158.40</td></tr></table>								Pin数	尺寸A	尺寸B	1X2	3.96	7.92	1X3	7.92	11.88	1X4	11.88	15.84	1X5	15.84	19.80	1X6	19.80	23.76	1X7	23.76	27.72	1X8	27.72	31.68	1X9	31.68	35.64	1X10	35.64	39.60	1X11	39.60	43.56	1X12	43.56	47.52	1X13	47.52	51.48	1X14	51.48	55.44	1X15	55.44	59.40	1X16	59.40	63.36	1X17	63.36	67.32	1X18	67.32	71.28	1X19	71.28	75.24	1X20	75.24	79.20	1X21	79.20	83.16	1X22	83.16	87.12	1X23	87.12	91.08	1X24	91.08	95.04	1X25	95.04	99.00	1X26	99.00	102.96	1X27	102.96	106.92	1X28	106.92	110.88	1X29	110.88	114.84	1X30	114.84	118.80	1X31	118.80	122.76	1X32	122.76	126.72	1X33	126.72	130.68	1X34	130.68	134.64	1X35	134.64	138.60	1X36	138.60	142.56	1X37	142.56	146.52	1X38	146.52	150.48	1X39	150.48	154.44	1X40	154.44	158.40																														
Pin数	尺寸A	尺寸B																																																																																																																																																												
1X2	3.96	7.92																																																																																																																																																												
1X3	7.92	11.88																																																																																																																																																												
1X4	11.88	15.84																																																																																																																																																												
1X5	15.84	19.80																																																																																																																																																												
1X6	19.80	23.76																																																																																																																																																												
1X7	23.76	27.72																																																																																																																																																												
1X8	27.72	31.68																																																																																																																																																												
1X9	31.68	35.64																																																																																																																																																												
1X10	35.64	39.60																																																																																																																																																												
1X11	39.60	43.56																																																																																																																																																												
1X12	43.56	47.52																																																																																																																																																												
1X13	47.52	51.48																																																																																																																																																												
1X14	51.48	55.44																																																																																																																																																												
1X15	55.44	59.40																																																																																																																																																												
1X16	59.40	63.36																																																																																																																																																												
1X17	63.36	67.32																																																																																																																																																												
1X18	67.32	71.28																																																																																																																																																												
1X19	71.28	75.24																																																																																																																																																												
1X20	75.24	79.20																																																																																																																																																												
1X21	79.20	83.16																																																																																																																																																												
1X22	83.16	87.12																																																																																																																																																												
1X23	87.12	91.08																																																																																																																																																												
1X24	91.08	95.04																																																																																																																																																												
1X25	95.04	99.00																																																																																																																																																												
1X26	99.00	102.96																																																																																																																																																												
1X27	102.96	106.92																																																																																																																																																												
1X28	106.92	110.88																																																																																																																																																												
1X29	110.88	114.84																																																																																																																																																												
1X30	114.84	118.80																																																																																																																																																												
1X31	118.80	122.76																																																																																																																																																												
1X32	122.76	126.72																																																																																																																																																												
1X33	126.72	130.68																																																																																																																																																												
1X34	130.68	134.64																																																																																																																																																												
1X35	134.64	138.60																																																																																																																																																												
1X36	138.60	142.56																																																																																																																																																												
1X37	142.56	146.52																																																																																																																																																												
1X38	146.52	150.48																																																																																																																																																												
1X39	150.48	154.44																																																																																																																																																												
1X40	154.44	158.40																																																																																																																																																												
B																																																																																																																																																														
C																																																																																																																																																														
D																																																																																																																																																														
E	Specification: Current Rating : 7AMP Temperature Range : -40℃to+105℃ Contact Resistance : 20mΩ Max Insulation Resistance : 1000MΩ Min Withstanding Voltage : AC 500V Material: Insulator : Polyester (UL94V-0) Standard:PA6T/LCP Contact: Bronze Plating : Au or Sn Over 50u" Ni																																																																																																																																																													
F	PCB LAYOUT																																																																																																																																																													
G	<table><tr><td colspan="2">① Series No:</td><td colspan="2">② Pitch:</td><td colspan="2">③ Tail&Mounting Style:</td><td colspan="2">④ No. of Pins:</td><td colspan="2">⑤ Insulator Color:</td></tr><tr><td colspan="2">P=Pin Header</td><td colspan="2">08=0.80</td><td colspan="2">90=Right Angle DIP Type</td><td colspan="2">Single Row Double Row</td><td colspan="2">A:Black B:Brom C:Red</td></tr><tr><td colspan="2">F=Female Header</td><td colspan="2">10=1.00</td><td colspan="2">9S=Straight SMT Type</td><td colspan="2">101=1*1Pin 201=2*1Pin</td><td colspan="2">D:Orange E:Yellow F:Green</td></tr><tr><td colspan="2">B=Box Header</td><td colspan="2">12=1.27</td><td colspan="2">0D=Straight DIP Type</td><td colspan="2">102=1*2Pin 202=2*2Pin</td><td colspan="2">G:Blue H:Violet J:Gray</td></tr><tr><td colspan="2">E=Ejector Header</td><td colspan="2">20=2.00</td><td colspan="2">0S=horizontal SMT Type</td><td colspan="2">140=1*40pin 240=2*40pin</td><td colspan="2">K:White P:Light Blue</td></tr><tr><td colspan="2"></td><td colspan="2">25=2.54</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2">39=3.96</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2">50=5.08</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">⑥ Material Type:</td><td colspan="2">⑦ Plating Type:</td><td colspan="2">⑧ RoHS Request:</td><td colspan="2">⑨ Customer Code</td><td colspan="2"></td></tr><tr><td colspan="2">A=PBT</td><td colspan="2">0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au</td><td colspan="2">0:No Request</td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">B-PA46</td><td colspan="2">0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"</td><td colspan="2">1:RoHS</td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">C-PA6T</td><td colspan="2">0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"</td><td colspan="2">2:HF (Halogen Free)</td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">D-PA9T</td><td colspan="2">0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">E-LCP</td><td colspan="2">0D-Sn-Au 4u" 0I-Sn-Au 40u"</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2">0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr></table>								① Series No:		② Pitch:		③ Tail&Mounting Style:		④ No. of Pins:		⑤ Insulator Color:		P=Pin Header		08=0.80		90=Right Angle DIP Type		Single Row Double Row		A:Black B:Brom C:Red		F=Female Header		10=1.00		9S=Straight SMT Type		101=1*1Pin 201=2*1Pin		D:Orange E:Yellow F:Green		B=Box Header		12=1.27		0D=Straight DIP Type		102=1*2Pin 202=2*2Pin		G:Blue H:Violet J:Gray		E=Ejector Header		20=2.00		0S=horizontal SMT Type		140=1*40pin 240=2*40pin		K:White P:Light Blue				25=2.54										39=3.96										50=5.08								⑥ Material Type:		⑦ Plating Type:		⑧ RoHS Request:		⑨ Customer Code				A=PBT		0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au		0:No Request						B-PA46		0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"		1:RoHS						C-PA6T		0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"		2:HF (Halogen Free)						D-PA9T		0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"								E-LCP		0D-Sn-Au 4u" 0I-Sn-Au 40u"										0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"							
① Series No:		② Pitch:		③ Tail&Mounting Style:		④ No. of Pins:		⑤ Insulator Color:																																																																																																																																																						
P=Pin Header		08=0.80		90=Right Angle DIP Type		Single Row Double Row		A:Black B:Brom C:Red																																																																																																																																																						
F=Female Header		10=1.00		9S=Straight SMT Type		101=1*1Pin 201=2*1Pin		D:Orange E:Yellow F:Green																																																																																																																																																						
B=Box Header		12=1.27		0D=Straight DIP Type		102=1*2Pin 202=2*2Pin		G:Blue H:Violet J:Gray																																																																																																																																																						
E=Ejector Header		20=2.00		0S=horizontal SMT Type		140=1*40pin 240=2*40pin		K:White P:Light Blue																																																																																																																																																						
		25=2.54																																																																																																																																																												
		39=3.96																																																																																																																																																												
		50=5.08																																																																																																																																																												
⑥ Material Type:		⑦ Plating Type:		⑧ RoHS Request:		⑨ Customer Code																																																																																																																																																								
A=PBT		0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au		0:No Request																																																																																																																																																										
B-PA46		0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"		1:RoHS																																																																																																																																																										
C-PA6T		0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"		2:HF (Halogen Free)																																																																																																																																																										
D-PA9T		0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"																																																																																																																																																												
E-LCP		0D-Sn-Au 4u" 0I-Sn-Au 40u"																																																																																																																																																												
		0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"																																																																																																																																																												
H	<table><tr><td></td><td></td><td></td><td></td><td>GENERAL TOLERANCES</td><td>SCALE: 1:1</td><td>NAME</td><td>DATE</td><td rowspan="4">东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827</td><td>PART. NO: KDFH-0214</td></tr><tr><td></td><td></td><td></td><td></td><td>LINEAR</td><td>ANGLES</td><td>APPROVED</td><td></td><td>DWG. NO: ENDE1214</td></tr><tr><td></td><td></td><td></td><td></td><td>0.0±0.25</td><td>X° REF±6°</td><td>DESIGNER</td><td></td><td>REV: AO</td></tr><tr><td></td><td></td><td></td><td></td><td>0.00±0.15</td><td>X° ±3°</td><td>DRAWN</td><td></td><td>SHEET: 1/1</td></tr><tr><td>REV.</td><td colspan="2">REVISION RECORD</td><td>DATE</td><td>SIZE: A4</td><td>0.000±0.08</td><td>X° X'±2°</td><td></td><td></td><td></td></tr></table>												GENERAL TOLERANCES	SCALE: 1:1	NAME	DATE	东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827	PART. NO: KDFH-0214					LINEAR	ANGLES	APPROVED		DWG. NO: ENDE1214					0.0±0.25	X° REF±6°	DESIGNER		REV: AO					0.00±0.15	X° ±3°	DRAWN		SHEET: 1/1	REV.	REVISION RECORD		DATE	SIZE: A4	0.000±0.08	X° X'±2°																																																																																																										
				GENERAL TOLERANCES	SCALE: 1:1	NAME	DATE	东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827	PART. NO: KDFH-0214																																																																																																																																																					
				LINEAR	ANGLES	APPROVED			DWG. NO: ENDE1214																																																																																																																																																					
				0.0±0.25	X° REF±6°	DESIGNER			REV: AO																																																																																																																																																					
				0.00±0.15	X° ±3°	DRAWN			SHEET: 1/1																																																																																																																																																					
REV.	REVISION RECORD		DATE	SIZE: A4	0.000±0.08	X° X'±2°																																																																																																																																																								
	1	2	3	4	5	6	7	8																																																																																																																																																						