

1		2		3		4		5		6		7		8																																																																																																																												
ROHS														For reference only																																																																																																																												
A		<table><tr><td>Pin数</td><td>尺寸A</td><td>尺寸B</td></tr><tr><td>1</td><td>-</td><td>2.54</td></tr><tr><td>2</td><td>2.54</td><td>5.08</td></tr><tr><td>3</td><td>5.08</td><td>7.62</td></tr><tr><td>4</td><td>7.62</td><td>10.16</td></tr><tr><td>5</td><td>10.16</td><td>12.70</td></tr><tr><td>6</td><td>12.70</td><td>15.24</td></tr><tr><td>7</td><td>15.24</td><td>17.78</td></tr><tr><td>8</td><td>17.78</td><td>20.32</td></tr><tr><td>9</td><td>20.32</td><td>22.86</td></tr><tr><td>10</td><td>22.86</td><td>25.40</td></tr><tr><td>11</td><td>25.40</td><td>27.94</td></tr><tr><td>12</td><td>27.94</td><td>30.48</td></tr><tr><td>13</td><td>30.48</td><td>33.02</td></tr><tr><td>14</td><td>33.02</td><td>35.56</td></tr><tr><td>15</td><td>35.56</td><td>38.10</td></tr><tr><td>16</td><td>38.10</td><td>40.64</td></tr><tr><td>17</td><td>40.64</td><td>43.18</td></tr><tr><td>18</td><td>43.18</td><td>45.72</td></tr><tr><td>19</td><td>45.72</td><td>48.26</td></tr><tr><td>20</td><td>48.26</td><td>50.80</td></tr><tr><td>21</td><td>50.80</td><td>53.34</td></tr><tr><td>22</td><td>53.34</td><td>55.88</td></tr><tr><td>23</td><td>55.88</td><td>58.42</td></tr><tr><td>24</td><td>58.42</td><td>60.96</td></tr><tr><td>25</td><td>60.96</td><td>63.50</td></tr><tr><td>26</td><td>63.50</td><td>66.04</td></tr><tr><td>27</td><td>66.04</td><td>68.58</td></tr><tr><td>28</td><td>68.58</td><td>71.12</td></tr><tr><td>29</td><td>71.12</td><td>73.66</td></tr><tr><td>30</td><td>73.66</td><td>76.20</td></tr><tr><td>31</td><td>76.20</td><td>78.74</td></tr><tr><td>32</td><td>78.74</td><td>81.28</td></tr><tr><td>33</td><td>81.28</td><td>83.82</td></tr><tr><td>34</td><td>83.82</td><td>86.36</td></tr><tr><td>35</td><td>86.36</td><td>88.90</td></tr><tr><td>36</td><td>88.90</td><td>91.44</td></tr><tr><td>37</td><td>91.44</td><td>93.98</td></tr><tr><td>38</td><td>93.98</td><td>96.52</td></tr><tr><td>39</td><td>96.52</td><td>99.06</td></tr><tr><td>40</td><td>99.06</td><td>101.60</td></tr></table>												Pin数	尺寸A	尺寸B	1	-	2.54	2	2.54	5.08	3	5.08	7.62	4	7.62	10.16	5	10.16	12.70	6	12.70	15.24	7	15.24	17.78	8	17.78	20.32	9	20.32	22.86	10	22.86	25.40	11	25.40	27.94	12	27.94	30.48	13	30.48	33.02	14	33.02	35.56	15	35.56	38.10	16	38.10	40.64	17	40.64	43.18	18	43.18	45.72	19	45.72	48.26	20	48.26	50.80	21	50.80	53.34	22	53.34	55.88	23	55.88	58.42	24	58.42	60.96	25	60.96	63.50	26	63.50	66.04	27	66.04	68.58	28	68.58	71.12	29	71.12	73.66	30	73.66	76.20	31	76.20	78.74	32	78.74	81.28	33	81.28	83.82	34	83.82	86.36	35	86.36	88.90	36	88.90	91.44	37	91.44	93.98	38	93.98	96.52	39	96.52	99.06	40	99.06	101.60	A	
Pin数	尺寸A	尺寸B																																																																																																																																								
1	-	2.54																																																																																																																																								
2	2.54	5.08																																																																																																																																								
3	5.08	7.62																																																																																																																																								
4	7.62	10.16																																																																																																																																								
5	10.16	12.70																																																																																																																																								
6	12.70	15.24																																																																																																																																								
7	15.24	17.78																																																																																																																																								
8	17.78	20.32																																																																																																																																								
9	20.32	22.86																																																																																																																																								
10	22.86	25.40																																																																																																																																								
11	25.40	27.94																																																																																																																																								
12	27.94	30.48																																																																																																																																								
13	30.48	33.02																																																																																																																																								
14	33.02	35.56																																																																																																																																								
15	35.56	38.10																																																																																																																																								
16	38.10	40.64																																																																																																																																								
17	40.64	43.18																																																																																																																																								
18	43.18	45.72																																																																																																																																								
19	45.72	48.26																																																																																																																																								
20	48.26	50.80																																																																																																																																								
21	50.80	53.34																																																																																																																																								
22	53.34	55.88																																																																																																																																								
23	55.88	58.42																																																																																																																																								
24	58.42	60.96																																																																																																																																								
25	60.96	63.50																																																																																																																																								
26	63.50	66.04																																																																																																																																								
27	66.04	68.58																																																																																																																																								
28	68.58	71.12																																																																																																																																								
29	71.12	73.66																																																																																																																																								
30	73.66	76.20																																																																																																																																								
31	76.20	78.74																																																																																																																																								
32	78.74	81.28																																																																																																																																								
33	81.28	83.82																																																																																																																																								
34	83.82	86.36																																																																																																																																								
35	86.36	88.90																																																																																																																																								
36	88.90	91.44																																																																																																																																								
37	91.44	93.98																																																																																																																																								
38	93.98	96.52																																																																																																																																								
39	96.52	99.06																																																																																																																																								
40	99.06	101.60																																																																																																																																								
B														B																																																																																																																												
C														C																																																																																																																												
D														D																																																																																																																												
E														E																																																																																																																												
F		<table><tr><td colspan="2">R 25 0D-XXX X X-XX-X-XXX</td></tr><tr><td>① Series No:</td><td>② Pitch:</td><td>③ Tail&Mounting Style:</td><td>④ No. of Pins:</td><td>⑤ Insulator Color:</td></tr><tr><td>P=Pin Header</td><td>08=0.80</td><td>90=Right Angle DIP Type</td><td>Single Row Double Row</td><td>A:Black B:Brom C:Red</td></tr><tr><td>F=Female Header</td><td>10=1.00</td><td>9S=Straight SMT Type</td><td>101=1*1Pin 201=2*1Pin</td><td>D:Orange E:Yellow F:Green</td></tr><tr><td>B=Box Header</td><td>12=1.27</td><td>0D=Straight DIP Type</td><td>102=1*2Pin 202=2*2Pin</td><td>G:Blue H:Violet J:Gray</td></tr><tr><td>E=Ejector Header</td><td>20=2.00</td><td>0S=horizontal SMT Type</td><td>140=1*40pin 240=2*40pin</td><td>K:White P:Light Blue</td></tr><tr><td>R=Round Pin</td><td>25=2.54</td><td></td><td></td><td></td></tr><tr><td></td><td>39=3.96</td><td></td><td></td><td></td></tr><tr><td></td><td>50=5.08</td><td></td><td></td><td></td></tr></table>												R 25 0D-XXX X X-XX-X-XXX		① Series No:	② Pitch:	③ Tail&Mounting Style:	④ No. of Pins:	⑤ Insulator Color:	P=Pin Header	08=0.80	90=Right Angle DIP Type	Single Row Double Row	A:Black B:Brom C:Red	F=Female Header	10=1.00	9S=Straight SMT Type	101=1*1Pin 201=2*1Pin	D:Orange E:Yellow F:Green	B=Box Header	12=1.27	0D=Straight DIP Type	102=1*2Pin 202=2*2Pin	G:Blue H:Violet J:Gray	E=Ejector Header	20=2.00	0S=horizontal SMT Type	140=1*40pin 240=2*40pin	K:White P:Light Blue	R=Round Pin	25=2.54					39=3.96					50=5.08				F																																																																																		
R 25 0D-XXX X X-XX-X-XXX																																																																																																																																										
① Series No:	② Pitch:	③ Tail&Mounting Style:	④ No. of Pins:	⑤ Insulator Color:																																																																																																																																						
P=Pin Header	08=0.80	90=Right Angle DIP Type	Single Row Double Row	A:Black B:Brom C:Red																																																																																																																																						
F=Female Header	10=1.00	9S=Straight SMT Type	101=1*1Pin 201=2*1Pin	D:Orange E:Yellow F:Green																																																																																																																																						
B=Box Header	12=1.27	0D=Straight DIP Type	102=1*2Pin 202=2*2Pin	G:Blue H:Violet J:Gray																																																																																																																																						
E=Ejector Header	20=2.00	0S=horizontal SMT Type	140=1*40pin 240=2*40pin	K:White P:Light Blue																																																																																																																																						
R=Round Pin	25=2.54																																																																																																																																									
	39=3.96																																																																																																																																									
	50=5.08																																																																																																																																									
G		<table><tr><td>⑥ Material Type:</td><td>⑦ Plating Type:</td><td>⑧ RoHS Request:</td><td>⑨ Customer Code</td></tr><tr><td>A=PBT</td><td>0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au</td><td>0:No Request</td><td></td></tr><tr><td>B=PA46</td><td>0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"</td><td>1:RoHS</td><td></td></tr><tr><td>C=PA6T</td><td>0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"</td><td>2:HF (Halogen Free)</td><td></td></tr><tr><td>D=PA9T</td><td>0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"</td><td></td><td></td></tr><tr><td>E=LCP</td><td>0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"</td><td></td><td></td></tr><tr><td></td><td>0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"</td><td></td><td></td></tr></table>												⑥ Material Type:	⑦ Plating Type:	⑧ RoHS Request:	⑨ Customer Code	A=PBT	0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au	0:No Request		B=PA46	0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"	1:RoHS		C=PA6T	0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"	2:HF (Halogen Free)		D=PA9T	0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"			E=LCP	0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"				0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"			G																																																																																																
⑥ Material Type:	⑦ Plating Type:	⑧ RoHS Request:	⑨ Customer Code																																																																																																																																							
A=PBT	0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au	0:No Request																																																																																																																																								
B=PA46	0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"	1:RoHS																																																																																																																																								
C=PA6T	0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"	2:HF (Halogen Free)																																																																																																																																								
D=PA9T	0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"																																																																																																																																									
E=LCP	0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"																																																																																																																																									
	0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"																																																																																																																																									
H		<table><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">GENERAL TOLERANCES</td><td colspan="2">SCALE: 1:1</td><td colspan="2">NAME</td><td colspan="2">DATE</td><td colspan="2" rowspan="4"> 东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827</td><td colspan="2">PART. NO:</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">APPROVED</td><td colspan="2"></td><td colspan="2"></td><td colspan="2">KDRH-0046</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">DESIGNER</td><td colspan="2"></td><td colspan="2"></td><td colspan="2">DWG. NO:</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">DRAWN</td><td colspan="2"></td><td colspan="2"></td><td colspan="2">ENDE4046</td></tr><tr><td colspan="2">REV.</td><td colspan="2">REVISION RECORD</td><td colspan="2">DATE</td><td colspan="2">UNIT: MM</td><td colspan="2">0.00±0.15</td><td colspan="2">X° ±3°</td><td colspan="2"></td><td colspan="2">TITLE:</td><td colspan="2">REV: AO</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">SIZE: A4</td><td colspan="2">0.000±0.08</td><td colspan="2">X° X'±2°</td><td colspan="2"></td><td colspan="2">Pitch2.54mm Round Pin,Single Row, Plastic Height 1.9mm,DIP</td><td colspan="2">SHEET: 1/1</td></tr><tr><td colspan="2">1</td><td colspan="2">2</td><td colspan="2">3</td><td colspan="2">4</td><td colspan="2">5</td><td colspan="2">6</td><td colspan="2">7</td><td colspan="2">8</td><td colspan="2"></td></tr></table>																		GENERAL TOLERANCES		SCALE: 1:1		NAME		DATE		 东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827		PART. NO:										APPROVED						KDRH-0046										DESIGNER						DWG. NO:										DRAWN						ENDE4046		REV.		REVISION RECORD		DATE		UNIT: MM		0.00±0.15		X° ±3°				TITLE:		REV: AO								SIZE: A4		0.000±0.08		X° X'±2°				Pitch2.54mm Round Pin,Single Row, Plastic Height 1.9mm,DIP		SHEET: 1/1		1		2		3		4		5		6		7		8				H				
						GENERAL TOLERANCES		SCALE: 1:1		NAME		DATE		 东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827		PART. NO:																																																																																																																										
								APPROVED								KDRH-0046																																																																																																																										
								DESIGNER								DWG. NO:																																																																																																																										
								DRAWN								ENDE4046																																																																																																																										
REV.		REVISION RECORD		DATE		UNIT: MM		0.00±0.15		X° ±3°				TITLE:		REV: AO																																																																																																																										
						SIZE: A4		0.000±0.08		X° X'±2°				Pitch2.54mm Round Pin,Single Row, Plastic Height 1.9mm,DIP		SHEET: 1/1																																																																																																																										
1		2		3		4		5		6		7		8																																																																																																																												

Specification:
Current Rating : 3AMP
Temperature Range : -40℃to+105℃
Contact Resistance : 20mΩ Max
Insulation Resistance : 1000MΩ Min
Withstanding Voltage : AC 1000V
Material:
Insulator : Polyester (UL94V-0)
Standard:PBT/PA6T/LCP
Contact: Brass
Plating : Au or Sn Over 50u" Ni