

	1	2	3	4	5	6	7	8																																																																																																																																																									
A	ROHS							For reference only																																																																																																																																																									
B	<table><tr><td>Pin数</td><td>尺寸A</td><td>尺寸B</td></tr><tr><td>1</td><td></td><td>1.68</td></tr><tr><td>2</td><td>1.27</td><td>2.95</td></tr><tr><td>3</td><td>2.54</td><td>4.22</td></tr><tr><td>4</td><td>3.81</td><td>5.49</td></tr><tr><td>5</td><td>5.08</td><td>6.76</td></tr><tr><td>6</td><td>6.35</td><td>8.03</td></tr><tr><td>7</td><td>7.62</td><td>9.30</td></tr><tr><td>8</td><td>8.89</td><td>10.57</td></tr><tr><td>9</td><td>10.16</td><td>11.84</td></tr><tr><td>10</td><td>11.43</td><td>13.11</td></tr><tr><td>11</td><td>12.70</td><td>14.38</td></tr><tr><td>12</td><td>13.97</td><td>15.65</td></tr><tr><td>13</td><td>15.24</td><td>16.92</td></tr><tr><td>14</td><td>16.51</td><td>18.19</td></tr><tr><td>15</td><td>17.78</td><td>19.46</td></tr><tr><td>16</td><td>19.05</td><td>20.73</td></tr><tr><td>17</td><td>20.32</td><td>22.00</td></tr><tr><td>18</td><td>21.59</td><td>23.27</td></tr><tr><td>19</td><td>22.86</td><td>24.54</td></tr><tr><td>20</td><td>24.13</td><td>25.81</td></tr><tr><td>21</td><td>25.40</td><td>27.08</td></tr><tr><td>22</td><td>26.67</td><td>28.35</td></tr><tr><td>23</td><td>27.94</td><td>29.62</td></tr><tr><td>24</td><td>29.21</td><td>30.89</td></tr><tr><td>25</td><td>30.48</td><td>32.16</td></tr><tr><td>26</td><td>31.75</td><td>33.43</td></tr><tr><td>27</td><td>33.02</td><td>34.70</td></tr><tr><td>28</td><td>34.29</td><td>35.97</td></tr><tr><td>29</td><td>35.56</td><td>37.24</td></tr><tr><td>30</td><td>36.83</td><td>38.51</td></tr><tr><td>31</td><td>38.10</td><td>39.78</td></tr><tr><td>32</td><td>39.37</td><td>41.05</td></tr><tr><td>33</td><td>40.64</td><td>42.32</td></tr><tr><td>34</td><td>41.91</td><td>43.59</td></tr><tr><td>35</td><td>43.18</td><td>44.86</td></tr><tr><td>36</td><td>44.45</td><td>46.13</td></tr><tr><td>37</td><td>45.72</td><td>47.40</td></tr><tr><td>38</td><td>46.99</td><td>48.67</td></tr><tr><td>39</td><td>48.26</td><td>49.94</td></tr><tr><td>40</td><td>49.53</td><td>51.21</td></tr><tr><td>41</td><td>50.80</td><td>52.48</td></tr><tr><td>42</td><td>52.07</td><td>53.75</td></tr><tr><td>43</td><td>53.34</td><td>55.02</td></tr><tr><td>44</td><td>54.61</td><td>56.29</td></tr><tr><td>45</td><td>55.88</td><td>57.56</td></tr><tr><td>46</td><td>57.15</td><td>58.83</td></tr><tr><td>47</td><td>58.42</td><td>60.10</td></tr><tr><td>48</td><td>59.69</td><td>61.37</td></tr><tr><td>49</td><td>60.96</td><td>62.64</td></tr><tr><td>50</td><td>62.23</td><td>63.91</td></tr></table>							Pin数	尺寸A	尺寸B	1		1.68	2	1.27	2.95	3	2.54	4.22	4	3.81	5.49	5	5.08	6.76	6	6.35	8.03	7	7.62	9.30	8	8.89	10.57	9	10.16	11.84	10	11.43	13.11	11	12.70	14.38	12	13.97	15.65	13	15.24	16.92	14	16.51	18.19	15	17.78	19.46	16	19.05	20.73	17	20.32	22.00	18	21.59	23.27	19	22.86	24.54	20	24.13	25.81	21	25.40	27.08	22	26.67	28.35	23	27.94	29.62	24	29.21	30.89	25	30.48	32.16	26	31.75	33.43	27	33.02	34.70	28	34.29	35.97	29	35.56	37.24	30	36.83	38.51	31	38.10	39.78	32	39.37	41.05	33	40.64	42.32	34	41.91	43.59	35	43.18	44.86	36	44.45	46.13	37	45.72	47.40	38	46.99	48.67	39	48.26	49.94	40	49.53	51.21	41	50.80	52.48	42	52.07	53.75	43	53.34	55.02	44	54.61	56.29	45	55.88	57.56	46	57.15	58.83	47	58.42	60.10	48	59.69	61.37	49	60.96	62.64	50	62.23	63.91	
Pin数	尺寸A	尺寸B																																																																																																																																																															
1		1.68																																																																																																																																																															
2	1.27	2.95																																																																																																																																																															
3	2.54	4.22																																																																																																																																																															
4	3.81	5.49																																																																																																																																																															
5	5.08	6.76																																																																																																																																																															
6	6.35	8.03																																																																																																																																																															
7	7.62	9.30																																																																																																																																																															
8	8.89	10.57																																																																																																																																																															
9	10.16	11.84																																																																																																																																																															
10	11.43	13.11																																																																																																																																																															
11	12.70	14.38																																																																																																																																																															
12	13.97	15.65																																																																																																																																																															
13	15.24	16.92																																																																																																																																																															
14	16.51	18.19																																																																																																																																																															
15	17.78	19.46																																																																																																																																																															
16	19.05	20.73																																																																																																																																																															
17	20.32	22.00																																																																																																																																																															
18	21.59	23.27																																																																																																																																																															
19	22.86	24.54																																																																																																																																																															
20	24.13	25.81																																																																																																																																																															
21	25.40	27.08																																																																																																																																																															
22	26.67	28.35																																																																																																																																																															
23	27.94	29.62																																																																																																																																																															
24	29.21	30.89																																																																																																																																																															
25	30.48	32.16																																																																																																																																																															
26	31.75	33.43																																																																																																																																																															
27	33.02	34.70																																																																																																																																																															
28	34.29	35.97																																																																																																																																																															
29	35.56	37.24																																																																																																																																																															
30	36.83	38.51																																																																																																																																																															
31	38.10	39.78																																																																																																																																																															
32	39.37	41.05																																																																																																																																																															
33	40.64	42.32																																																																																																																																																															
34	41.91	43.59																																																																																																																																																															
35	43.18	44.86																																																																																																																																																															
36	44.45	46.13																																																																																																																																																															
37	45.72	47.40																																																																																																																																																															
38	46.99	48.67																																																																																																																																																															
39	48.26	49.94																																																																																																																																																															
40	49.53	51.21																																																																																																																																																															
41	50.80	52.48																																																																																																																																																															
42	52.07	53.75																																																																																																																																																															
43	53.34	55.02																																																																																																																																																															
44	54.61	56.29																																																																																																																																																															
45	55.88	57.56																																																																																																																																																															
46	57.15	58.83																																																																																																																																																															
47	58.42	60.10																																																																																																																																																															
48	59.69	61.37																																																																																																																																																															
49	60.96	62.64																																																																																																																																																															
50	62.23	63.91																																																																																																																																																															
C																																																																																																																																																																	
D																																																																																																																																																																	
E	Specification: Current Rating : 1AMP Temperature Range : -40℃to+105℃ Contact Resistance : 20mΩ Max Insulation Resistance : 1000MΩ Min Withstanding Voltage : AC 500V Material: Insulator : Polyester (UL94V-0) Standard:PA6T/LCP Contact: Bronze Plating : Au or Sn Over 50u" Ni																																																																																																																																																																
F	PCB LAYOUT																																																																																																																																																																
G	<table><tr><td colspan="4">R 12 9S-XXX X X-XX-X-XXX</td></tr><tr><td>① Series No:</td><td>② Pitch:</td><td>③ Tail&Mounting Style:</td><td>④ No. of Pins:</td><td>⑤ Insulator Color:</td></tr><tr><td>P=Pin Header</td><td>08=0.80</td><td>90=Right Angle DIP Type</td><td>Single Row Double Row</td><td>A:Black B:Brom C:Red</td></tr><tr><td>F=Female Header</td><td>10=1.00</td><td>9S=Straight SMT Type</td><td>101=1*1Pin 201=2*1Pin</td><td>D:Orange E:Yellow F:Green</td></tr><tr><td>B=Box Header</td><td>12=1.27</td><td>0D=Straight DIP Type</td><td>102=1*2Pin 202=2*2Pin</td><td>G:Blue H:Violet J:Gray</td></tr><tr><td>E=Ejector Header</td><td>20=2.00</td><td>0S=horizontal SMT Type</td><td>! ! ! !</td><td>K:White P:Light Blue</td></tr><tr><td>R=Round Pin</td><td>25=2.54</td><td></td><td>140=1*40pin 240=2*40pin</td><td></td></tr><tr><td></td><td>39=3.96</td><td></td><td></td><td></td></tr><tr><td></td><td>50=5.08</td><td></td><td></td><td></td></tr><tr><td>⑥ Material Type:</td><td>⑦ Plating Type:</td><td>⑧ RoHS Request:</td><td>⑨ Customer Code</td><td></td></tr><tr><td>A=PBT</td><td>0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au</td><td>0:No Request</td><td></td><td></td></tr><tr><td>B=PA66</td><td>0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"</td><td>1:RoHS</td><td></td><td></td></tr><tr><td>C=PA6T</td><td>0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"</td><td>2:HF (Halogen Free)</td><td></td><td></td></tr><tr><td>D=PA9T</td><td>0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"</td><td></td><td></td><td></td></tr><tr><td>E=LCP</td><td>0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"</td><td></td><td></td><td></td></tr><tr><td></td><td>0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"</td><td></td><td></td><td></td></tr></table>							R 12 9S-XXX X X-XX-X-XXX				① Series No:	② Pitch:	③ Tail&Mounting Style:	④ No. of Pins:	⑤ Insulator Color:	P=Pin Header	08=0.80	90=Right Angle DIP Type	Single Row Double Row	A:Black B:Brom C:Red	F=Female Header	10=1.00	9S=Straight SMT Type	101=1*1Pin 201=2*1Pin	D:Orange E:Yellow F:Green	B=Box Header	12=1.27	0D=Straight DIP Type	102=1*2Pin 202=2*2Pin	G:Blue H:Violet J:Gray	E=Ejector Header	20=2.00	0S=horizontal SMT Type	! ! ! !	K:White P:Light Blue	R=Round Pin	25=2.54		140=1*40pin 240=2*40pin			39=3.96					50=5.08				⑥ Material Type:	⑦ Plating Type:	⑧ RoHS Request:	⑨ Customer Code		A=PBT	0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au	0:No Request			B=PA66	0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"	1:RoHS			C=PA6T	0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"	2:HF (Halogen Free)			D=PA9T	0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"				E=LCP	0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"					0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"																																																																														
R 12 9S-XXX X X-XX-X-XXX																																																																																																																																																																	
① Series No:	② Pitch:	③ Tail&Mounting Style:	④ No. of Pins:	⑤ Insulator Color:																																																																																																																																																													
P=Pin Header	08=0.80	90=Right Angle DIP Type	Single Row Double Row	A:Black B:Brom C:Red																																																																																																																																																													
F=Female Header	10=1.00	9S=Straight SMT Type	101=1*1Pin 201=2*1Pin	D:Orange E:Yellow F:Green																																																																																																																																																													
B=Box Header	12=1.27	0D=Straight DIP Type	102=1*2Pin 202=2*2Pin	G:Blue H:Violet J:Gray																																																																																																																																																													
E=Ejector Header	20=2.00	0S=horizontal SMT Type	! ! ! !	K:White P:Light Blue																																																																																																																																																													
R=Round Pin	25=2.54		140=1*40pin 240=2*40pin																																																																																																																																																														
	39=3.96																																																																																																																																																																
	50=5.08																																																																																																																																																																
⑥ Material Type:	⑦ Plating Type:	⑧ RoHS Request:	⑨ Customer Code																																																																																																																																																														
A=PBT	0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au	0:No Request																																																																																																																																																															
B=PA66	0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"	1:RoHS																																																																																																																																																															
C=PA6T	0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"	2:HF (Halogen Free)																																																																																																																																																															
D=PA9T	0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"																																																																																																																																																																
E=LCP	0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"																																																																																																																																																																
	0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"																																																																																																																																																																
H	<table><tr><td></td><td></td><td></td><td></td><td>GENERAL TOLERANCES</td><td>SCALE: 1:1</td><td>NAME</td><td>DATE</td><td rowspan="5">东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827</td><td>PART. NO:</td></tr><tr><td></td><td></td><td></td><td></td><td>LINEAR</td><td>ANGLES</td><td>APPROVED</td><td></td><td>KDRH-0012</td></tr><tr><td></td><td></td><td></td><td></td><td>0.0±0.25</td><td>X° REF±6°</td><td>DESIGNER</td><td></td><td>DWG. NO:</td></tr><tr><td></td><td></td><td></td><td></td><td>0.00±0.15</td><td>X° ±3°</td><td></td><td></td><td>ENDE4012</td></tr><tr><td>REV.</td><td>REVISION RECORD</td><td>DATE</td><td>UNIT: MM</td><td>0.000±0.08</td><td>X° X'±2°</td><td>DRAWN</td><td></td><td>REV: AO SHEET: 1/1</td></tr></table>											GENERAL TOLERANCES	SCALE: 1:1	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827	PART. NO:					LINEAR	ANGLES	APPROVED		KDRH-0012					0.0±0.25	X° REF±6°	DESIGNER		DWG. NO:					0.00±0.15	X° ±3°			ENDE4012	REV.	REVISION RECORD	DATE	UNIT: MM	0.000±0.08	X° X'±2°	DRAWN		REV: AO SHEET: 1/1																																																																																																												
				GENERAL TOLERANCES	SCALE: 1:1	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827	PART. NO:																																																																																																																																																								
				LINEAR	ANGLES	APPROVED			KDRH-0012																																																																																																																																																								
				0.0±0.25	X° REF±6°	DESIGNER			DWG. NO:																																																																																																																																																								
				0.00±0.15	X° ±3°				ENDE4012																																																																																																																																																								
REV.	REVISION RECORD	DATE	UNIT: MM	0.000±0.08	X° X'±2°	DRAWN			REV: AO SHEET: 1/1																																																																																																																																																								
	1	2	3	4	5	6	7	8																																																																																																																																																									