

1			2		3		4		5		6		7		8																																																																																																																															
ROHS												For reference only																																																																																																																																		
<table><tr><td>Pin数</td><td>尺寸A</td><td>尺寸B</td></tr><tr><td>1</td><td></td><td>1.778</td></tr><tr><td>2</td><td>1.778</td><td>3.556</td></tr><tr><td>3</td><td>3.556</td><td>5.334</td></tr><tr><td>4</td><td>5.334</td><td>7.112</td></tr><tr><td>5</td><td>7.112</td><td>8.890</td></tr><tr><td>6</td><td>8.890</td><td>10.668</td></tr><tr><td>7</td><td>10.668</td><td>14.446</td></tr><tr><td>8</td><td>14.446</td><td>14.224</td></tr><tr><td>9</td><td>14.224</td><td>16.002</td></tr><tr><td>10</td><td>16.002</td><td>17.780</td></tr><tr><td>11</td><td>17.780</td><td>19.558</td></tr><tr><td>12</td><td>19.558</td><td>21.336</td></tr><tr><td>13</td><td>21.336</td><td>23.114</td></tr><tr><td>14</td><td>23.114</td><td>24.892</td></tr><tr><td>15</td><td>24.892</td><td>26.670</td></tr><tr><td>16</td><td>26.670</td><td>28.448</td></tr><tr><td>17</td><td>28.448</td><td>30.226</td></tr><tr><td>18</td><td>30.226</td><td>32.004</td></tr><tr><td>19</td><td>32.004</td><td>33.782</td></tr><tr><td>20</td><td>33.782</td><td>35.560</td></tr><tr><td>21</td><td>35.560</td><td>37.338</td></tr><tr><td>22</td><td>37.338</td><td>39.116</td></tr><tr><td>23</td><td>39.116</td><td>40.894</td></tr><tr><td>24</td><td>40.894</td><td>42.672</td></tr><tr><td>25</td><td>42.672</td><td>44.450</td></tr><tr><td>26</td><td>44.450</td><td>46.228</td></tr><tr><td>27</td><td>46.228</td><td>48.006</td></tr><tr><td>28</td><td>48.006</td><td>49.784</td></tr><tr><td>29</td><td>49.784</td><td>51.562</td></tr><tr><td>30</td><td>51.562</td><td>53.340</td></tr><tr><td>31</td><td>53.340</td><td>55.118</td></tr><tr><td>32</td><td>55.118</td><td>56.896</td></tr><tr><td>33</td><td>56.896</td><td>58.674</td></tr><tr><td>34</td><td>58.674</td><td>60.452</td></tr><tr><td>35</td><td>60.452</td><td>62.230</td></tr><tr><td>36</td><td>62.230</td><td>64.008</td></tr><tr><td>37</td><td>64.008</td><td>65.786</td></tr><tr><td>38</td><td>65.786</td><td>67.564</td></tr><tr><td>39</td><td>67.564</td><td>69.342</td></tr><tr><td>40</td><td>69.342</td><td>71.120</td></tr></table>												Pin数	尺寸A	尺寸B	1		1.778	2	1.778	3.556	3	3.556	5.334	4	5.334	7.112	5	7.112	8.890	6	8.890	10.668	7	10.668	14.446	8	14.446	14.224	9	14.224	16.002	10	16.002	17.780	11	17.780	19.558	12	19.558	21.336	13	21.336	23.114	14	23.114	24.892	15	24.892	26.670	16	26.670	28.448	17	28.448	30.226	18	30.226	32.004	19	32.004	33.782	20	33.782	35.560	21	35.560	37.338	22	37.338	39.116	23	39.116	40.894	24	40.894	42.672	25	42.672	44.450	26	44.450	46.228	27	46.228	48.006	28	48.006	49.784	29	49.784	51.562	30	51.562	53.340	31	53.340	55.118	32	55.118	56.896	33	56.896	58.674	34	58.674	60.452	35	60.452	62.230	36	62.230	64.008	37	64.008	65.786	38	65.786	67.564	39	67.564	69.342	40	69.342	71.120								
Pin数	尺寸A	尺寸B																																																																																																																																												
1		1.778																																																																																																																																												
2	1.778	3.556																																																																																																																																												
3	3.556	5.334																																																																																																																																												
4	5.334	7.112																																																																																																																																												
5	7.112	8.890																																																																																																																																												
6	8.890	10.668																																																																																																																																												
7	10.668	14.446																																																																																																																																												
8	14.446	14.224																																																																																																																																												
9	14.224	16.002																																																																																																																																												
10	16.002	17.780																																																																																																																																												
11	17.780	19.558																																																																																																																																												
12	19.558	21.336																																																																																																																																												
13	21.336	23.114																																																																																																																																												
14	23.114	24.892																																																																																																																																												
15	24.892	26.670																																																																																																																																												
16	26.670	28.448																																																																																																																																												
17	28.448	30.226																																																																																																																																												
18	30.226	32.004																																																																																																																																												
19	32.004	33.782																																																																																																																																												
20	33.782	35.560																																																																																																																																												
21	35.560	37.338																																																																																																																																												
22	37.338	39.116																																																																																																																																												
23	39.116	40.894																																																																																																																																												
24	40.894	42.672																																																																																																																																												
25	42.672	44.450																																																																																																																																												
26	44.450	46.228																																																																																																																																												
27	46.228	48.006																																																																																																																																												
28	48.006	49.784																																																																																																																																												
29	49.784	51.562																																																																																																																																												
30	51.562	53.340																																																																																																																																												
31	53.340	55.118																																																																																																																																												
32	55.118	56.896																																																																																																																																												
33	56.896	58.674																																																																																																																																												
34	58.674	60.452																																																																																																																																												
35	60.452	62.230																																																																																																																																												
36	62.230	64.008																																																																																																																																												
37	64.008	65.786																																																																																																																																												
38	65.786	67.564																																																																																																																																												
39	67.564	69.342																																																																																																																																												
40	69.342	71.120																																																																																																																																												
<table><tr><td colspan="2">A±0.20</td></tr><tr><td colspan="2">1.778</td></tr><tr><td colspan="2">φ0.43</td></tr></table>												A±0.20		1.778		φ0.43						Specification: Current Rating : 1AMP Temperature Range : -40℃to+105℃ Contact Resistance : 20mΩ Max Insulation Resistance : 1000MΩ Min Withstanding Voltage : AC 500V Material: Insulator : Polyester (UL94V-0) Standard:PBT/PA6T/LCP Contact: Bronze Plating : Au or Sn Over 50u" Ni																																																																																																																								
A±0.20																																																																																																																																														
1.778																																																																																																																																														
φ0.43																																																																																																																																														
<table><tr><td colspan="4">R 17 9D-XXX X X-XX-X-XXX</td></tr><tr><td colspan="4">① Series No: P=Pin Header F=Female Header B=Box Header E=Ejector Header R=Round Pin</td></tr><tr><td colspan="4">② Pitch: 08=0.80 10=1.00 12=1.27 17=1.778 20=2.00 25=2.54</td></tr><tr><td colspan="4">③ Tail&Mounting Style: 90=Right Angle DIP Type 9S=Straight SMT Type 0D=Straight DIP Type 0S=horizontal SMT Type</td></tr><tr><td colspan="4">④ No. of Pins: Single Row Double Row 101=1*1Pin 201=2*1Pin 102=1*2Pin 202=2*2Pin 140=1*40pin 240=2*40pin</td></tr><tr><td colspan="4">⑤ Insulator Color: A:Black B:Brom C:Red D:Orange E:Yellow F:Green G:Blue H:Violet J:Gray K:White P:Light Blue</td></tr><tr><td colspan="4">⑥ Material Type: A=PBT B=PA6 C=PA6T D=PA9T E=LCP</td></tr><tr><td colspan="4">⑦ Plating Type: 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au 0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u" 0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u" 0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u" 0D-Sn-Au 4u" 0I-Sn-Au 40u" 0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"</td></tr><tr><td colspan="4">⑧ RoHS Request: 0:No Request 1:RoHS 2:HF (Halogen Free)</td></tr><tr><td colspan="4">⑨ Customer Code</td></tr></table>												R 17 9D-XXX X X-XX-X-XXX				① Series No: P=Pin Header F=Female Header B=Box Header E=Ejector Header R=Round Pin				② Pitch: 08=0.80 10=1.00 12=1.27 17=1.778 20=2.00 25=2.54				③ Tail&Mounting Style: 90=Right Angle DIP Type 9S=Straight SMT Type 0D=Straight DIP Type 0S=horizontal SMT Type				④ No. of Pins: Single Row Double Row 101=1*1Pin 201=2*1Pin 102=1*2Pin 202=2*2Pin 140=1*40pin 240=2*40pin				⑤ Insulator Color: A:Black B:Brom C:Red D:Orange E:Yellow F:Green G:Blue H:Violet J:Gray K:White P:Light Blue				⑥ Material Type: A=PBT B=PA6 C=PA6T D=PA9T E=LCP				⑦ Plating Type: 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au 0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u" 0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u" 0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u" 0D-Sn-Au 4u" 0I-Sn-Au 40u" 0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"				⑧ RoHS Request: 0:No Request 1:RoHS 2:HF (Halogen Free)				⑨ Customer Code																																																																																														
R 17 9D-XXX X X-XX-X-XXX																																																																																																																																														
① Series No: P=Pin Header F=Female Header B=Box Header E=Ejector Header R=Round Pin																																																																																																																																														
② Pitch: 08=0.80 10=1.00 12=1.27 17=1.778 20=2.00 25=2.54																																																																																																																																														
③ Tail&Mounting Style: 90=Right Angle DIP Type 9S=Straight SMT Type 0D=Straight DIP Type 0S=horizontal SMT Type																																																																																																																																														
④ No. of Pins: Single Row Double Row 101=1*1Pin 201=2*1Pin 102=1*2Pin 202=2*2Pin 140=1*40pin 240=2*40pin																																																																																																																																														
⑤ Insulator Color: A:Black B:Brom C:Red D:Orange E:Yellow F:Green G:Blue H:Violet J:Gray K:White P:Light Blue																																																																																																																																														
⑥ Material Type: A=PBT B=PA6 C=PA6T D=PA9T E=LCP																																																																																																																																														
⑦ Plating Type: 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au 0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u" 0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u" 0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u" 0D-Sn-Au 4u" 0I-Sn-Au 40u" 0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"																																																																																																																																														
⑧ RoHS Request: 0:No Request 1:RoHS 2:HF (Halogen Free)																																																																																																																																														
⑨ Customer Code																																																																																																																																														
<table><tr><td colspan="2">SCALE: 1:1</td><td colspan="2">NAME</td><td colspan="2">DATE</td></tr><tr><td colspan="2">APPROVED</td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">DESIGNER</td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">DRAWN</td><td colspan="2"></td><td colspan="2"></td></tr></table>												SCALE: 1:1		NAME		DATE		APPROVED						DESIGNER						DRAWN						东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827				PART. NO: KDRH-0026 DWG. NO: ENDE4026 REV: A0 SHEET: 1/1																																																																																																						
SCALE: 1:1		NAME		DATE																																																																																																																																										
APPROVED																																																																																																																																														
DESIGNER																																																																																																																																														
DRAWN																																																																																																																																														
<table><tr><td colspan="2">REV.</td><td colspan="2">REVISION RECORD</td><td colspan="2">DATE</td><td colspan="2">UNIT: MM</td><td colspan="2">SIZE: A4</td><td colspan="2">0.000±0.08</td><td colspan="2">X° X'±2°</td><td colspan="2">DRAWN</td></tr><tr><td colspan="2">1</td><td colspan="2">2</td><td colspan="2">3</td><td colspan="2">4</td><td colspan="2">5</td><td colspan="2">6</td><td colspan="2">7</td><td colspan="2">8</td></tr></table>												REV.		REVISION RECORD		DATE		UNIT: MM		SIZE: A4		0.000±0.08		X° X'±2°		DRAWN		1		2		3		4		5		6		7		8																																																																																																				
REV.		REVISION RECORD		DATE		UNIT: MM		SIZE: A4		0.000±0.08		X° X'±2°		DRAWN																																																																																																																																
1		2		3		4		5		6		7		8																																																																																																																																