

	1	2	3	4	5	6	7	8																																																																																																																											
A	ROHS							For reference only																																																																																																																											
B	<table><tr><td>Pin数</td><td>尺寸A</td><td>尺寸B</td></tr><tr><td>1</td><td></td><td>1.778</td></tr><tr><td>2</td><td>1.778</td><td>3.556</td></tr><tr><td>3</td><td>3.556</td><td>5.334</td></tr><tr><td>4</td><td>5.334</td><td>7.112</td></tr><tr><td>5</td><td>7.112</td><td>8.890</td></tr><tr><td>6</td><td>8.890</td><td>10.668</td></tr><tr><td>7</td><td>10.668</td><td>14.446</td></tr><tr><td>8</td><td>14.446</td><td>14.224</td></tr><tr><td>9</td><td>14.224</td><td>16.002</td></tr><tr><td>10</td><td>16.002</td><td>17.780</td></tr><tr><td>11</td><td>17.780</td><td>19.558</td></tr><tr><td>12</td><td>19.558</td><td>21.336</td></tr><tr><td>13</td><td>21.336</td><td>23.114</td></tr><tr><td>14</td><td>23.114</td><td>24.892</td></tr><tr><td>15</td><td>24.892</td><td>26.670</td></tr><tr><td>16</td><td>26.670</td><td>28.448</td></tr><tr><td>17</td><td>28.448</td><td>30.226</td></tr><tr><td>18</td><td>30.226</td><td>32.004</td></tr><tr><td>19</td><td>32.004</td><td>33.782</td></tr><tr><td>20</td><td>33.782</td><td>35.560</td></tr><tr><td>21</td><td>35.560</td><td>37.338</td></tr><tr><td>22</td><td>37.338</td><td>39.116</td></tr><tr><td>23</td><td>39.116</td><td>40.894</td></tr><tr><td>24</td><td>40.894</td><td>42.672</td></tr><tr><td>25</td><td>42.672</td><td>44.450</td></tr><tr><td>26</td><td>44.450</td><td>46.228</td></tr><tr><td>27</td><td>46.228</td><td>48.006</td></tr><tr><td>28</td><td>48.006</td><td>49.784</td></tr><tr><td>29</td><td>49.784</td><td>51.562</td></tr><tr><td>30</td><td>51.562</td><td>53.340</td></tr><tr><td>31</td><td>53.340</td><td>55.118</td></tr><tr><td>32</td><td>55.118</td><td>56.896</td></tr><tr><td>33</td><td>56.896</td><td>58.674</td></tr><tr><td>34</td><td>58.674</td><td>60.452</td></tr><tr><td>35</td><td>60.452</td><td>62.230</td></tr><tr><td>36</td><td>62.230</td><td>64.008</td></tr><tr><td>37</td><td>64.008</td><td>65.786</td></tr><tr><td>38</td><td>65.786</td><td>67.564</td></tr><tr><td>39</td><td>67.564</td><td>69.342</td></tr><tr><td>40</td><td>69.342</td><td>71.120</td></tr></table>							Pin数	尺寸A	尺寸B	1		1.778	2	1.778	3.556	3	3.556	5.334	4	5.334	7.112	5	7.112	8.890	6	8.890	10.668	7	10.668	14.446	8	14.446	14.224	9	14.224	16.002	10	16.002	17.780	11	17.780	19.558	12	19.558	21.336	13	21.336	23.114	14	23.114	24.892	15	24.892	26.670	16	26.670	28.448	17	28.448	30.226	18	30.226	32.004	19	32.004	33.782	20	33.782	35.560	21	35.560	37.338	22	37.338	39.116	23	39.116	40.894	24	40.894	42.672	25	42.672	44.450	26	44.450	46.228	27	46.228	48.006	28	48.006	49.784	29	49.784	51.562	30	51.562	53.340	31	53.340	55.118	32	55.118	56.896	33	56.896	58.674	34	58.674	60.452	35	60.452	62.230	36	62.230	64.008	37	64.008	65.786	38	65.786	67.564	39	67.564	69.342	40	69.342	71.120	
Pin数	尺寸A	尺寸B																																																																																																																																	
1		1.778																																																																																																																																	
2	1.778	3.556																																																																																																																																	
3	3.556	5.334																																																																																																																																	
4	5.334	7.112																																																																																																																																	
5	7.112	8.890																																																																																																																																	
6	8.890	10.668																																																																																																																																	
7	10.668	14.446																																																																																																																																	
8	14.446	14.224																																																																																																																																	
9	14.224	16.002																																																																																																																																	
10	16.002	17.780																																																																																																																																	
11	17.780	19.558																																																																																																																																	
12	19.558	21.336																																																																																																																																	
13	21.336	23.114																																																																																																																																	
14	23.114	24.892																																																																																																																																	
15	24.892	26.670																																																																																																																																	
16	26.670	28.448																																																																																																																																	
17	28.448	30.226																																																																																																																																	
18	30.226	32.004																																																																																																																																	
19	32.004	33.782																																																																																																																																	
20	33.782	35.560																																																																																																																																	
21	35.560	37.338																																																																																																																																	
22	37.338	39.116																																																																																																																																	
23	39.116	40.894																																																																																																																																	
24	40.894	42.672																																																																																																																																	
25	42.672	44.450																																																																																																																																	
26	44.450	46.228																																																																																																																																	
27	46.228	48.006																																																																																																																																	
28	48.006	49.784																																																																																																																																	
29	49.784	51.562																																																																																																																																	
30	51.562	53.340																																																																																																																																	
31	53.340	55.118																																																																																																																																	
32	55.118	56.896																																																																																																																																	
33	56.896	58.674																																																																																																																																	
34	58.674	60.452																																																																																																																																	
35	60.452	62.230																																																																																																																																	
36	62.230	64.008																																																																																																																																	
37	64.008	65.786																																																																																																																																	
38	65.786	67.564																																																																																																																																	
39	67.564	69.342																																																																																																																																	
40	69.342	71.120																																																																																																																																	
C																																																																																																																																			
D																																																																																																																																			
E																																																																																																																																			
F	<table><tr><td colspan="5">R 17 9S-XXX X X-XX-X-XXX</td></tr><tr><td>① Series No:</td><td>② Pitch:</td><td>③ Tail&Mounting Style:</td><td>④ No. of Pins:</td><td>⑤ Insulator Color:</td></tr><tr><td>P=Pin Header</td><td>08=0.80</td><td>90=Right Angle DIP Type</td><td>Single Row Double Row</td><td>A:Black B:Brom C:Red</td></tr><tr><td>F=Female Header</td><td>10=1.00</td><td>9S=Straight SMT Type</td><td>101=1*1Pin 201=2*1Pin</td><td>D:Orange E:Yellow F:Green</td></tr><tr><td>B=Box Header</td><td>12=1.27</td><td>0D=Straight DIP Type</td><td>102=1*2Pin 202=2*2Pin</td><td>G:Blue H:Violet J:Gray</td></tr><tr><td>E=Ejector Header</td><td>17=1.778</td><td>0S=horizontal SMT Type</td><td>140=1*40pin 240=2*40pin</td><td>K:White P:Light Blue</td></tr><tr><td>R=Round Pin</td><td>20=2.00 25=2.54</td><td></td><td></td><td></td></tr></table>							R 17 9S-XXX X X-XX-X-XXX					① Series No:	② Pitch:	③ Tail&Mounting Style:	④ No. of Pins:	⑤ Insulator Color:	P=Pin Header	08=0.80	90=Right Angle DIP Type	Single Row Double Row	A:Black B:Brom C:Red	F=Female Header	10=1.00	9S=Straight SMT Type	101=1*1Pin 201=2*1Pin	D:Orange E:Yellow F:Green	B=Box Header	12=1.27	0D=Straight DIP Type	102=1*2Pin 202=2*2Pin	G:Blue H:Violet J:Gray	E=Ejector Header	17=1.778	0S=horizontal SMT Type	140=1*40pin 240=2*40pin	K:White P:Light Blue	R=Round Pin	20=2.00 25=2.54																																																																																												
R 17 9S-XXX X X-XX-X-XXX																																																																																																																																			
① Series No:	② Pitch:	③ Tail&Mounting Style:	④ No. of Pins:	⑤ Insulator Color:																																																																																																																															
P=Pin Header	08=0.80	90=Right Angle DIP Type	Single Row Double Row	A:Black B:Brom C:Red																																																																																																																															
F=Female Header	10=1.00	9S=Straight SMT Type	101=1*1Pin 201=2*1Pin	D:Orange E:Yellow F:Green																																																																																																																															
B=Box Header	12=1.27	0D=Straight DIP Type	102=1*2Pin 202=2*2Pin	G:Blue H:Violet J:Gray																																																																																																																															
E=Ejector Header	17=1.778	0S=horizontal SMT Type	140=1*40pin 240=2*40pin	K:White P:Light Blue																																																																																																																															
R=Round Pin	20=2.00 25=2.54																																																																																																																																		
G	<table><tr><td>⑥ Material Type:</td><td>⑦ Plating Type:</td><td>⑧ RoHS Request:</td><td>⑨ Customer Code</td></tr><tr><td>A=PBT</td><td>0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au</td><td>0:No Request</td><td></td></tr><tr><td>B=PA46</td><td>0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"</td><td>1:RoHS</td><td></td></tr><tr><td>C=PA6T</td><td>0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"</td><td>2:HF (Halogen Free)</td><td></td></tr><tr><td>D=PA9T</td><td>0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"</td><td></td><td></td></tr><tr><td>E=LCP</td><td>0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"</td><td></td><td></td></tr><tr><td></td><td>0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"</td><td></td><td></td></tr></table>							⑥ Material Type:	⑦ Plating Type:	⑧ RoHS Request:	⑨ Customer Code	A=PBT	0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au	0:No Request		B=PA46	0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"	1:RoHS		C=PA6T	0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"	2:HF (Halogen Free)		D=PA9T	0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"			E=LCP	0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"				0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"																																																																																																		
⑥ Material Type:	⑦ Plating Type:	⑧ RoHS Request:	⑨ Customer Code																																																																																																																																
A=PBT	0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au	0:No Request																																																																																																																																	
B=PA46	0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"	1:RoHS																																																																																																																																	
C=PA6T	0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"	2:HF (Halogen Free)																																																																																																																																	
D=PA9T	0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"																																																																																																																																		
E=LCP	0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u"																																																																																																																																		
	0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"																																																																																																																																		
H	<table><tr><td></td><td></td><td></td><td></td><td>GENERAL TOLERANCES</td><td>SCALE: 1:1</td><td>NAME</td><td>DATE</td><td rowspan="5">东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827</td><td>PART. NO:</td></tr><tr><td></td><td></td><td></td><td></td><td>LINEAR</td><td>ANGLES</td><td>APPROVED</td><td></td><td>KDRH-0029</td></tr><tr><td></td><td></td><td></td><td></td><td>0.0±0.25</td><td>X° REF±6°</td><td>DESIGNER</td><td></td><td>DWG. NO:</td></tr><tr><td></td><td></td><td></td><td></td><td>0.00±0.15</td><td>X° ±3°</td><td>DRAWN</td><td></td><td>ENDE4029</td></tr><tr><td>REV.</td><td>REVISION RECORD</td><td>DATE</td><td>UNIT: MM</td><td>0.000±0.08</td><td>X° X'±2°</td><td></td><td></td><td>REV: AO SHEET: 1/1</td></tr></table>											GENERAL TOLERANCES	SCALE: 1:1	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827	PART. NO:					LINEAR	ANGLES	APPROVED		KDRH-0029					0.0±0.25	X° REF±6°	DESIGNER		DWG. NO:					0.00±0.15	X° ±3°	DRAWN		ENDE4029	REV.	REVISION RECORD	DATE	UNIT: MM	0.000±0.08	X° X'±2°			REV: AO SHEET: 1/1																																																																														
				GENERAL TOLERANCES	SCALE: 1:1	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827	PART. NO:																																																																																																																										
				LINEAR	ANGLES	APPROVED			KDRH-0029																																																																																																																										
				0.0±0.25	X° REF±6°	DESIGNER			DWG. NO:																																																																																																																										
				0.00±0.15	X° ±3°	DRAWN			ENDE4029																																																																																																																										
REV.	REVISION RECORD	DATE	UNIT: MM	0.000±0.08	X° X'±2°				REV: AO SHEET: 1/1																																																																																																																										
	1	2	3	4	5	6	7	8																																																																																																																											

Specification:
Current Rating : 1AMP
Temperature Range : -40℃to+105℃
Contact Resistance : 20mΩ Max
Insulation Resistance : 1000MΩ Min
Withstanding Voltage : AC 500V
Material:
Insulator : Polyester (UL94V-0)
Standard:PA6T/LCP
Contact: Bronze
Plating : Au or Sn Over 50u" Ni