

1		2		3		4		5		6		7		8																																																																																																																																															
ROHS														For reference only																																																																																																																																															
A		<table><tr><td>Pin数</td><td>尺寸A</td><td>尺寸B</td></tr><tr><td>1</td><td></td><td>2.0</td></tr><tr><td>2</td><td>2.0</td><td>4.0</td></tr><tr><td>3</td><td>4.0</td><td>6.0</td></tr><tr><td>4</td><td>6.0</td><td>8.0</td></tr><tr><td>5</td><td>8.0</td><td>10.0</td></tr><tr><td>6</td><td>10.0</td><td>12.0</td></tr><tr><td>7</td><td>12.0</td><td>14.0</td></tr><tr><td>8</td><td>14.0</td><td>16.0</td></tr><tr><td>9</td><td>16.0</td><td>18.0</td></tr><tr><td>10</td><td>18.0</td><td>20.0</td></tr><tr><td>11</td><td>20.0</td><td>22.0</td></tr><tr><td>12</td><td>22.0</td><td>24.0</td></tr><tr><td>13</td><td>24.0</td><td>26.0</td></tr><tr><td>14</td><td>26.0</td><td>28.0</td></tr><tr><td>15</td><td>28.0</td><td>30.0</td></tr><tr><td>16</td><td>30.0</td><td>32.0</td></tr><tr><td>17</td><td>32.0</td><td>34.0</td></tr><tr><td>18</td><td>34.0</td><td>36.0</td></tr><tr><td>19</td><td>36.0</td><td>38.0</td></tr><tr><td>20</td><td>38.0</td><td>40.0</td></tr><tr><td>21</td><td>40.0</td><td>42.0</td></tr><tr><td>22</td><td>42.0</td><td>44.0</td></tr><tr><td>23</td><td>44.0</td><td>46.0</td></tr><tr><td>24</td><td>46.0</td><td>48.0</td></tr><tr><td>25</td><td>48.0</td><td>50.0</td></tr><tr><td>26</td><td>50.0</td><td>52.0</td></tr><tr><td>27</td><td>52.0</td><td>54.0</td></tr><tr><td>28</td><td>54.0</td><td>56.0</td></tr><tr><td>29</td><td>56.0</td><td>58.0</td></tr><tr><td>30</td><td>58.0</td><td>60.0</td></tr><tr><td>31</td><td>60.0</td><td>62.0</td></tr><tr><td>32</td><td>62.0</td><td>64.0</td></tr><tr><td>33</td><td>64.0</td><td>66.0</td></tr><tr><td>34</td><td>66.0</td><td>68.0</td></tr><tr><td>35</td><td>68.0</td><td>70.0</td></tr><tr><td>36</td><td>70.0</td><td>72.0</td></tr><tr><td>37</td><td>72.0</td><td>74.0</td></tr><tr><td>38</td><td>74.0</td><td>76.0</td></tr><tr><td>39</td><td>76.0</td><td>78.0</td></tr><tr><td>40</td><td>78.0</td><td>80.0</td></tr></table>														Pin数	尺寸A	尺寸B	1		2.0	2	2.0	4.0	3	4.0	6.0	4	6.0	8.0	5	8.0	10.0	6	10.0	12.0	7	12.0	14.0	8	14.0	16.0	9	16.0	18.0	10	18.0	20.0	11	20.0	22.0	12	22.0	24.0	13	24.0	26.0	14	26.0	28.0	15	28.0	30.0	16	30.0	32.0	17	32.0	34.0	18	34.0	36.0	19	36.0	38.0	20	38.0	40.0	21	40.0	42.0	22	42.0	44.0	23	44.0	46.0	24	46.0	48.0	25	48.0	50.0	26	50.0	52.0	27	52.0	54.0	28	54.0	56.0	29	56.0	58.0	30	58.0	60.0	31	60.0	62.0	32	62.0	64.0	33	64.0	66.0	34	66.0	68.0	35	68.0	70.0	36	70.0	72.0	37	72.0	74.0	38	74.0	76.0	39	76.0	78.0	40	78.0	80.0	A																		
Pin数	尺寸A	尺寸B																																																																																																																																																											
1		2.0																																																																																																																																																											
2	2.0	4.0																																																																																																																																																											
3	4.0	6.0																																																																																																																																																											
4	6.0	8.0																																																																																																																																																											
5	8.0	10.0																																																																																																																																																											
6	10.0	12.0																																																																																																																																																											
7	12.0	14.0																																																																																																																																																											
8	14.0	16.0																																																																																																																																																											
9	16.0	18.0																																																																																																																																																											
10	18.0	20.0																																																																																																																																																											
11	20.0	22.0																																																																																																																																																											
12	22.0	24.0																																																																																																																																																											
13	24.0	26.0																																																																																																																																																											
14	26.0	28.0																																																																																																																																																											
15	28.0	30.0																																																																																																																																																											
16	30.0	32.0																																																																																																																																																											
17	32.0	34.0																																																																																																																																																											
18	34.0	36.0																																																																																																																																																											
19	36.0	38.0																																																																																																																																																											
20	38.0	40.0																																																																																																																																																											
21	40.0	42.0																																																																																																																																																											
22	42.0	44.0																																																																																																																																																											
23	44.0	46.0																																																																																																																																																											
24	46.0	48.0																																																																																																																																																											
25	48.0	50.0																																																																																																																																																											
26	50.0	52.0																																																																																																																																																											
27	52.0	54.0																																																																																																																																																											
28	54.0	56.0																																																																																																																																																											
29	56.0	58.0																																																																																																																																																											
30	58.0	60.0																																																																																																																																																											
31	60.0	62.0																																																																																																																																																											
32	62.0	64.0																																																																																																																																																											
33	64.0	66.0																																																																																																																																																											
34	66.0	68.0																																																																																																																																																											
35	68.0	70.0																																																																																																																																																											
36	70.0	72.0																																																																																																																																																											
37	72.0	74.0																																																																																																																																																											
38	74.0	76.0																																																																																																																																																											
39	76.0	78.0																																																																																																																																																											
40	78.0	80.0																																																																																																																																																											
B																B																																																																																																																																													
C																C																																																																																																																																													
D																D																																																																																																																																													
E																E																																																																																																																																													
F		<table><tr><td colspan="14">R 20 9D-XXX X X-XX-X-XXX</td></tr><tr><td colspan="14">① Series No: P=Pin Header F=Female Header B=Box Header E=Ejector Header R=Round Pin</td></tr><tr><td colspan="14">② Pitch: 08=0.80 10=1.00 12=1.27 20=2.00 25=2.54 39=3.96 50=5.08</td></tr><tr><td colspan="14">③ Tail&Mounting Style: 90=Right Angle DIP Type 95=Straight SMT Type 00=Straight DIP Type 05=Horizontal SMT Type</td></tr><tr><td colspan="14">④ No. of Pins: Single Row Double Row 101=1*1Pin 201=2*1Pin 102=1*2Pin 202=2*2Pin 140=1*40pin 240=2*40pin</td></tr><tr><td colspan="14">⑤ Insulator Color: A:Black B:Brom C:Red D:Orange E:Yellow F:Green G:Blue H:Violet J:Gray K:White P:Light Blue</td></tr><tr><td colspan="14">⑥ Material Type: A=PBT B=PA46 C=PA6T D=PA9T E=LCP</td></tr><tr><td colspan="14">⑦ Plating Type: 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au 0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u" 0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u" 0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u" 0D-Sn-Au 4u" 0I-Sn-Au 40u" 0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"</td></tr><tr><td colspan="14">⑧ RoHS Request: 0:No Request 1:RoHS 2:HF (Halogen Free)</td></tr><tr><td colspan="14">⑨ Customer Code</td></tr></table>														R 20 9D-XXX X X-XX-X-XXX														① Series No: P=Pin Header F=Female Header B=Box Header E=Ejector Header R=Round Pin														② Pitch: 08=0.80 10=1.00 12=1.27 20=2.00 25=2.54 39=3.96 50=5.08														③ Tail&Mounting Style: 90=Right Angle DIP Type 95=Straight SMT Type 00=Straight DIP Type 05=Horizontal SMT Type														④ No. of Pins: Single Row Double Row 101=1*1Pin 201=2*1Pin 102=1*2Pin 202=2*2Pin 140=1*40pin 240=2*40pin														⑤ Insulator Color: A:Black B:Brom C:Red D:Orange E:Yellow F:Green G:Blue H:Violet J:Gray K:White P:Light Blue														⑥ Material Type: A=PBT B=PA46 C=PA6T D=PA9T E=LCP														⑦ Plating Type: 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au 0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u" 0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u" 0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u" 0D-Sn-Au 4u" 0I-Sn-Au 40u" 0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"														⑧ RoHS Request: 0:No Request 1:RoHS 2:HF (Halogen Free)														⑨ Customer Code														F	
R 20 9D-XXX X X-XX-X-XXX																																																																																																																																																													
① Series No: P=Pin Header F=Female Header B=Box Header E=Ejector Header R=Round Pin																																																																																																																																																													
② Pitch: 08=0.80 10=1.00 12=1.27 20=2.00 25=2.54 39=3.96 50=5.08																																																																																																																																																													
③ Tail&Mounting Style: 90=Right Angle DIP Type 95=Straight SMT Type 00=Straight DIP Type 05=Horizontal SMT Type																																																																																																																																																													
④ No. of Pins: Single Row Double Row 101=1*1Pin 201=2*1Pin 102=1*2Pin 202=2*2Pin 140=1*40pin 240=2*40pin																																																																																																																																																													
⑤ Insulator Color: A:Black B:Brom C:Red D:Orange E:Yellow F:Green G:Blue H:Violet J:Gray K:White P:Light Blue																																																																																																																																																													
⑥ Material Type: A=PBT B=PA46 C=PA6T D=PA9T E=LCP																																																																																																																																																													
⑦ Plating Type: 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au 0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u" 0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u" 0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u" 0D-Sn-Au 4u" 0I-Sn-Au 40u" 0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"																																																																																																																																																													
⑧ RoHS Request: 0:No Request 1:RoHS 2:HF (Halogen Free)																																																																																																																																																													
⑨ Customer Code																																																																																																																																																													
G		<table><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">GENERAL TOLERANCES</td><td colspan="2">SCALE: 1:1</td><td colspan="2">NAME</td><td colspan="2">DATE</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">LINEAR</td><td colspan="2">ANGLES</td><td colspan="2">APPROVED</td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">0.0±0.25</td><td colspan="2">X° REF±6°</td><td colspan="2">DESIGNER</td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">0.00±0.15</td><td colspan="2">X° ±3°</td><td colspan="2">DRAWN</td><td colspan="2"></td></tr><tr><td colspan="2">REV.</td><td colspan="2">REVISION RECORD</td><td colspan="2">DATE</td><td colspan="2">UNIT: MM</td><td colspan="2">SIZE: A4</td><td colspan="2">0.000±0.08</td><td colspan="2">X° X'±2°</td></tr></table>																				GENERAL TOLERANCES		SCALE: 1:1		NAME		DATE								LINEAR		ANGLES		APPROVED										0.0±0.25		X° REF±6°		DESIGNER										0.00±0.15		X° ±3°		DRAWN				REV.		REVISION RECORD		DATE		UNIT: MM		SIZE: A4		0.000±0.08		X° X'±2°		G																																																																							
						GENERAL TOLERANCES		SCALE: 1:1		NAME		DATE																																																																																																																																																	
						LINEAR		ANGLES		APPROVED																																																																																																																																																			
						0.0±0.25		X° REF±6°		DESIGNER																																																																																																																																																			
						0.00±0.15		X° ±3°		DRAWN																																																																																																																																																			
REV.		REVISION RECORD		DATE		UNIT: MM		SIZE: A4		0.000±0.08		X° X'±2°																																																																																																																																																	
H		<table><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">东莞市康导新能源科技有限公司</td><td colspan="2">PART. NO:</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD.</td><td colspan="2">KDRH-0035</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">Web: www.dgconne.com</td><td colspan="2">Tel: 0769-85337633</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">Email: 2850175986@qq.com</td><td colspan="2">Fax: 0769-85392827</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">TITLE:</td><td colspan="2">DWG. NO:</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">Pitch2.00mm Round Pin,Single Row, Plastic Height 2.8mm,Right Angle Type</td><td colspan="2">ENDE4035</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">REV: A0</td><td colspan="2">SHEET: 1/1</td></tr></table>																								东莞市康导新能源科技有限公司		PART. NO:														DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD.		KDRH-0035														Web: www.dgconne.com		Tel: 0769-85337633														Email: 2850175986@qq.com		Fax: 0769-85392827														TITLE:		DWG. NO:														Pitch2.00mm Round Pin,Single Row, Plastic Height 2.8mm,Right Angle Type		ENDE4035														REV: A0		SHEET: 1/1		H																															
										东莞市康导新能源科技有限公司		PART. NO:																																																																																																																																																	
												DONGGUANG KD NEW ENERGY TECHNOLOGY CO.,LTD.		KDRH-0035																																																																																																																																															
												Web: www.dgconne.com		Tel: 0769-85337633																																																																																																																																															
												Email: 2850175986@qq.com		Fax: 0769-85392827																																																																																																																																															
												TITLE:		DWG. NO:																																																																																																																																															
												Pitch2.00mm Round Pin,Single Row, Plastic Height 2.8mm,Right Angle Type		ENDE4035																																																																																																																																															
												REV: A0		SHEET: 1/1																																																																																																																																															
1		2		3		4		5		6		7		8																																																																																																																																															

Specification:
Current Rating : 1.5AMP
Temperature Range : -40℃to+105℃
Contact Resistance : 20mΩ Max
Insulation Resistance : 1000MΩ Min
Withstanding Voltage : AC 500V
Material:
Insulator : Polyester (UL94V-0)
Standard:PBT/PA6T/LCP
Contact: Brass
Plating : Au or Sn Over 50u" Ni