

1		2		3		4		5		6		7		8																																																																																																																												
ROHS													For reference only																																																																																																																													
A															A																																																																																																																											
B															B																																																																																																																											
C															C																																																																																																																											
D															D																																																																																																																											
E															E																																																																																																																											
F															F																																																																																																																											
G															G																																																																																																																											
H															H																																																																																																																											
<table><tr><td>Pin数</td><td>尺寸A</td><td>尺寸B</td></tr><tr><td>1</td><td></td><td>2.0</td></tr><tr><td>2</td><td>2.0</td><td>4.0</td></tr><tr><td>3</td><td>4.0</td><td>6.0</td></tr><tr><td>4</td><td>6.0</td><td>8.0</td></tr><tr><td>5</td><td>8.0</td><td>10.0</td></tr><tr><td>6</td><td>10.0</td><td>12.0</td></tr><tr><td>7</td><td>12.0</td><td>14.0</td></tr><tr><td>8</td><td>14.0</td><td>16.0</td></tr><tr><td>9</td><td>16.0</td><td>18.0</td></tr><tr><td>10</td><td>18.0</td><td>20.0</td></tr><tr><td>11</td><td>20.0</td><td>22.0</td></tr><tr><td>12</td><td>22.0</td><td>24.0</td></tr><tr><td>13</td><td>24.0</td><td>26.0</td></tr><tr><td>14</td><td>26.0</td><td>28.0</td></tr><tr><td>15</td><td>28.0</td><td>30.0</td></tr><tr><td>16</td><td>30.0</td><td>32.0</td></tr><tr><td>17</td><td>32.0</td><td>34.0</td></tr><tr><td>18</td><td>34.0</td><td>36.0</td></tr><tr><td>19</td><td>36.0</td><td>38.0</td></tr><tr><td>20</td><td>38.0</td><td>40.0</td></tr><tr><td>21</td><td>40.0</td><td>42.0</td></tr><tr><td>22</td><td>42.0</td><td>44.0</td></tr><tr><td>23</td><td>44.0</td><td>46.0</td></tr><tr><td>24</td><td>46.0</td><td>48.0</td></tr><tr><td>25</td><td>48.0</td><td>50.0</td></tr><tr><td>26</td><td>50.0</td><td>52.0</td></tr><tr><td>27</td><td>52.0</td><td>54.0</td></tr><tr><td>28</td><td>54.0</td><td>56.0</td></tr><tr><td>29</td><td>56.0</td><td>58.0</td></tr><tr><td>30</td><td>58.0</td><td>60.0</td></tr><tr><td>31</td><td>60.0</td><td>62.0</td></tr><tr><td>32</td><td>62.0</td><td>64.0</td></tr><tr><td>33</td><td>64.0</td><td>66.0</td></tr><tr><td>34</td><td>66.0</td><td>68.0</td></tr><tr><td>35</td><td>68.0</td><td>70.0</td></tr><tr><td>36</td><td>70.0</td><td>72.0</td></tr><tr><td>37</td><td>72.0</td><td>74.0</td></tr><tr><td>38</td><td>74.0</td><td>76.0</td></tr><tr><td>39</td><td>76.0</td><td>78.0</td></tr><tr><td>40</td><td>78.0</td><td>80.0</td></tr></table>															Pin数	尺寸A	尺寸B	1		2.0	2	2.0	4.0	3	4.0	6.0	4	6.0	8.0	5	8.0	10.0	6	10.0	12.0	7	12.0	14.0	8	14.0	16.0	9	16.0	18.0	10	18.0	20.0	11	20.0	22.0	12	22.0	24.0	13	24.0	26.0	14	26.0	28.0	15	28.0	30.0	16	30.0	32.0	17	32.0	34.0	18	34.0	36.0	19	36.0	38.0	20	38.0	40.0	21	40.0	42.0	22	42.0	44.0	23	44.0	46.0	24	46.0	48.0	25	48.0	50.0	26	50.0	52.0	27	52.0	54.0	28	54.0	56.0	29	56.0	58.0	30	58.0	60.0	31	60.0	62.0	32	62.0	64.0	33	64.0	66.0	34	66.0	68.0	35	68.0	70.0	36	70.0	72.0	37	72.0	74.0	38	74.0	76.0	39	76.0	78.0	40	78.0	80.0	
Pin数	尺寸A	尺寸B																																																																																																																																								
1		2.0																																																																																																																																								
2	2.0	4.0																																																																																																																																								
3	4.0	6.0																																																																																																																																								
4	6.0	8.0																																																																																																																																								
5	8.0	10.0																																																																																																																																								
6	10.0	12.0																																																																																																																																								
7	12.0	14.0																																																																																																																																								
8	14.0	16.0																																																																																																																																								
9	16.0	18.0																																																																																																																																								
10	18.0	20.0																																																																																																																																								
11	20.0	22.0																																																																																																																																								
12	22.0	24.0																																																																																																																																								
13	24.0	26.0																																																																																																																																								
14	26.0	28.0																																																																																																																																								
15	28.0	30.0																																																																																																																																								
16	30.0	32.0																																																																																																																																								
17	32.0	34.0																																																																																																																																								
18	34.0	36.0																																																																																																																																								
19	36.0	38.0																																																																																																																																								
20	38.0	40.0																																																																																																																																								
21	40.0	42.0																																																																																																																																								
22	42.0	44.0																																																																																																																																								
23	44.0	46.0																																																																																																																																								
24	46.0	48.0																																																																																																																																								
25	48.0	50.0																																																																																																																																								
26	50.0	52.0																																																																																																																																								
27	52.0	54.0																																																																																																																																								
28	54.0	56.0																																																																																																																																								
29	56.0	58.0																																																																																																																																								
30	58.0	60.0																																																																																																																																								
31	60.0	62.0																																																																																																																																								
32	62.0	64.0																																																																																																																																								
33	64.0	66.0																																																																																																																																								
34	66.0	68.0																																																																																																																																								
35	68.0	70.0																																																																																																																																								
36	70.0	72.0																																																																																																																																								
37	72.0	74.0																																																																																																																																								
38	74.0	76.0																																																																																																																																								
39	76.0	78.0																																																																																																																																								
40	78.0	80.0																																																																																																																																								
Specification: Current Rating : 1.5AMP Temperature Range : -40℃to+105℃ Contact Resistance : 20mΩ Max Insulation Resistance : 1000MΩ Min Withstanding Voltage : AC 500V Material: Insulator : Polyester (UL94V-0) Standard:PBT/PA6T/LCP Contact: Brass Plating : Au or Sn Over 50u" Ni																																																																																																																																										
R 20 9D-XXX X X-XX-X-XXX ① Series No: P=Pin Header 10=1.00 9S=Straight SMT Type 101=1*1Pin 201=2*1Pin 102=1*2Pin 202=2*2Pin 140=1*40pin 240=2*40pin ② Pitch: 08=0.80 9S=Straight SMT Type 101=1*1Pin 201=2*1Pin 102=1*2Pin 202=2*2Pin 140=1*40pin 240=2*40pin ③ Tail&Mounting Style: 9D=Right Angle DIP Type 101=1*1Pin 201=2*1Pin 102=1*2Pin 202=2*2Pin 140=1*40pin 240=2*40pin ④ No. of Pins: Single Row Double Row 101=1*1Pin 201=2*1Pin 102=1*2Pin 202=2*2Pin 140=1*40pin 240=2*40pin ⑤ Insulator Color: A:Black B:Brom C:Red D:Orange E:Yellow F:Green G:Blue H:Violet J:Gray K:White P:Light Blue ⑥ Material Type: A-PBT 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au B-PA46 0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u" C-PA6T 0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u" D-PA9T 0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u" E-LCP 0D-Sn-Au 4u" 0I-Sn-Au 40u" 0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u" ⑦ Plating Type: 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au ⑧ RoHS Request: 0:No Request 1:RoHS 2:HF (Halogen Free) ⑨ Customer Code																																																																																																																																										
<table><tr><td colspan="2">GENERAL TOLERANCES</td><td>SCALE: 1:1</td><td>NAME</td><td>DATE</td><td colspan="2">东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD.</td><td colspan="2">PART. NO: KDRH-0036</td></tr><tr><td colspan="2">LINEAR</td><td>ANGLES</td><td>APPROVED</td><td></td><td colspan="2">Web: www.dgconne.com Tel: 0769-85337633</td><td colspan="2">DWG. NO: ENDE4036</td></tr><tr><td colspan="2">0.0±0.25</td><td>X° REF±6°</td><td>DESIGNER</td><td></td><td colspan="2">Email: 2850175986@qq.com Fax: 0769-85392827</td><td colspan="2">REV: A0 SHEET: 1/1</td></tr><tr><td colspan="2">0.00±0.15</td><td>X° ±3°</td><td>DRAWN</td><td></td><td colspan="2">TITLE: Pitch2.00mm Round Pin,Single Row, Plastic Height 2.8mm,Right Angle Type</td><td colspan="2"></td></tr><tr><td colspan="2">0.000±0.08</td><td>X° X'±2°</td><td></td><td></td><td colspan="2"></td><td colspan="2"></td></tr></table>															GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD.		PART. NO: KDRH-0036		LINEAR		ANGLES	APPROVED		Web: www.dgconne.com Tel: 0769-85337633		DWG. NO: ENDE4036		0.0±0.25		X° REF±6°	DESIGNER		Email: 2850175986@qq.com Fax: 0769-85392827		REV: A0 SHEET: 1/1		0.00±0.15		X° ±3°	DRAWN		TITLE: Pitch2.00mm Round Pin,Single Row, Plastic Height 2.8mm,Right Angle Type				0.000±0.08		X° X'±2°																																																																																					
GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD.		PART. NO: KDRH-0036																																																																																																																																			
LINEAR		ANGLES	APPROVED		Web: www.dgconne.com Tel: 0769-85337633		DWG. NO: ENDE4036																																																																																																																																			
0.0±0.25		X° REF±6°	DESIGNER		Email: 2850175986@qq.com Fax: 0769-85392827		REV: A0 SHEET: 1/1																																																																																																																																			
0.00±0.15		X° ±3°	DRAWN		TITLE: Pitch2.00mm Round Pin,Single Row, Plastic Height 2.8mm,Right Angle Type																																																																																																																																					
0.000±0.08		X° X'±2°																																																																																																																																								
1		2		3		4		5		6		7		8																																																																																																																												