

	1	2	3	4	5	6	7	8																																																																																																																												
	ROHS							For reference only																																																																																																																												
A	<table><tr><td>Pin数</td><td>尺寸A</td><td>尺寸B</td></tr><tr><td>1</td><td></td><td>2.0</td></tr><tr><td>2</td><td>2.0</td><td>4.0</td></tr><tr><td>3</td><td>4.0</td><td>6.0</td></tr><tr><td>4</td><td>6.0</td><td>8.0</td></tr><tr><td>5</td><td>8.0</td><td>10.0</td></tr><tr><td>6</td><td>10.0</td><td>12.0</td></tr><tr><td>7</td><td>12.0</td><td>14.0</td></tr><tr><td>8</td><td>14.0</td><td>16.0</td></tr><tr><td>9</td><td>16.0</td><td>18.0</td></tr><tr><td>10</td><td>18.0</td><td>20.0</td></tr><tr><td>11</td><td>20.0</td><td>22.0</td></tr><tr><td>12</td><td>22.0</td><td>24.0</td></tr><tr><td>13</td><td>24.0</td><td>26.0</td></tr><tr><td>14</td><td>26.0</td><td>28.0</td></tr><tr><td>15</td><td>28.0</td><td>30.0</td></tr><tr><td>16</td><td>30.0</td><td>32.0</td></tr><tr><td>17</td><td>32.0</td><td>34.0</td></tr><tr><td>18</td><td>34.0</td><td>36.0</td></tr><tr><td>19</td><td>36.0</td><td>38.0</td></tr><tr><td>20</td><td>38.0</td><td>40.0</td></tr><tr><td>21</td><td>40.0</td><td>42.0</td></tr><tr><td>22</td><td>42.0</td><td>44.0</td></tr><tr><td>23</td><td>44.0</td><td>46.0</td></tr><tr><td>24</td><td>46.0</td><td>48.0</td></tr><tr><td>25</td><td>48.0</td><td>50.0</td></tr><tr><td>26</td><td>50.0</td><td>52.0</td></tr><tr><td>27</td><td>52.0</td><td>54.0</td></tr><tr><td>28</td><td>54.0</td><td>56.0</td></tr><tr><td>29</td><td>56.0</td><td>58.0</td></tr><tr><td>30</td><td>58.0</td><td>60.0</td></tr><tr><td>31</td><td>60.0</td><td>62.0</td></tr><tr><td>32</td><td>62.0</td><td>64.0</td></tr><tr><td>33</td><td>64.0</td><td>66.0</td></tr><tr><td>34</td><td>66.0</td><td>68.0</td></tr><tr><td>35</td><td>68.0</td><td>70.0</td></tr><tr><td>36</td><td>70.0</td><td>72.0</td></tr><tr><td>37</td><td>72.0</td><td>74.0</td></tr><tr><td>38</td><td>74.0</td><td>76.0</td></tr><tr><td>39</td><td>76.0</td><td>78.0</td></tr><tr><td>40</td><td>78.0</td><td>80.0</td></tr></table>								Pin数	尺寸A	尺寸B	1		2.0	2	2.0	4.0	3	4.0	6.0	4	6.0	8.0	5	8.0	10.0	6	10.0	12.0	7	12.0	14.0	8	14.0	16.0	9	16.0	18.0	10	18.0	20.0	11	20.0	22.0	12	22.0	24.0	13	24.0	26.0	14	26.0	28.0	15	28.0	30.0	16	30.0	32.0	17	32.0	34.0	18	34.0	36.0	19	36.0	38.0	20	38.0	40.0	21	40.0	42.0	22	42.0	44.0	23	44.0	46.0	24	46.0	48.0	25	48.0	50.0	26	50.0	52.0	27	52.0	54.0	28	54.0	56.0	29	56.0	58.0	30	58.0	60.0	31	60.0	62.0	32	62.0	64.0	33	64.0	66.0	34	66.0	68.0	35	68.0	70.0	36	70.0	72.0	37	72.0	74.0	38	74.0	76.0	39	76.0	78.0	40	78.0	80.0	A
Pin数	尺寸A	尺寸B																																																																																																																																		
1		2.0																																																																																																																																		
2	2.0	4.0																																																																																																																																		
3	4.0	6.0																																																																																																																																		
4	6.0	8.0																																																																																																																																		
5	8.0	10.0																																																																																																																																		
6	10.0	12.0																																																																																																																																		
7	12.0	14.0																																																																																																																																		
8	14.0	16.0																																																																																																																																		
9	16.0	18.0																																																																																																																																		
10	18.0	20.0																																																																																																																																		
11	20.0	22.0																																																																																																																																		
12	22.0	24.0																																																																																																																																		
13	24.0	26.0																																																																																																																																		
14	26.0	28.0																																																																																																																																		
15	28.0	30.0																																																																																																																																		
16	30.0	32.0																																																																																																																																		
17	32.0	34.0																																																																																																																																		
18	34.0	36.0																																																																																																																																		
19	36.0	38.0																																																																																																																																		
20	38.0	40.0																																																																																																																																		
21	40.0	42.0																																																																																																																																		
22	42.0	44.0																																																																																																																																		
23	44.0	46.0																																																																																																																																		
24	46.0	48.0																																																																																																																																		
25	48.0	50.0																																																																																																																																		
26	50.0	52.0																																																																																																																																		
27	52.0	54.0																																																																																																																																		
28	54.0	56.0																																																																																																																																		
29	56.0	58.0																																																																																																																																		
30	58.0	60.0																																																																																																																																		
31	60.0	62.0																																																																																																																																		
32	62.0	64.0																																																																																																																																		
33	64.0	66.0																																																																																																																																		
34	66.0	68.0																																																																																																																																		
35	68.0	70.0																																																																																																																																		
36	70.0	72.0																																																																																																																																		
37	72.0	74.0																																																																																																																																		
38	74.0	76.0																																																																																																																																		
39	76.0	78.0																																																																																																																																		
40	78.0	80.0																																																																																																																																		
B									B																																																																																																																											
C									C																																																																																																																											
D									D																																																																																																																											
E									E																																																																																																																											
F	<table><tr><td colspan="8">R 20 0D-XXX X X-XX-X-XXX</td></tr><tr><td colspan="8">① Series No: P=Pin Header 08=0.80 90=Right Angle DIP Type Single Row Double Row 101=1*1Pin 201=2*1Pin 102=1*2Pin 202=2*2Pin 140=1*40pin 240=2*40pin</td></tr><tr><td colspan="8">② Pitch: 08=0.80 9S=Straight SMT Type 10=1.00 9S=Straight SMT Type 12=1.27 0D=Straight DIP Type 20=2.00 0S=horizontal SMT Type 25=2.54 39=3.96 50=5.08</td></tr><tr><td colspan="8">③ Tail&Mounting Style: 90=Right Angle DIP Type 101=1*1Pin 102=1*2Pin 140=1*40pin 240=2*40pin</td></tr><tr><td colspan="8">④ No. of Pins: Single Row Double Row 101=1*1Pin 201=2*1Pin 102=1*2Pin 202=2*2Pin 140=1*40pin 240=2*40pin</td></tr><tr><td colspan="8">⑤ Insulator Color: A:Black B:Brom C:Red D:Orange E:Yellow F:Green G:Blue H:Violet J:Gray K:White P:Light Blue</td></tr><tr><td colspan="8">⑥ Material Type: A=PBT B=PA46 C=PA6T D=PA9T E=LCP 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au 0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u" 0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u" 0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u" 0D-Sn-Au 4u" 0I-Sn-Au 40u" 0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"</td></tr><tr><td colspan="8">⑦ Plating Type: 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au 0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u" 0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u" 0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u" 0D-Sn-Au 4u" 0I-Sn-Au 40u" 0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"</td></tr><tr><td colspan="8">⑧ RoHS Request: 0:No Request 1:RoHS 2:HF (Halogen Free)</td></tr><tr><td colspan="8">⑨ Customer Code</td></tr></table>								R 20 0D-XXX X X-XX-X-XXX								① Series No: P=Pin Header 08=0.80 90=Right Angle DIP Type Single Row Double Row 101=1*1Pin 201=2*1Pin 102=1*2Pin 202=2*2Pin 140=1*40pin 240=2*40pin								② Pitch: 08=0.80 9S=Straight SMT Type 10=1.00 9S=Straight SMT Type 12=1.27 0D=Straight DIP Type 20=2.00 0S=horizontal SMT Type 25=2.54 39=3.96 50=5.08								③ Tail&Mounting Style: 90=Right Angle DIP Type 101=1*1Pin 102=1*2Pin 140=1*40pin 240=2*40pin								④ No. of Pins: Single Row Double Row 101=1*1Pin 201=2*1Pin 102=1*2Pin 202=2*2Pin 140=1*40pin 240=2*40pin								⑤ Insulator Color: A:Black B:Brom C:Red D:Orange E:Yellow F:Green G:Blue H:Violet J:Gray K:White P:Light Blue								⑥ Material Type: A=PBT B=PA46 C=PA6T D=PA9T E=LCP 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au 0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u" 0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u" 0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u" 0D-Sn-Au 4u" 0I-Sn-Au 40u" 0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"								⑦ Plating Type: 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au 0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u" 0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u" 0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u" 0D-Sn-Au 4u" 0I-Sn-Au 40u" 0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"								⑧ RoHS Request: 0:No Request 1:RoHS 2:HF (Halogen Free)								⑨ Customer Code								F																																											
R 20 0D-XXX X X-XX-X-XXX																																																																																																																																				
① Series No: P=Pin Header 08=0.80 90=Right Angle DIP Type Single Row Double Row 101=1*1Pin 201=2*1Pin 102=1*2Pin 202=2*2Pin 140=1*40pin 240=2*40pin																																																																																																																																				
② Pitch: 08=0.80 9S=Straight SMT Type 10=1.00 9S=Straight SMT Type 12=1.27 0D=Straight DIP Type 20=2.00 0S=horizontal SMT Type 25=2.54 39=3.96 50=5.08																																																																																																																																				
③ Tail&Mounting Style: 90=Right Angle DIP Type 101=1*1Pin 102=1*2Pin 140=1*40pin 240=2*40pin																																																																																																																																				
④ No. of Pins: Single Row Double Row 101=1*1Pin 201=2*1Pin 102=1*2Pin 202=2*2Pin 140=1*40pin 240=2*40pin																																																																																																																																				
⑤ Insulator Color: A:Black B:Brom C:Red D:Orange E:Yellow F:Green G:Blue H:Violet J:Gray K:White P:Light Blue																																																																																																																																				
⑥ Material Type: A=PBT B=PA46 C=PA6T D=PA9T E=LCP 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au 0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u" 0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u" 0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u" 0D-Sn-Au 4u" 0I-Sn-Au 40u" 0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"																																																																																																																																				
⑦ Plating Type: 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au 0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u" 0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u" 0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u" 0D-Sn-Au 4u" 0I-Sn-Au 40u" 0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"																																																																																																																																				
⑧ RoHS Request: 0:No Request 1:RoHS 2:HF (Halogen Free)																																																																																																																																				
⑨ Customer Code																																																																																																																																				
G	<table><tr><td></td><td></td><td></td><td></td><td>GENERAL TOLERANCES</td><td>SCALE: 1:1</td><td>NAME</td><td>DATE</td><td rowspan="4">东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827</td><td rowspan="4">PART. NO: KDRH-0042 DWG. NO: ENDE4042 REV: AO SHEET: 1/1</td></tr><tr><td></td><td></td><td></td><td></td><td>LINEAR</td><td>ANGLES</td><td>APPROVED</td><td></td></tr><tr><td></td><td></td><td></td><td></td><td>0.0±0.25</td><td>X° REF±6°</td><td>DESIGNER</td><td></td></tr><tr><td></td><td></td><td></td><td></td><td>0.00±0.15</td><td>X° ±3°</td><td>DRAWN</td><td></td></tr><tr><td></td><td>REV.</td><td>REVISION RECORD</td><td>DATE</td><td>UNIT: MM</td><td>0.00±0.15</td><td>X° ±3°</td><td></td><td>TITLE: Pitch2.00mm Round Pin,Dual Row, Plastic Height 2.8mm,DIP</td><td></td></tr></table>												GENERAL TOLERANCES	SCALE: 1:1	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827	PART. NO: KDRH-0042 DWG. NO: ENDE4042 REV: AO SHEET: 1/1					LINEAR	ANGLES	APPROVED						0.0±0.25	X° REF±6°	DESIGNER						0.00±0.15	X° ±3°	DRAWN			REV.	REVISION RECORD	DATE	UNIT: MM	0.00±0.15	X° ±3°		TITLE: Pitch2.00mm Round Pin,Dual Row, Plastic Height 2.8mm,DIP		G																																																																															
				GENERAL TOLERANCES	SCALE: 1:1	NAME	DATE	东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827	PART. NO: KDRH-0042 DWG. NO: ENDE4042 REV: AO SHEET: 1/1																																																																																																																											
				LINEAR	ANGLES	APPROVED																																																																																																																														
				0.0±0.25	X° REF±6°	DESIGNER																																																																																																																														
				0.00±0.15	X° ±3°	DRAWN																																																																																																																														
	REV.	REVISION RECORD	DATE	UNIT: MM	0.00±0.15	X° ±3°		TITLE: Pitch2.00mm Round Pin,Dual Row, Plastic Height 2.8mm,DIP																																																																																																																												
H	1	2	3	4	5	6	7	8																																																																																																																												

Specification:
Current Rating : 1.5AMP
Temperature Range : -40℃to+105℃
Contact Resistance : 20mΩ Max
Insulation Resistance : 1000MΩ Min
Withstanding Voltage : AC 500V
Material:
Insulator : Polyester (UL94V-0)
Standard:PBT/PA6T/LCP
Contact: Bronze
Plating : Au or Sn Over 50u" Ni