


环保物料

Reference Informations:
*Used in 43812 Receptacle Housing



Ordering Information & Specifications

Part No	Wire Range	Insulation O. D.	Material	Finish
33812T 0P-**	AWG#28 -#24	0.8mm-1.4mm (1.4mm max)	Phosphor Bronze	Au or Sn
33812T 1P-**	AWG#24 -#20	1.2mm-2.6mm (2.6mm max)	Phosphor Bronze	Au or Sn
33812T 2P-**	AWG#20 -#16	1.8mm-2.8mm (2.8mm max)	Phosphor Bronze	Au or Sn
33812T 3P-**	AWG#16 -#14	2.4mm-3.4mm (3.4mm max)	Phosphor Bronze	Au or Sn

Unit: mm

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD 公司网址: www.dgkonne.cn 公司电话: 0769-85337633 邮箱: 2850175988@qq.com 公司传真: 0769-85392827	PART. NO: 33812T*P-**
				LINEAR	ANGLES	APPROVED				DWG. NO:
A0	新图面发行	2018.07.28		0.0±0.25	X° REF±6°	DESIGNER				ENDE05
REV.	REVISION RECORD	DATE		0.00±0.15	X° ±3°	DRAWN	肖丽娟	2018.07.28		REV: A0 SHEET: 1/1
			UNIT: MM	0.00±0.08	X° X'±2°				TITLE: 3.81mm pitch Crimp Terminal	