

The drawing illustrates a mechanical component with the following features and dimensions:

- Front View:** Shows a central vertical shaft with a circular feature at the top. Section lines A-A, B-B, and C-C are indicated.
- Top View:** Shows a circular cross-section with a central hole. The hole has a diameter of 0.15 mm.
- SECTION A-A:** A cross-section showing a U-shaped profile with a width of 1.40 mm and a height of 1.50 mm.
- SECTION B-B:** A cross-section showing a U-shaped profile with a width of 1.30 mm and a height of 1.10 mm.
- SECTION C-C:** A cross-section showing a rectangular profile with a width of 0.95 mm and a height of 0.75 mm.
- Other Dimensions:**
 - 0.55 mm: Distance from the top of the shaft to the first step.
 - 2.00 mm: Distance between the first and second steps.
 - 0.75 mm: Distance from the bottom of the shaft to the third step.
 - 3.00 mm: Total height of the shaft.
 - 2.75 mm: Distance from the bottom of the shaft to the top of the third step.
 - 0.30 mm: Thickness of the third step.
 - 5.60 mm: Total length of the component.

Unit: mm

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	 东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD 公司网址: www.dgconnr.cn 公司电话: 0769-85337633 邮 箱: 2850175988@qq.com 公司传真: 0769-85392827	PART. NO: 21255TOP-**	
				LINEAR	ANGLES					APPROVED	
				0.0±0.25	X° REF±6°	DESIGNER				ENDE05	
A0	新图面发行	2018.07.28		UNIT: MM	0.00±0.15	X° ±3°					TITLE: 1.25mm pitch Crimp Terminal
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	肖丽娟	2018.07.28	REV: A0 SHEET: 1/1		