

	1	2	3	4	5	6	7	8																																																																																																																											
A	ROHS						For reference only																																																																																																																												
B	<table><tr><th>Pin数</th><th>尺寸A</th><th>尺寸B</th></tr><tr><td>1</td><td></td><td>2.54</td></tr><tr><td>2</td><td>2.54</td><td>5.08</td></tr><tr><td>3</td><td>5.08</td><td>7.62</td></tr><tr><td>4</td><td>7.62</td><td>10.16</td></tr><tr><td>5</td><td>10.16</td><td>12.70</td></tr><tr><td>6</td><td>12.70</td><td>15.24</td></tr><tr><td>7</td><td>15.24</td><td>17.78</td></tr><tr><td>8</td><td>17.78</td><td>20.32</td></tr><tr><td>9</td><td>20.32</td><td>22.86</td></tr><tr><td>10</td><td>22.86</td><td>25.40</td></tr><tr><td>11</td><td>25.40</td><td>27.94</td></tr><tr><td>12</td><td>27.94</td><td>30.48</td></tr><tr><td>13</td><td>30.48</td><td>33.02</td></tr><tr><td>14</td><td>33.02</td><td>35.56</td></tr><tr><td>15</td><td>35.56</td><td>38.10</td></tr><tr><td>16</td><td>38.10</td><td>40.64</td></tr><tr><td>17</td><td>40.64</td><td>43.18</td></tr><tr><td>18</td><td>43.18</td><td>45.72</td></tr><tr><td>19</td><td>45.72</td><td>48.26</td></tr><tr><td>20</td><td>48.26</td><td>50.80</td></tr><tr><td>21</td><td>50.80</td><td>53.34</td></tr><tr><td>22</td><td>53.34</td><td>55.88</td></tr><tr><td>23</td><td>55.88</td><td>58.42</td></tr><tr><td>24</td><td>58.42</td><td>60.96</td></tr><tr><td>25</td><td>60.96</td><td>63.50</td></tr><tr><td>26</td><td>63.50</td><td>66.04</td></tr><tr><td>27</td><td>66.04</td><td>68.58</td></tr><tr><td>28</td><td>68.58</td><td>71.12</td></tr><tr><td>29</td><td>71.12</td><td>73.66</td></tr><tr><td>30</td><td>73.66</td><td>76.20</td></tr><tr><td>31</td><td>76.20</td><td>78.74</td></tr><tr><td>32</td><td>78.74</td><td>81.28</td></tr><tr><td>33</td><td>81.28</td><td>83.82</td></tr><tr><td>34</td><td>83.82</td><td>86.36</td></tr><tr><td>35</td><td>86.36</td><td>88.90</td></tr><tr><td>36</td><td>88.90</td><td>91.44</td></tr><tr><td>37</td><td>91.44</td><td>93.98</td></tr><tr><td>38</td><td>93.98</td><td>96.52</td></tr><tr><td>39</td><td>96.52</td><td>99.06</td></tr><tr><td>40</td><td>99.06</td><td>101.60</td></tr></table>						Pin数	尺寸A	尺寸B	1		2.54	2	2.54	5.08	3	5.08	7.62	4	7.62	10.16	5	10.16	12.70	6	12.70	15.24	7	15.24	17.78	8	17.78	20.32	9	20.32	22.86	10	22.86	25.40	11	25.40	27.94	12	27.94	30.48	13	30.48	33.02	14	33.02	35.56	15	35.56	38.10	16	38.10	40.64	17	40.64	43.18	18	43.18	45.72	19	45.72	48.26	20	48.26	50.80	21	50.80	53.34	22	53.34	55.88	23	55.88	58.42	24	58.42	60.96	25	60.96	63.50	26	63.50	66.04	27	66.04	68.58	28	68.58	71.12	29	71.12	73.66	30	73.66	76.20	31	76.20	78.74	32	78.74	81.28	33	81.28	83.82	34	83.82	86.36	35	86.36	88.90	36	88.90	91.44	37	91.44	93.98	38	93.98	96.52	39	96.52	99.06	40	99.06	101.60	技术规范: 额定电流 : 3AMP 适用温度 : -40℃to+105℃ 接触电阻 : 20mΩ Max 绝缘电阻 : 1000MΩ Min 耐电压 : AC 1000V 绝缘材料 : Polyester (UL94V-0) Standard:PA6T 端子材质 : Brass 电镀规范 : Au or Sn Over 50u" Ni	
Pin数							尺寸A	尺寸B																																																																																																																											
1		2.54																																																																																																																																	
2	2.54	5.08																																																																																																																																	
3	5.08	7.62																																																																																																																																	
4	7.62	10.16																																																																																																																																	
5	10.16	12.70																																																																																																																																	
6	12.70	15.24																																																																																																																																	
7	15.24	17.78																																																																																																																																	
8	17.78	20.32																																																																																																																																	
9	20.32	22.86																																																																																																																																	
10	22.86	25.40																																																																																																																																	
11	25.40	27.94																																																																																																																																	
12	27.94	30.48																																																																																																																																	
13	30.48	33.02																																																																																																																																	
14	33.02	35.56																																																																																																																																	
15	35.56	38.10																																																																																																																																	
16	38.10	40.64																																																																																																																																	
17	40.64	43.18																																																																																																																																	
18	43.18	45.72																																																																																																																																	
19	45.72	48.26																																																																																																																																	
20	48.26	50.80																																																																																																																																	
21	50.80	53.34																																																																																																																																	
22	53.34	55.88																																																																																																																																	
23	55.88	58.42																																																																																																																																	
24	58.42	60.96																																																																																																																																	
25	60.96	63.50																																																																																																																																	
26	63.50	66.04																																																																																																																																	
27	66.04	68.58																																																																																																																																	
28	68.58	71.12																																																																																																																																	
29	71.12	73.66																																																																																																																																	
30	73.66	76.20																																																																																																																																	
31	76.20	78.74																																																																																																																																	
32	78.74	81.28																																																																																																																																	
33	81.28	83.82																																																																																																																																	
34	83.82	86.36																																																																																																																																	
35	86.36	88.90																																																																																																																																	
36	88.90	91.44																																																																																																																																	
37	91.44	93.98																																																																																																																																	
38	93.98	96.52																																																																																																																																	
39	96.52	99.06																																																																																																																																	
40	99.06	101.60																																																																																																																																	
C																																																																																																																																			
D																																																																																																																																			
E																																																																																																																																			
F							R 25 9D-XXX X X-XX-X-XXX ① Series No: P=Pin Header F=Female Header B=Box Header E=Ejector Header R=Round Pin ② Pitch: 08=0.80 10=1.00 12=1.27 20=2.00 25=2.54 39=3.96 50=5.08 ③ Tail&Mounting Style: 9D=Right Angle DIP Type 9S=Straight SMT Type 0D=Straight DIP Type 0S=Horizontal SMT Type ④ No. of Pins: Single Row Double Row 101=1*1Pin 201=2*1Pin 102=1*2Pin 202=2*2Pin 140=1*40pin 240=2*40pin ⑤ Insulator Color: A:Black B:Brom C:Red D:Orange E:Yellow F:Green G:Blue H:Violet J:Gray K:White P:Light Blue																																																																																																																												
G	PCB LAYOUT						⑥ Material Type: A-PBT B-PA66 C-PA6T D-PA9T E-LCP ⑦ Plating Type: 0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au 0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u" 0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u" 0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u" 0D-Sn-Au 4u" 0I-Sn-Au 40u" 5D-Au 4u" 0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u" ⑧ RoHS Request: 0:No Request 1:RoHS 2:HF(Halogen Free) ⑨ Customer Code																																																																																																																												
H	<table><tr><td></td><td></td><td></td><td rowspan="4"></td><td colspan="2">GENERAL TOLERANCES</td><td>SCALE: 1:1</td><td rowspan="4">NAME</td><td rowspan="4">DATE</td><td rowspan="4"> 东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827 </td><td colspan="2">PART. NO: KDRH-0069</td></tr><tr><td></td><td></td><td></td><td>LINEAR</td><td>ANGLES</td><td>APPROVED</td><td></td><td></td></tr><tr><td></td><td></td><td></td><td>0.0±0.25</td><td>X° REF±6°</td><td>DESIGNER</td><td></td><td></td></tr><tr><td></td><td></td><td></td><td>0.00±0.15</td><td>X° ±3°</td><td>DRAWN</td><td></td><td></td></tr><tr><td>REV.</td><td colspan="2">REVISION RECORD</td><td>DATE</td><td>UNIT: MM</td><td>0.00±0.08</td><td>X° X'±2°</td><td colspan="3">TITLE: Pitch2.54mm Female Header,Single Row, Plastic Height 3.0mm,DIP</td><td>REV: A0</td><td>SHEET: 1/1</td></tr></table>										GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827	PART. NO: KDRH-0069					LINEAR	ANGLES	APPROVED						0.0±0.25	X° REF±6°	DESIGNER						0.00±0.15	X° ±3°	DRAWN			REV.	REVISION RECORD		DATE	UNIT: MM	0.00±0.08	X° X'±2°	TITLE: Pitch2.54mm Female Header,Single Row, Plastic Height 3.0mm,DIP			REV: A0	SHEET: 1/1																																																																													
				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	东莞市康号新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD. Web: www.dgconne.com Tel: 0769-85337633 Email: 2850175986@qq.com Fax: 0769-85392827		PART. NO: KDRH-0069																																																																																																																								
				LINEAR	ANGLES	APPROVED																																																																																																																													
				0.0±0.25	X° REF±6°	DESIGNER																																																																																																																													
				0.00±0.15	X° ±3°	DRAWN																																																																																																																													
REV.	REVISION RECORD		DATE	UNIT: MM	0.00±0.08	X° X'±2°	TITLE: Pitch2.54mm Female Header,Single Row, Plastic Height 3.0mm,DIP			REV: A0	SHEET: 1/1																																																																																																																								
	1	2	3	4	5	6	7	8																																																																																																																											